

WEST 1/4 CORNER SECTION 04, TOWNSHIP 16 SOUTH, RANGE 11 EAST

- 1) ON PAGE 299 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 15" X 2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 4 & 5-16-11 ON JANUARY 12, 1857. THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 41.30 CHAINS NORTH TO THE 17" X 10" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 4 & 5-16-11 ON THE 3RD STANDARD PARALLEL
 - 2) 40.00 CHAINS SOUTH TO THE 24" X 6" X 6" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 4, 5, 8 & 9-16-11

- 2) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, BY MATTHEW BROWN, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 77 RECORDED IN SURVEY BOOK "F" ON PAGES 100 TO 103 DATED APRIL 26 THROUGH JUNE 22, 1886, TO SUBDIVIDE SECTIONS 7, 8, 17 & 18 AND THE SOUTH 1/2 OF SECTION 5, ALL IN TOWNSHIP 16, RANGE 10, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 5-16-11 LYING LOOSE ON THE GROUND. HE APPARENTLY DID **NOT** RESET THE EAST 1/4 CORNER OF SECTION 5-16-11 ON THIS SURVEY.

- 3) AARON C. DAVIS, P.S. 1368, IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 18, 2015 FOR PROJECT NUMBER 15132-02, THE SURVEY OF A TRACT OF LAND IN THE SOUTH HALF OF SECTION 5-16-11 FOR JOHN WHITE, SURVEY F05001 IN THE SURVEY FILE FOR TOWNSHIP 16-11, SAID THAT HE FOUND NO PHYSICAL EVIDENCE OF THE NORTH-SOUTH POSITION FOR THE EAST 1/4 CORNER OF SECTION 5-16-11. HE DEEMED THAT THIS CORNER WAS **LOST**. **HE RESET** THIS CORNER ON LINE BETWEEN THE NORTHEAST AND SOUTHEAST SECTION CORNERS AND AT THE SAME DISTANCE AS THE SOUTHWEST CORNER TO THE WEST 1/4 CORNER OF SECTION 5. THE STONE WAS REPORTED TO BE "LAID OUT" IN 1886 IN A SURVEY BY M. BROWN [SURVEY BOOK F ON PAGE 100] AND NOT RESET ON THAT SURVEY. **HE SET A 1/2" X 24" IRON BARE WITH HIS "PS 1368" CAP** FOR THE EAST 1/4 CORNER OF SECTION 5-16-11. HIS SURVEY DRAWING SHOWS THAT THIS CORNER IS ALSO THE NORTHEAST CORNER OF GOVERNMENT LOT 3.
 - 1) 20.00' NE TO A 40 D NAIL IN A STEEL FENCE POST
 - 2) 6.50' ENE TO A 40 D NAIL IN A STEEL FENCE POST
 - 3) 10.50' SE TO A 40 D NAIL IN A STEEL FENCE POST
 - 4) 2.50' EAST TO A LINE OF FENCE RUNNING NORTH AND SOUTHHIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,271.48' SOUTH TO THE 1/2" X 24" REBAR WITH HIS "PS 1368" CAP HE SET FOR THE NORTHEAST CORNER OF GOVERNMENT LOT 4 ON THE EAST LINE OF SECTION 5-16-11
 - 2) 2,634.48' SOUTH TO THE 5/8" X 24" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHEAST CORNER OF SECTION 5-16-11 AND THE SOUTHEAST CORNER OF GOVERNMENT LOT 4
 - 3) 2,772.79' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHEAST CORNER OF SECTION 5-16-11 AND THE NORTHEAST CORNER OF GOVERNMENT

WEST QUARTER CORNER SECTION 04-16-11