

**NORTHWEST CORNER LOT 1 ON THE KANSAS INDIAN RESERVATION ON THE NORTH LINE OF THE NORTHEAST QUARTER OF SECTION 05, TOWNSHIP 16 SOUTH, RANGE 11 EAST**

1) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A ROAD SURVEY FOR ROAD 347 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 338 TO 340 PETITIONED BY CHARLES MOSS AND OTHERS FOR THE LOCATION OF A COUNTY ROAD IN TOWNSHIPS 15-11 AND 16-11 THAT HE SURVEYED ON DECEMBER 8, 1886, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD ON JANUARY 10, 1887 BY T. E. McMILLAN, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON MARCH 15, 1887 BY ROLAND LAKIN, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE INTERSECTION OF THE KAW RESERVE LINE WITH THE 3<sup>RD</sup> STANDARD PARALLEL ON THE NORTH LINE OF THE NORTHEAST 1/4 OF SECTION 5-16-11 ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS NORTH ON THE KAW RESERVE LINE FOR 10,507 FEET [HE NOTED THAT THIS DISTANCE WAS 118 FEET SHORT]]TO THE STONE HE FOUND AT THE INTERSECTION OF THE NORTH LINE OF SECTION 29-15-11, THEN CONTINUES NORTH ON THE KAW RESERVE LINE FOR 5,215 FEET TO THE STONE HE FOUND AT THE INTERSECTION OF THE KAW RESERVE LINE WITH THE NORTH LINE BETWEEN LYON AND WABAUNSEE COUNTY ON THE NORTH LINE OF THE NORTHEAST 1/4 OF SECTION 20-15-11
- 2) THIS ROAD EXTENDS SOUTH ON THE KAW RESERVE LINE FOR 1,150 FEET TO INTERSECT THE SANTA FE TRAIL AT THE END OF THIS ROAD SURVEY

2) AARON C. DAVIS, P.S. 1368, IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 18, 2015 FOR PROJECT NUMBER 15132-02, THE SURVEY OF A TRACT OF LAND IN THE SOUTH HALF OF SECTION 5-16-11 FOR JOHN WHITE, SURVEY F05001 IN THE SURVEY FILE FOR TOWNSHIP 16-11, SAID THAT HE SEARCHED FOR THE STONE AT THE NORTHWEST CORNER OF GOVERNMENT LOT 1 ON THE NORTH LINE OF THE NORTHEAST 1/4 OF SECTION 5-16-11 ON THE 3<sup>RD</sup> STANDARD PARALLEL, BUT THE STONE WAS **NOT** FOUND. HE DEEMED THAT THIS CORNER WAS BOTH **LOST AND OBLITERATED**. HE RESET THIS CORNER IN LINE WITH A FENCE TO THE NORTH EXTENDED FOR EAST-WEST POSITION, AND ON THE 3<sup>RD</sup> STANDARD PARALLEL [ON LINE BETWEEN THE SOUTH 1/4 CORNER AND THE SOUTHEAST CORNER OF SECTION 32-15-11] FOR NORTH-SOUTH POSITION. **HE SET A 1/2" X 24" IRON BAR WITH HIS "PS 1368" CAP** FOR THE NORTHWEST CORNER OF GOVERNMENT LOT 1 ON THE NORTH LINE OF THE NORTHEAST 1/4 OF SECTION 5-16-11 ON THE 3<sup>RD</sup> STANDARD PARALLEL.

- 1) IN LINE WITH A FENCE TO THE NORTH EXTENDED
- 2) 16.70' NE TO A CONCRETE NAIL & BOTTLECAP IN THE EAST GATE POST TO THE WEST
- 3) 9.20' NW TO A CONCRETE NAIL & BOTTLECAP IN THE EAST GATE POST TO THE EAST
- 4) 7.00' NORTH TO A CONCRETE NAIL & BOTTLECAP IN THE EAST CORNER POST
- 5) 6.50' NORTH TO A LINE OF FENCE TO THE EAST AND WEST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,567.46' EAST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE 5/8" X 24" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHEAST CORNER OF SECTION 6-16-11, BEING THE NORTHEAST CORNER OF GOVERNMENT LOT 1
- 2) 1,976.58' EAST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE 1/2" X 24" REBAR WITH HIS "PS 1368" CAP HE SET FOR THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 32-15-11
- 3) 664.71' WEST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE GLO STONE HE FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 32-15-11

HIS INFORMATION IS CONTINUED ON PAGE 2

- 4) 3,309.87' WEST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE 1/2" X 24" REBAR WITH HIS "PS 1368" CAP HE SET FOR THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 32-15-11
- 5) 4,037.11' SOUTH ON THE EAST BOUNDARY OF THE KANSAS RESERVE TO THE STONE SET BY BROWN HE FOUND AT THE NORTHEAST CORNER OF GOVERNMENT LOT 5
- 6) 5,373.00' SOUTH ON THE EAST BOUNDARY OF THE KANSAS RESERVE TO THE 1/2" X 24" REBAR WITH HIS "PS 1368" CAP HE SET FOR THE SOUTHEAST CORNER OF GOVERNMENT LOT 5

NORTHWEST CORNER LOT 1 NORTHEAST QUARTER SECTION 05-16-11