

WEST 1/4 CORNER SECTION 05, TOWNSHIP 16 SOUTH, RANGE 11 EAST

- 1) ON PAGE 305 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 12" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 5 & 6-16-11 ON MARCH 6, 1861.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.70 CHAINS NORTH TO THE 18" X 10" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 5 & 6-16-11 ON THE 3RD STANDARD PARALLEL
 - 2) 40.00 CHAINS SOUTH TO THE 18" X 14" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 5, 6, 7 & 8-16-11

- 2) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, BY MATTHEW BROWN, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 77 RECORDED IN SURVEY BOOK "F" ON PAGES 100 TO 103 DATED APRIL 26 THROUGH JUNE 22, 1886, TO SUBDIVIDE SECTIONS 7, 8, 17 & 18 AND THE SOUTH 1/2 OF SECTION 5, ALL IN TOWNSHIP 16, RANGE 10, SAID THAT **HE FOUND THE STONE IN GOOD CONDITION** AT THE WEST 1/4 CORNER OF SECTION 5-16-11 ON THIS SURVEY.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 19.88 CHAINS SOUTH TO THE STAKE HE SET FOR THE WEST 1/8TH CORNER OF THE SW1/4 OF SECTION 5-16-11
 - 2) 39.76 CHAINS SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 5-16-11
 - 3) 19.82-1/2 CHAINS EAST TO THE STAKE HE SET FOR THE NORTH 1/8TH CORNER OF THE SW1/4 OF SECTION 5-16-11
 - 4) 39.65 CHAINS EAST TO THE STONE HE FOUND AT THE CENTER CORNER OF SECTION 5-16-11

- 3) AARON C. DAVIS, P.S. 1368, IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 18, 2015 FOR PROJECT NUMBER 15132-02, THE SURVEY OF A TRACT OF LAND IN THE SOUTH HALF OF SECTION 5-16-11 FOR JOHN WHITE, SURVEY F05001 IN THE SURVEY FILE FOR TOWNSHIP 16-11, SAID THAT HE SEARCHED FOR THE LIMESTONE OF RECORD AT THE WEST 1/4 CORNER OF SECTION 5-16-11, AND **HE FOUND THE 18" X 12" X 4" GLO LIMESTONE** USING DISTANCES FROM A PRIOR SURVEY BY MATTHEW BROWN (1886) FILED IN SURVEY BOOK "F" AT PAGES 100-103 IN THE LYON COUNTY ENGINEERS OFFICE. **HE SET A 1/2" X 24" REBAR WITH HIS "PS 1368" CAP** ON THE NORTH SIDE OF THE LIMESTONE AT THE CENTER OF THE LIMESTONE.
 - 1) 2,724.22' NNE TO A 1/2" REBAR WITH "PS 1368" CAP AT THE SOUTHWEST CORNER OF SECTION 32-15-11 ON THE 3RD STANDARD PARALLEL
 - 2) 1,317.24' SOUTH TO A 1/2" REBAR WITH "PS 1368" CAP AT THE NORTHWEST CORNER OF THE SW1/4 OF THE SW1/4 OF SECTION 5-16-11
 - 3) 2,634.48' SOUTH TO A 1/2" REBAR WITH "PS 1368" CAP AT THE SOUTHWEST CORNER OF SECTION 5-16-11
 - 4) 1,884.34' SE TO A 1/2" REBAR WITH "PS 1368" CAP AT THE NORTHEAST CORNER OF THE SW1/4 OF THE SW1/4 OF SECTION 5-16-11
 - 5) 1/2" X 24" REBAR WITH "PS 1368" CAP ON THE NORTH SIDE OF LIMESTONE AT CENTER
 - 6) NO OTHER TIES AVAILABLEHIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,317.24' SOUTH TO THE 1/2" X 24" REBAR WITH HIS "PS 1368" CAP HE SET FOR THE NORTHWEST CORNER OF THE SW1/4 OF THE SW1/4 OF SECTION 5-16-11
 - 2) 2,634.48' SOUTH TO THE 1/2" X 24" REBAR WITH HIS "PS 1368" CAP HE SET FOR THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 5-16-11.

WEST QUARTER CORNER SECTION 05-16-11