

**WEST 1/6TH CORNER SOUTHWEST QUARTER OF SECTION 05, TOWNSHIP 16 SOUTH,
RANGE 11 EAST**

- 1) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, BY MATTHEW BROWN, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 77 RECORDED IN SURVEY BOOK "F" ON PAGES 100 TO 103 DATED APRIL 26 THROUGH JUNE 22, 1886, TO SUBDIVIDE SECTIONS 7, 8, 17 & 18 AND THE SOUTH 1/2 OF SECTION 5, ALL IN TOWNSHIP 16, RANGE 10, SAID THAT **HE SET A STAKE** FOR THE WEST 1/8TH CORNER OF THE SOUTHWEST 1/4 OF SECTION 5-16-11 ON LINE AND HALFWAY BETWEEN THE STONE THAT HE FOUND AT THE WEST 1/4 CORNER OF SECTION 5-16-11 AND THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 5-16-11.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 19.88 CHAINS NORTH TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 5-16-11
- 2) 19.88 CHAINS SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 5-16-11
- 2) AARON C. DAVIS, P.S. 1368, IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 18, 2015 FOR PROJECT NUMBER 15132-02, THE SURVEY OF A TRACT OF LAND IN THE SOUTH HALF OF SECTION 5-16-11 FOR JOHN WHITE, SURVEY F05001 IN THE SURVEY FILE FOR TOWNSHIP 16-11, SAID THAT HE SEARCHED FOR THE STONE AT THE WEST 1/16TH CORNER OF THE SOUTHWEST 1/4 OF SECTION 5-16-11 FROM THE SURVEY BY M. BROWN IN SURVEY BOOK "F" ON PAGE 100, BUT THE STONE WAS **NOT** FOUND. HE DEEMED THAT THIS CORNER WAS **LOST**. **HE RESET** THIS CORNER ON LINE AND AT HALF DISTANCE BETWEEN THE SOUTHWEST CORNER OF THE SOUTHWEST 1/4 AND THE NORTHWEST CORNER OF THE SOUTHWEST 1/4 OF SECTION 5. **HE SET A 1/2" X 24" IRON BAR WITH HIS "PS 1368" CAP** FOR THE WEST 1/16TH CORNER OF THE SOUTHWEST 1/4 OF SECTION 5-16-11.
- 1) 4.10' SSW TO A CONCRETE NAIL & BOTTLECAP IN A CORNER FENCE POST
- 2) 15.50' SW TO A CONCRETE NAIL & BOTTLECAP IN THE WEST GATE POST
- 3) 2.20' WEST TO A LINE OF FENCE TO THE SOUTH EXTENDED
- 4) 3.60' SOUTH TO A LINE OF FENCE TO THE EAST AND WEST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,317.24' NORTH TO THE GLO LIMESTONE HE FOUND AT THE NORTHWEST CORNER OF THE SW1/4 OF SECTION 5-16-11
- 2) 1,317.24' SOUTH TO THE 1/2" X 24" REBAR WITH HIS "PS 1368" CAP HE SET FOR THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 5-16-11
- 3) 1,318.92' EAST TO THE 1/2" X 24" REBAR WITH HIS "PS 1368" CAP HE SET FOR THE NORTHWEST CORNER OF THE SE1/4 OF THE SW1/4 OF SECTION 5-16-11, AS WITNESSED BY THE 1/2" X 24" REBAR WITH HIS "PS 1368" CAP HE SET AT 20' EAST AS A WITNESS CORNER ON THE EAST RIGHT-OF-WAY LINE OF COUNTY ROAD H2
- 4) 2,637.84' EAST TO THE MATTHEW BROWN STONE HE FOUND AT THE NORTHEAST CORNER OF THE SE1/4 OF THE SW1/4 OF SECTION 5-16-11
- 5) 3,662.48' EAST TO THE M. BROWN STONE HE FOUND AT THE NORTHEAST CORNER OF GOVERNMENT LOT 5 ON THE EAST BOUNDARY OF THE KANSAS RESERVE
- 6) 5,229.47' EAST TO THE 1/2" X 24" REBAR WITH HIS "PS 1368" CAP HE SET FOR THE NORTHEAST CORNER OF GOVERNMENT LOT 4 ON THE EAST LINE OF THE SE1/4 OF SECTION 5-16-11

WEST SIXTEENTH CORNER SOUTHWEST QUARTER 05-16-11