

NORTH 1/4 CORNER SECTION 08, TOWNSHIP 16 SOUTH, RANGE 11 EAST

- 1) ON PAGE 304 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 24" X 16" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 5 & 8-16-11.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS WEST TO THE 18" X 14" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 5, 6, 7 & 8-16-11
 - 2) 17.38 CHAINS EAST TO THE 17" X 14" X 2" LIMESTONE THEY SET ON THE EAST BOUNDARY OF THE KANSAS INDIAN RESERVATION
 - 3) 40.28 CHAINS EAST TO THE 24" X 6" X 6" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 4, 5, 8 & 9-16-11

 - 2) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, BY MATTHEW BROWN, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 77 RECORDED IN SURVEY BOOK "F" ON PAGES 100 TO 103 DATED APRIL 26 THROUGH JUNE 22, 1886, TO SUBDIVIDE SECTIONS 7, 8, 17 & 18 AND THE SOUTH 1/2 OF SECTION 5, ALL IN TOWNSHIP 16, RANGE 10, SAID THAT **HE FOUND THE STONE IN GOOD CONDITION** AT THE SOUTH 1/4 CORNER OF SECTION 5-16-11 ON THIS SURVEY.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 19.82-1/2 CHAINS WEST TO THE 24" X 12" X 2-1/2" STONE MARKED "1/8" ON THE WEST FACE HE SET FOR THE SOUTH 1/8TH CORNER OF THE SW1/4 OF SECTION 5-16-11
 - 2) 39.65 CHAINS WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 5-16-11

 - 3) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN SURVEY F08001 IN THE SURVEY FILE FOR TOWNSHIP 16-11 FOR A SURVEY OF THE WEST LINE OF THE EAST 1/2 OF THE NORTHWEST 1/4 AND THE SOUTHWEST 1/4 OF SECTION 8-16-11 FOR THE LYON COUNTY ROAD & BRIDGE DEPARTMENT [LYON COUNTY PROJECT 03-CN], DATED SEPTEMBER 9, 2003 FOR PROJECT NUMBER 03231-02, SAID THAT HE EXCAVATED FOR THE STONE AT THE NORTH 1/4 CORNER OF SECTION 8-16-11, BUT HE DID **NOT** FIND THE STONE. HE DID **NOT** RESET THE NORTH 1/4 CORNER OF SECTION 8-16-11 ON THIS SURVEY.

 - 4) AARON C. DAVIS, P.S. 1368, IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 18, 2015 FOR PROJECT NUMBER 15132-02, THE SURVEY OF A TRACT OF LAND IN THE SOUTH HALF OF SECTION 5-16-11 FOR JOHN WHITE, SURVEY F05001 IN THE SURVEY FILE FOR TOWNSHIP 16-11, SAID THAT THE STONE AT THE SOUTH 1/4 CORNER OF SECTION 5-16-11 WAS EXCAVATED FOR BY S. BROSEMER, P.S. 752, ON A PRIOR SURVEY IN 2003, BUT THE STONE WAS **NOT** FOUND AND THE CORNER WAS **NOT** RESET ON THAT SURVEY. HE DEEMED THAT THIS CORNER WAS BOTH **LOST AND OBLITERATED**. **HE RESET THIS CORNER BY A SPLIT OF THE ROAD RIGHT-OF-WAY FENCES FOR NORTH-SOUTH POSITION, AND A LINE PARALLEL WITH THE WEST LINE OF THE SOUTHWEST 1/4 FROM THE STONE FOUND AT THE NORTHEAST CORNER OF THE SOUTHWEST 1/4 OF THE SOUTHWEST 1/4 WAS USED FOR EAST-WEST POSITION PER THE PRIOR SURVEY BY MATTHEW BROWN, 1886, IN SURVEY BOOK "F" ON PAGE 100. HE SET A 5/8" X 24" IRON BAR WITH A LYON COUNTY CAP FOR THE SOUTH 1/4 CORNER OF SECTION 5-16-11. HIS SURVEY DRAWING SHOWS THAT THIS CORNER IS ALSO THE SOUTHWEST CORNER OF GOVERNMENT LOT 5.**
 - 1) 25.00' NW TO A CONCRETE NAIL & BOTTLECAP IN THE WEST GATE POST
 - 2) 19.00' NNE TO A CONCRETE NAIL & BOTTLECAP IN THE EAST GATE POST
 - 3) 22.80' SW TO A CONCRETE NAIL & BOTTLECAP IN THE WEST BRACE POST
- HIS TIES ARE CONTINUED ON PAGE 2

- 4) IN THE CENTERLINE OF THE TRAVELED WAY OF COUNTY ROAD 360 TO THE WEST EXTENDED

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,309.13' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE SOUTHWEST CORNER OF THE SE1/4 OF THE SW1/4 OF SECTION 5-16-11
- 2) 2,638.22' WEST TO THE 1/2" X 24" REBAR WITH HIS "PS 1368" CAP HE SET FOR THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 5-16-11
- 3) 1,008.13' EAST TO THE 1/2" X 24" REBAR WITH HIS "PS 1368" CAP HE SET FOR THE SOUTHEAST CORNER OF GOVERNMENT LOT 5 AND THE SOUTHWEST CORNER OF GOVERNMENT LOT 4 ON THE EAST BOUNDARY OF THE KANSAS RESERVE
- 4) 2,575.27' EAST TO THE 5/8" X 24" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHEAST CORNER OF SECTION 5-16-11 AND THE SOUTHEAST CORNER OF GOVERNMENT LOT 4

NORTH QUARTER CORNER SECTION 08-16-11