

**NORTH 1/6TH CORNER SOUTHWEST QUARTER OF SECTION 08, TOWNSHIP 16 SOUTH, RANGE 11 EAST**

- 1) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, BY MATTHEW BROWN, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 77 RECORDED IN SURVEY BOOK "F" ON PAGES 100 TO 103 DATED APRIL 26 THROUGH JUNE 22, 1886, TO SUBDIVIDE SECTIONS 7, 8, 17 & 18 AND THE SOUTH 1/2 OF SECTION 5, ALL IN TOWNSHIP 16, RANGE 11, SAID THAT **HE SET A 14" X 9" X 2" STONE MARKED "1/8"** FOR THE NORTHEAST CORNER OF THE WEST 1/2 OF THE SOUTHWEST 1/4 OF SECTION 8-16-11.

**HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:**

- 1) 17.79 CHAINS WEST TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 8-16-11
- 2) 20.00 CHAINS EAST TO THE STONE HE SET FOR THE CENTER CORNER OF SECTION 8-16-11
- 3) 19.87-1/2 CHAINS SOUTH TO THE 17" X 5" X 2-1/2" STONE MARKED "1/8" ON THE WEST FACE HE SET FOR THE CENTER CORNER OF THE SW1/4 OF SEC. 8-16-11
- 4) 39.75 CHAINS SOUTH TO THE 16" X 10" X 4" STONE MARKED "1/8" ON THE SOUTH FACE HE SET FOR THE SOUTH 1/16<sup>TH</sup> CORNER OF THE SW1/4 OF SECTION 8-16-11

- 2) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED SEPTEMBER 09, 2003, FOR PROJECT NUMBER 03231-02, SURVEY F08001 IN THE SURVEY FILE FOR TOWNSHIP 16-11 FOR A SURVEY OF THE WEST LINE OF THE EAST 1/2 OF THE NORTHWEST 1/4 AND THE SOUTHWEST 1/4 OF SECTION 8-16-11 FOR THE LYON COUNTY ROAD & BRIDGE DEPARTMENT FOR BRIDGE REPLACEMENT PROJECT 03-CN, SAID THAT HE EXCAVATED WITH A COUNTY MAINTAINER FOR THE STONE AT THE NORTH 1/16<sup>TH</sup> CORNER OF THE SOUTHWEST 1/4 OF SECTION 8-16-11, BUT HE DID **NOT** FIND THE STONE FROM THE PERMANENT SURVEY [1886] BY DEPUTY COUNTY SURVEYOR MATTHEW BROWN [SURVEY BOOK "F" ON PAGE 100 IN THE COUNTY ENGINEERS OFFICE, AND VOLUME 36 ON PAGE 488 IN THE REGISTER OF DEEDS OFFICE] DUE TO THE ROCK LEDGE. **HE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP** FOR THE NORTH 1/16<sup>TH</sup> CORNER OF THE SOUTHWEST 1/4 OF SECTION 8-16-11 ON LINE AND HALFWAY BETWEEN THE 1/16<sup>TH</sup> CORNERS ON THE NORTH SIDE OF THE NORTHWEST 1/4 OF SECTION 8-16-11 AND ON THE SOUTH SIDE OF THE SOUTHWEST 1/4 OF SECTION 8-16-11 AS PER THE NOTES AND PLAT FROM BROWN'S SURVEY.

- 1) 55.75' SW TO A 40 D NAIL & WASHER IN A 14" KENTUCKY COFFEE TREE
- 2) 57.95' SSE TO THE TOP CENTER OF THE EAST END OF AN 18" CORRUGATED METAL PIPE CULVERT
- 3) 19.0' EAST TO A LINE OF FENCE TO THE NORTH-SOUTH
- 4) 35.5' WEST TO A LINE OF FENCE TO THE NORTH-SOUTH
- 4) 9.0' WEST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "H2" NORTH-SOUTH

**HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**

- 1) 500.00' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR A P.O.T.
- 2) 1,300' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR A P.O.T.
- 3) 2,640.09' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET WHERE HE FOUND THE STONE REMAINS AT THE NORTHWEST CORNER OF THE W1/2 OF THE NW1/4 OF SECTION 8-16-11
- 4) 2,640.08' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHEAST CORNER OF THE W1/2 OF THE SW1/4 OF SECTION 8-16-11

NORTH SIXTEENTH CORNER SOUTHWEST QUARTER 08-16-11