

NORTHWEST CORNER SECTION 08, TOWNSHIP 16 SOUTH, RANGE 11 EAST

- 1) ON PAGE 304 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 14" X 5"** FOR THE CORNER TO SECTIONS 5, 6, 7 & 8-16-11 ON MARCH 6, 1861.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS NORTH TO THE 18" X 12" X 4" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 5 & 6-16-11
 - 2) 80.70 CHAINS NORTH TO THE 18" X 10" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 5 & 6-16-11 ON THE 3RD STANDARD PARALLEL
 - 3) 40.00 CHAINS EAST TO THE 24" X 16" X 11" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 5 & 8-16-11
 - 4) 57.38 CHAINS EAST TO THE 17" X 14" X 2" LIMESTONE THEY SET FOR THE CORNER TO FRACTIONAL SECTIONS 5 & 8-16-11 ON THE EASTERN BOUNDARY OF THE KANSAS INDIAN RESERVATION
 - 5) 80.28 CHAINS EAST TO THE 24" X 6" X 6" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 4, 5, 8 & 9-16-11
 - 6) 40.00 CHAINS SOUTH TO THE 15" X 12" 4" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 7 & 8-16-11
 - 7) 80.00 CHAINS SOUTH TO THE 30" X 10" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 7, 8, 17 & 18-16-11
 - 8) 40.00 CHAINS WEST TO THE 20" X 14" X 5" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 6 & 7-16-11
 - 9) 75.89 CHAINS WEST TO THE 18" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 6 & 7-16-11 ON THE WEST TOWNSHIP BOUNDARY

- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 72 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 290 TO 292 PETITIONED BY J. W. BOWERSOCK AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 16-10 AND 16-11 [PACKET 320 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JUNE 22, 1880, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD ON JULY 13, 1880, AND WAS RECORDED ON JULY 19, 1880 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 6-16-11 ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS WEST ON THE SECTION LINE FOR 6 MILES TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 5-16-10 TO COMMENCE THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 3 MILES TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 3-16-11 AT THE TERMINUS OF THIS ROAD SURVEY

- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE RIGHT SIDE PAGE 185 DATED JUNE 23, 1880, FOR A COUNTY ROAD IN TOWNSHIPS 16-10 & 16-11, APPARENTLY **FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 6-16-11 ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS WEST ON THE SECTION LINE FOR 6 MILES TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 5-16-10 TO COMMENCE THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 3 MILES TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 3-16-11 AT THE TERMINUS OF THIS ROAD SURVEY

CONTINUED ON PAGE 2

- 4) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, BY MATTHEW BROWN, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 77 RECORDED IN SURVEY BOOK "F" ON PAGES 100 TO 103 DATED APRIL 26 THROUGH JUNE 22, 1886, TO SUBDIVIDE SECTIONS 7, 8, 17 & 18 AND THE SOUTH 1/2 OF SECTION 5, ALL IN TOWNSHIP 16, RANGE 10, SAID THAT **HE FOUND THE STONE IN GOOD CONDITION** AT THE SOUTHWEST CORNER OF SECTION 5-16-11 ON THIS SURVEY. HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 19.88 CHAINS NORTH TO THE STAKE HE SET FOR THE WEST 1/8TH CORNER OF THE SW1/4 OF SECTION 5-16-11
 - 2) 39.76 CHAINS NORTH TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 5-16-11
 - 3) 19.82-1/2 CHAINS EAST TO THE 12" X 12" X 2-1/2" STONE MARKED "1/8" HE SET FOR THE SOUTH 1/8TH CORNER OF THE SW1/4 OF SECTION 5-16-11
 - 4) 39.65 CHAINS EAST TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 5-16-11
 - 5) 39.75 CHAINS SOUTH TO THE STAKE HE SET FOR THE WEST 1/4 CORNER OF SECTION 5-16-11
 - 6) 79.50 CHAINS SOUTH TO THE STAKE HE SET FOR THE SOUTHWEST CORNER OF SECTION 8-16-11
- 5) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN SURVEY F08001 IN THE SURVEY FILE FOR TOWNSHIP 16-11 FOR A SURVEY OF THE WEST LINE OF THE EAST 1/2 OF THE NORTHWEST 1/4 AND THE SOUTHWEST 1/4 OF SECTION 8-16-11 FOR THE LYON COUNTY ROAD & BRIDGE DEPARTMENT [LYON COUNTY PROJECT 03-CN], DATED SEPTEMBER 9, 2003 FOR PROJECT NUMBER 03231-02, SAID THAT HE EXCAVATED FOR THE STONE AT THE NORTHWEST CORNER OF SECTION 8-16-11, BUT HE DID **NOT** FIND THE STONE. HE DID **NOT** RESET THE NORTHWEST CORNER OF SECTION 8-16-11 ON THIS SURVEY.
- 6) AARON C. DAVIS, P.S. 1368, IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 18, 2015 FOR PROJECT NUMBER 15132-02, THE SURVEY OF A TRACT OF LAND IN THE SOUTH HALF OF SECTION 5-16-11 FOR JOHN WHITE, SURVEY F05001 IN THE SURVEY FILE FOR TOWNSHIP 16-11, SAID THAT HE SEARCHED FOR THE STONE AT THE SOUTHWEST CORNER OF SECTION 5-16-11, BUT THE STONE WAS **NOT** FOUND. HE DETERMINED THAT THIS CORNER WAS **OBLITERATED**. **HE RESET** THIS CORNER TO BE IN HARMONY WITH THE PHYSICAL EVIDENCE, I.E., IN LINE OF THE FENCES TO THE NORTH, SOUTH AND WEST AS THIS IS THE BEST EVIDENCE OF THE ORIGINAL LOCATION. **HE SET A 1/2" X 24" IRON BAR WITH HIS "PS 1368" CAP ON THE EAST SIDE OF A CORNER FENCE POST FOR FENCES TO THE NORTH, SOUTH AND WEST** FOR THE SOUTHWEST CORNER OF SEC. 5-16-11.
- 1) 20.35' SE TO A CONCRETE NAIL & BOTTLECAP IN A BRACE POST
 - 2) 16.30' NE TO A CONCRETE NAIL & BOTTLECAP IN A BRACE POST
 - 3) 18.50' SOUTH TO A LINE OF FENCE TO THE EAST
 - 4) 14.70' NORTH TO A LINE OF FENCE TO THE EAST
 - 5) IRON BAR FALLS ON THE EAST SIDE OF A CORNER FENCE POST FOR FENCES TO THE NORTH, SOUTH AND WEST
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 1,317.24' NORTH TO THE 1/2" X 24" REBAR WITH HIS "PS 1368" CAP HE SET FOR THE NORTHWEST CORNER OF THE SW1/4 OF THE SW1/4 OF SECTION 5-16-11
 - 2) 2,634.48' NORTH TO THE GLO STONE HE FOUND AT THE NORTHWEST CORNER OF THE SW1/4 OF SECTION 5-16-11
 - 3) 1,329.09' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE SOUTHWEST CORNER OF THE SE1/4 OF THE SW1/4 OF SECTION 5-16-11

HIS INFORMATION IS CONTINUED ON PAGE 3

- 4) 2,638.22' EAST TO THE 5/8" X 24" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 5-16-11, BEING THE SOUTHWEST CORNER OF GOVERNMENT LOT 5
- 5) 3,646.35' EAST TO THE 1/2" X 24" REBAR WITH HIS "PS 1368" CAP HE SET FOR THE SOUTHEAST CORNER OF GOVERNMENT LOT 5 ON THE EAST BOUNDARY OF THE KANSAS RESERVE, BEING THE SOUTHWEST CORNER OF GOVERNMENT LOT 4
- 6) 5,213.49' EAST TO THE 5/8" X 24" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHEAST CORNER OF SECTION 5-16-11, BEING THE SOUTHEAST CORNER OF GOVERNMENT LOT 5

NORTHWEST CORNER SECTION 08-16-11