

NORTHWEST CORNER SECTION 09, TOWNSHIP 16 SOUTH, RANGE 11 EAST

- 1) ON PAGE 298 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 24" X 6" X 6"** FOR THE CORNER TO SECTIONS 4, 5, 8 & 9-16-11 ON JANUARY 12, 1857.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS NORTH TO THE 20" X 15" X 2" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 4 & 5-16-11
 - 2) 81.30 CHAINS NORTH TO THE 17" X 10" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 4 & 5-16-11 ON THE 3RD STANDARD PARALLEL
 - 3) 40.00 CHAINS EAST TO THE 18" X 14" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 4 & 9-16-11
 - 4) 80.00 CHAINS EAST TO THE 23" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 3, 4, 9 & 10-16-11
 - 5) 22.90 CHAINS WEST TO THE 17" X 14" X 2" LIMESTONE THE SET FOR THE CORNER TO FRACTIONAL SECTIONS 5 & 8-16-11 ON THE EAST BOUNDARY OF THE KANSAS INDIAN RESERVATION
 - 6) 40.28 CHAINS WEST TO THE 24" X 6" X 4" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 5 & 8-16-11
 - 7) 80.28 CHAINS WEST TO THE 18" X 14" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 5, 6, 7 & 8-16-11
 - 8) 40.00 CHAINS SOUTH TO THE 20" X 16" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 8 & 9-16-11
 - 9) 80.00 CHAINS SOUTH TO THE 26" X 12" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 8, 9, 16 & 17-16-11

- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 72 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 290 TO 292 PETITIONED BY J. W. BOWERSOCK AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 16-10 AND 16-11 [PACKET 320 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JUNE 22, 1880, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD ON JULY 13, 1880, AND WAS RECORDED ON JULY 19, 1880 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 5-16-11 ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS WEST ON THE SECTION LINE FOR 7 MILES TO THE SOUTH-WEST CORNER OF SECTION 5-16-10 TO COMMENCE THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 2 MILES TO THE SOUTHEAST CORNER OF SECTION 3-16-11 TO THE TERMINUS OF THIS ROAD SURVEY

- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE RIGHT SIDE PAGE 185 DATED JUNE 23, 1880, FOR A COUNTY ROAD IN TOWNSHIPS 16-10 & 16-11, APPARENTLY **FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 5-16-11 ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 5-16-10 TO COMMENCE THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 3-16-11 TO THE TERMINUS OF THIS ROAD SURVEY

- 4) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, BY MATTHEW BROWN, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 77 RECORDED IN SURVEY BOOK "F" ON PAGES 100 TO 103 DATED APRIL 26 THROUGH JUNE 22, 1886, TO

SUBDIVIDE SECTIONS 7, 8, 17 & 18 AND THE SOUTH 1/2 OF SECTION 5, ALL IN TOWNSHIP 16, RANGE 10, SAID THAT **HE FOUND THE STONE LYING ON THE GROUND** AT THE SOUTHEAST CORNER OF SECTION 5-16-11 ON THIS SURVEY. HE DID **NOT** RESET THE SOUTHEAST CORNER OF SECTION 5-16-11 ON THIS SURVEY.

5) AARON C. DAVIS, P.S. 1368, IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 18, 2015 FOR PROJECT NUMBER 15132-02, THE SURVEY OF A TRACT OF LAND IN THE SOUTH HALF OF SECTION 5-16-11 FOR JOHN WHITE, SURVEY F05001 IN THE SURVEY FILE FOR TOWNSHIP 16-11, SAID THAT THE STONE AT THE SOUTHEAST CORNER OF SECTION 5-16-11 WAS REPORTED TO BE "LAYING ON THE GROUND" ON A PRIOR SURVEY BY MATTHEW BROWN IN 1886 IN SURVEY BOOK "F" ON PAGE 100. HE DEEMED THAT THIS CORNER WAS **OBLITERATED**. HE **RESET** THIS CORNER AT THE PHYSICAL EVIDENCE FOR THIS LOCATION, I.E., LINES OF FENCES TO THE NORTH, EAST AND WEST. THIS LOCATION IS IN HARMONY WITH THE PHYSICAL EVIDENCE OF THE ROAD ALONG THE SOUTH LINE OF THE SOUTHEAST 1/4 OF SECTION 4 EXTENDED TO THE WEST. **HE SET A 5/8" X 24" IRON BAR WITH A LYON COUNTY CAP** FOR THE SOUTHEAST CORNER OF SECTION 5-16-11. HIS SURVEY DRAWING SHOWS THAT THIS CORNER IS ALSO THE SOUTHEAST CORNER OF GOVERNMENT LOT 4.

- 1) IN LINE WITH A FENCE TO THE NORTH EXTENDED
- 2) IN LINE WITH A FENCE TO THE EAST AND WEST
- 3) 18.90' EAST TO THE NEAR FACE OF A PIPE POST AT THE GROUND
- 4) 0.90' NORTH TO A CONCRETE NAIL & BOTTLECAP IN THE WEST GATE POST
- 5) 26.50' NORTH TO A CONCRETE NAIL & BOTTLECAP IN THE NORTH BRACE POST
- 6) 8.70' WEST TO A CONCRETE NAIL & BOTTLECAP IN THE SOUTH GATE POST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,567.14' WEST TO THE 1/2" X 24" REBAR WITH HIS "PS 1368" CAP HE SET FOR THE SOUTHWEST CORNER OF GOVERNMENT LOT 4 ON THE EAST BOUNDARY OF THE KANSAS RESERVE, BEING THE SOUTHEAST CORNER OF GOVERNMENT LOT 5
- 2) 2,575.27' WEST TO THE 5/8" X 24" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 5-16-11, BEING THE SOUTHWEST CORNER OF GOVERNMENT LOT 5
- 3) 3,884.40' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE SOUTHWEST CORNER OF THE SE1/4 OF THE SW1/4 OF SECTION 5-16-11
- 4) 5,213.49' WEST TO THE 1/2" X 24" REBAR WITH HIS "PS 1368" CAP HE SET FOR THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 5-16-11
- 5) 1,363.00' NORTH TO THE 1/2" X 24" REBAR WITH HIS "PS 1368" CAP HE SET FOR THE NORTHEAST CORNER OF GOVERNMENT LOT 4
- 6) 2,634.48' NORTH TO THE 1/2" BY 24" REBAR WITH HIS "PS 1368" CAP HE SET FOR THE EAST 1/4 CORNER OF SECTION 5-16-11, BEING THE NORTHEAST CORNER OF GOVERNMENT LOT 3
- 7) 5,407.27' NORTH TO THE 5/8" X 24" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHEAST CORNER OF SECTION 5-16-11 ON THE 3RD STANDARD PARALLEL, BEING THE NORTHEAST CORNER OF GOVERNMENT LOT 1

NORTHWEST CORNER SECTION 09-16-11