

**NORTH 1/4 CORNER SECTION 10, TOWNSHIP 16 SOUTH, RANGE 11 EAST**

- 1) ON PAGE 294 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 16" X 14" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 3 & 10-16-11.  
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 39.87 CHAINS WEST TO THE 23" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 3, 4, 9 & 10-16-11
  - 2) 39.87 CHAINS EAST TO THE 21" X 10" X 6" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 2, 3, 10 & 11-16-11
  
- 2) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGES 139 & 140 DATED JANUARY 3-8, 1883 ORDERED BY GEORGE W. DeCAMP TO SURVEY SECTIONS 2, 3 & 4 IN TOWNSHIP 16, RANGE 11, SAID THAT **HE SET A STONE** FOR THE SOUTH 1/4 CORNER OF SECTION 3-16-11 BY DIVIDING THE DIFFERENCE BETWEEN HIS MEASUREMENT BETWEEN THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 3-16-11 AND THE STONE THAT HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 4-16-11 AND THE GOVERNMENT MEASUREMENT ON THIS **PERMANENT SURVEY**.  
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
  - 1) 39.56 CHAINS WEST TO THE STONE HE SET FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 3-16-11
  - 2) 79.24 CHAINS WEST TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 4-16-11
  - 3) 39.56 CHAINS EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 3-16-11
  - 4) 79.55 CHAINS EAST TO THE STONE HE SET FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 2-16-11
  - 5) 119.54 CHAINS EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 2-16-11
  - 6) 40.00 CHAINS NORTH TO THE STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 3-16-11
  - 7) 81.16 CHAINS NORTH TO THE STONE HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 3-16-11 ON THE 3<sup>RD</sup> STANDARD PARALLEL
  
- 3) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, BY MATTHEW BROWN, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 77 RECORDED IN SURVEY BOOK "F" ON PAGE 100 AND APRIL 26 THROUGH JUNE 22, 1886, TO SUBDIVIDE SECTIONS 7, 8, 17 & 18-16-11, SAID THAT **HE FOUND THE STONE IN GOOD CONDITION** AT THE SOUTH 1/4 CORNER OF SECTION 4-16-11 ON THIS SURVEY.
  
- 4) LLOYD J. DOBLER, L.S. 541, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 09, 1990, SURVEY F10002 IN THE SURVEY FILE FOR TOWNSHIP 16-11, FOR A SURVEY FOR PRICE RANCH IN SECTION 10-16-11 DATED MARCH 20, 1990 AND REVISED SEPTEMBER 26, 1990, SAID IN HIS *STATEMENT OF SURVEY* THAT HE DID **NOT** FIND THE STONE AT THE NORTH 1/4 CORNER OF SECTION 10-16-11. **HE SET A PIN** AT THE END POST OF A FENCE RUNNING SOUTH AND IN LINE WITH AN EAST-WEST FENCE FOR THE NORTH 1/4 CORNER OF SECTION 10-16-11. HIS SURVEY DRAWING SHOWS A "PIN IN PLACE" AT THE NORTH 1/4 CORNER OF SECTION 10-16-11.  
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 2,620.53' WEST TO THE 1/2" PIN HE SET FOR THE NORTHWEST CORNER OF SECTION 10-16-11
  - 2) 2,609.58' EAST TO THE "PIN IN PLACE" HE FOUND AT THE NORTHEAST CORNER OF SECTION 10016011

HIS INFORMATION IS CONTINUED ON PAGE 2

- 3) 2,645.12' SOUTH TO THE THEORETICAL POSITION FOR THE CENTER CORNER OF SECTION 10-16-11
  - 4) 5,286.30' SOUTH TO THE 1/2" PIN HE SET FOR THE SOUTH 1/4 CORNER OF SECTION 10-16-11
- 5) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 25, 2005, FOR PROJECT NUMBER 05289-02, SURVEY F10001 IN THE SURVEY FILE FOR TOWNSHIP 16-11 TO SURVEY THE SOUTH 1/2 OF THE SOUTHWEST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 10-16-11 FOR JACKIE WALL, SAID THAT HE SEARCHED FOR THE GLO STONE AT THE NORTH 1/4 CORNER OF SECTION 10-16-11, BUT DID **NOT** FIND THE STONE. HE DETERMINED THAT THE CORNER WAS **LOST** IN NORTH-SOUTH POSITION AND **OBLITERATED** IN EAST-WEST POSITION [I.E. IN LINE WITH FENCE TO SOUTH AND EAST]. **HE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP** FOR THE NORTH 1/4 CORNER OF SECTION 10-16-11.
- 1) IN LINE WITH A FENCE TO THE SOUTH
  - 2) IN LINE WITH A FENCE TO THE EAST EXTENDED
  - 3) 1.3' SOUTH TO A CONCRETE NAIL & WASHER IN CORNER FENCE POST [FENCES TO THE EAST, WEST AND SOUTH]
  - 4) 11.9' WSW TO A CONCRETE NAIL & WASHER IN A BRACE POST
  - 5) 33.75' ESE TO A CONCRETE NAIL & WASHER IN A GATE POST
  - 6) 1.5' SOUTH TO A LINE OF FENCE TO THE WEST
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,619.65' WEST TO THE 1/2" REBAR HE FOUND AT THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 10-16-10
  - 2) 2,611.83' EAST TO THE 1/2" REBAR HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 10-16-11
  - 3) 2,646.01' SOUTH TO THE THEORETICAL POSITION FOR THE NORTHEAST CORNER OF THE SW1/4 OF SECTION 10-16-11
  - 4) 5,287.47' SOUTH TO THE 1/2" REBAR HE FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 10-16-11

NORTH QUARTER CORNER SECTION 10-16-11