

WEST 1/4 CORNER SECTION 10, TOWNSHIP 16 SOUTH, RANGE 11 EAST

- 1) ON PAGE 294 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 14" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 9 & 10-16-11.
- 2) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGES 139 & 140 DATED JANUARY 3-8, 1883 ORDERED BY GEORGE W. DeCAMP TO SURVEY SECTIONS 2, 3 & 4 IN TOWNSHIP 16, RANGE 11, SAID THAT TO FIND THE TRUE LINE BETWEEN SECTIONS 3 & 4-16-11, HE TRACED THE LINE BETWEEN SECTIONS 9 & 10-16-11 AND HE FOUND THE TRUE COURSE TO BE 10°20', MEANING THAT HE APPARENTLY FOUND THE STONE AT THE WEST 1/4 CORNER OF SECTION 10-16-11 ON THIS **PERMANENT SURVEY**.
- 3) LLOYD J. DOBLER, L.S. 541, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 9, 1990, SURVEY F10002 IN THE SURVEY FILE FOR TOWNSHIP 16-11, FOR A SURVEY FOR PRICE RANCH IN SECTION 10-16-11 DATED MARCH 20, 1990 AND REVISED SEPTEMBER 26, 1990, SAID THAT HE EXCAVATED WITH A COUNTY GRADER FOR THE STONE AT THE WEST 1/4 CORNER OF SECTION 10-16-11, BUT HE DID **NOT** FIND THE STONE. HE CONSIDERED THAT THIS CORNER WAS **OBLITERATED**. **HE SET A 1/2" X 16" REBAR** FOR THE WEST 1/4 CORNER OF SECTION 10-16-11 IN THE CENTER OF THE RIGHT-OF-WAY, AND IN LINE WITH A FENCE TO THE EAST IN SECTION 10-16-11, AND A FENCE TO THE WEST IN SECTION 9-16-11.
 - 1) 32.8' SW TO A NAIL IN THE TOP OF A FENCE POST
 - 2) 26.0' NE TO A NAIL IN THE NORTH GATE POST
 - 3) 19.3' EAST TO A NAIL IN WEST FACE OF A POWER POLE

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

 - 1) 2,649.93' NORTH TO THE 1/2" PIN HE SET FOR THE NORTHWEST CORNER OF SECTION 10-16-11
 - 2) 2,636.16' SOUTH TO THE 1/2" PIN HE SET FOR THE SOUTHWEST CORNER OF SECTION 10-16-11 [**NOTE:** HIS *STATEMENT OF SURVEY* SHOWS THAT **HE SET A RAILROAD SPIKE** AT THIS CORNER – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]
 - 3) 2,635.74' EAST TO THE THEORETICAL POSITION FOR THE CENTER CORNER OF SECTION 10-16-11
 - 4) 5,241.16' EAST TO THE "PIN IN PLACE" HE FOUND AT THE EAST 1/4 CORNER OF SECTION 10-16-11
- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 25, 2005, FOR PROJECT NUMBER 05289-02, SURVEY F10001 IN THE SURVEY FILE FOR TOWNSHIP 16-11 TO SURVEY THE SOUTH 1/2 OF THE SOUTHWEST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 10-16-11 FOR JACKIE WALL, SAID THAT **HE FOUND THE 1/2" REBAR** AT THE WEST 1/4 CORNER OF SECTION 10-16-11 FROM EXISTING REFERENCE TIES ON FILE AT THE COUNTY ENGINEER'S OFFICE FROM LLOYD DOBLER, L.S. 541, IN 1990.
 - 1) 28.6' NE TO A NAIL & SHINER IN THE TOP OF A GATE POST
 - 2) 19.6' EAST TO A NAIL & SHINER IN A POWER POLE
 - 3) 38.95' NW TO A NAIL & SHINER IN THE TOP OF A LONE POST
 - 4) IN LINE WITH THE FENCE TO THE EAST
 - 5) 1.0' EAST TO THE CENTERLINE OF TRAVELED WAY OF COUNTY ROAD "K" NORTH-SOUTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

 - 1) 2,605.10' NORTH TO THE 1/2" REBAR HE FOUND AT THE NORTHWEST CORNER OF THE NW1/4 OF SECTION OF SECTION 10-16-11

HIS INFORMATION IS CONTINUED ON PAGE 2

- 2) 1,318.15' SOUTH TO THE THEORETICAL POSITION FOR THE WEST 1/16TH CORNER OF THE SW1/4 OF SECTION 10-16-11
 - 3) 2,636.31' SOUTH TO THE RAILROAD SPIKE HE FOUND AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 10-16-11
 - 4) 1,317.73' EAST TO THE THEORETICAL POSITION FOR THE NORTH 1/16TH CORNER OF THE SW1/4 OF SECTION 10-16-11
 - 5) 2,635.46' EAST TO THE THEORETICAL POSITION FOR THE NORTHEAST CORNER OF THE SW1/4 OF SECTION 10-16-11
 - 6) 5,241.30' EAST TO THE 1/2" REBAR HE FOUND AT THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 10-16-11
- 5) JAMES A. BRULL, L.S. 1475, ASSISTANT COUNTY ENGINEER AND DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED AUGUST 20, 2008 FOR LYON COUNTY PROJECT NUMBER 08-RV, SAID THAT **HE FOUND THE 1/2" REBAR** AT THE WEST 1/4 CORNER OF SECTION 10-16-11 FROM EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE FROM STEVEN S. BROSEMER, L.S. 752, IN 2005. **HE PLACED A LYON COUNTY CAP ON THE REBAR.**
- 1) 28.60' NE TO A NAIL & SHINER FOUND IN THE TOP OF A GATE POT
 - 2) 19.60' EAST TO A NAIL & SHINER FOUND IN A POWER POLE
 - 3) 38.90' NW TO A NAIL & SHINER FOUND IN THE TOP OF A LONE POST
 - 4) IN LINE WITH A FENCE TO THE EAST
 - 5) 2' EAST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "K" NORTH-SOUTH

WEST QUARTER CORNER SECTION 10-16-11