

WEST 1/4 CORNER SECTION 11, TOWNSHIP 16 SOUTH, RANGE 11 EAST

- 1) ON PAGE 291 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 12" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 10 & 11-16-11 ON JANUARY 5, 1857.
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS NORTH TO THE 21" X 10" X 6" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 2, 3, 10 & 11-16-11
 - 2) 40.00 CHAINS SOUTH TO THE 23" X 12" X 6" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 10, 11, 14 & 15-16-11

- 2) LLOYD J. DOBLER, L.S. 541, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 9, 1990, SURVEY F10002 IN THE SURVEY FILE FOR TOWNSHIP 16-11, FOR A SURVEY FOR PRICE RANCH IN SECTION 10-16-11 DATED MARCH 20, 1990 AND REVISED SEPTEMBER 26, 1990, SAID THAT THAT **HE FOUND A 1/2" IRON PIN THAT WAS SET BY OTHERS** AT THE EAST 1/4 CORNER OF SECTION 10-16-11.
 - 1) 54.6' TO A SPIKE IN THE TOP OF A POLE TO THE EAST
 - 2) 38.4' NW TO A SPIKE IN THE TOP OF THE NORTH GATE POST
 - 3) 29.4' WEST TO A SPIKE IN THE TOP OF A FENCE POST
 - 4) IN LINE WITH A FENCE TO THE EAST AND WESTHIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,605.42' WEST TO THE THEORETICAL LOCATION FOR THE CENTER CORNER OF SECTION 10-16-11
 - 2) 5,241.16' WEST TO THE 1/2" PIN HE SET FOR THE WEST 1/4 CORNER OF SECTION 10-16-11
 - 3) 2,640.33' NORTH TO THE "PIN IN PLACE" HE FOUND AT THE NORTHEAST CORNER OF SECTION 10-16-11
 - 4) 2,640.65' SOUTH TO THE "PIN IN PLACE" HE FOUND AT THE SOUTHEAST CORNER OF SECTION 10-16-11

- 3) LLOYD J. DOBLER, L.S. 541, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 16, 1990, AND REVISED AUGUST 1990, FOR THE PRICE RANCH SURVEY, LARGE SURVEY SR #10001 IN THE SURVEY DRAWER FOR TOWNSHIP 16-11, SHOWS ON HIS DRAWING THAT **HE SET A PIN** FOR THE EAST 1/4 CORNER OF SECTION 10-16-11 ON THIS SURVEY.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,605.42' WEST TO THE THEORETICAL LOCATION FOR THE CENTER CORNER OF SECTION 10-16-11
 - 2) 1,320.32' SOUTH TO THE PIN HE SET FOR THE EAST 1/16TH CORNER OF THE SE1/4 OF SECTION 10-16-11
 - 3) 2,640.64' SOUTH TO THE "PIN ON STONE" HE FOUND AT THE SOUTHEAST CORNER OF SECTION 10-16-11

- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED AUGUST 16, 2002, FOR PROJECT NUMBER 02233-02, SURVEY F11002 IN THE SURVEY FILE FOR TOWNSHIP 16-11 FOR A 76.71 ACRE TRACT LOCATED IN THE SOUTHEAST AND SOUTHWEST QUARTERS OF SECTION 11-16-11, SAID THAT **HE FOUND THE 1/2" REBAR** AT THE WEST 1/4 CORNER OF SECTION 11-16-11 FROM EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE BY LLOYD J. DOBLER, L.S. 541 IN AUGUST 1990.
 - 1) 0.7' DEEP IN THE GRAVEL ROAD
 - 2) 2.5' EAST TO THE CENTERLINE TRAVELED WAY OF THE ROAD NORTH-SOUTH
 - 3) IN LINE WITH A FENCE TO THE EAST
 - 4) IN LINE WITH A FENCE TO THE WEST

HIS TIES ARE CONTINUED ON PAGE 2

- 5) 20.7' WEST TO A CONCRETE NAIL & WASHER IN THE SIDE OF A CORNER FENCE POST
- 6) 38.0' WNW TO A CONCRETE NAIL & WASHER IN A GATE POST
- 7) 65.1' SE TO A 40 D SPIKE & WASHER IN THE NORTHWEST MULBERRY TREE IN A GROUP OF 4 TREES

HIS SURVEY DRAWING SHOWS THE FOLLOWING DISTANCES:

- 1) 5,280.81' EAST TO THE 1/2" REBAR HE FOUND AT THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 11-16-11
- 2) 2,640.10' SOUTH TO THE SQUARE #4 REBAR OVER THE STONE HE FOUND AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 11-16-11

- 5) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 25, 2005, FOR PROJECT NUMBER 05289-02, SURVEY F10001 IN THE SURVEY FILE FOR TOWNSHIP 16-11 TO SURVEY THE SOUTH 1/2 OF THE SOUTHWEST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 10-16-11 FOR JACKIE WALL, SAID THAT **HE FOUND THE 1/2" REBAR** AT THE EAST 1/4 CORNER OF SECTION 10-16-11 FROM EXISTING REFERENCE TIES ON FILE AT THE COUNTY ENGINEER'S OFFICE FROM LLOYD DOBLER, L.S. 541, IN 1990.

- 1) REBAR IS 0.7' DEEP IN THE GRAVEL ROAD
- 2) 38.4' NW TO A CONCRETE NAIL & SHINER IN THE TOP OF A GATE POST
- 3) 28.7' WEST TO A CONCRETE NAIL & SHINER IN THE SIDE OF A CORNER FENCE POST
- 4) IN LINE WITH A FENCE TO THE EAST
- 5) IN LINE WITH A FENCE TO THE WEST
- 6) 2.0' EAST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "L" NORTH-SOUTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,605.84' WEST TO THE THEORETICAL POSITION FOR THE CENTER CORNER OF SECTION 10-16-11
- 2) 5,241.30' WEST TO THE 1/2" REBAR HE FOUND AT THE NORTHWEST CORNER OF THE SW1/4 OF SECTION 10-16-11
- 3) 2,641.95' NORTH TO THE 1/2" REBAR HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 10-16-11

- 6) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED AUGUST 22, 2016, FOR PROJECT NUMBER 16205-02-02, SURVEY F11003 IN THE SURVEY FILE FOR TOWNSHIP 16-11, TO SURVEY A TRACT IN THE NORTH HALF OF SECTION 11-16-11 FOR PETE WHEAT, SAID THAT **HE FOUND THE EXISTING RECORD 5/8" REBAR** AT THE WEST 1/4 CORNER OF SECTION 11-16-11 FROM HIS EXISTING REFERENCE TIES ON FILE AT THE COUNTY SURVEYORS OFFICE. HE NOTED THAT HE HAD PREVIOUSLY IDENTIFIED THIS MONUMENT AS A 1/2" REBAR IN 2002. THIS CORNER IS THE SOUTHWEST CORNER OF THE SURVEYED TRACT.

- 1) 29.7' WEST TO THE TOP OF A PIPE CORNER FENCE POST
- 2) 53.2' ENE TO THE TOP OF A PIPE BRACE FENCE POST
- 3) 52.1' EAST TO THE TOP OF A CORNER FENCE PIPE POST
- 4) 46.0' NW TO THE TOP OF A BRACE POST PIPE
- 5) IN LINE WITH A FENCE TO THE WEST EXTENDED
- 6) IN LINE WITH A FENCE TO THE EAST EXTENDED

HIS REPORT OF SURVEY SHOWS THE FOLLOWING INFORMATION:

- 1) 2,641.87' NORTH TO THE 1/2" REBAR HE FOUND AT THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 11-16-11 FROM REFERENCE TIES, BEING THE NORTHWEST CORNER OF THE SURVEYED TRACT
- 2) 3,014.00' EAST TO THE 1/2" X 24" REBAR WITH HIS "PS 752" CAP HE SET FOR THE SOUTHEAST CORNER OF THE SURVEYED TRACT

HIS INFORMATION IS CONTINUED ON PAGE 3

- 3) 5,280.66' EAST TO THE 5/8" REBAR HE FOUND AT THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 11-16-11 FROM REFERENCE TIES

WEST QUARTER CORNER SECTION 11-16-11