

WEST 1/4 CORNER SECTION 12, TOWNSHIP 16 SOUTH, RANGE 11 EAST

- 1) ON PAGE 287 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 16" X 2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 11 & 12-16-11 ON JANUARY 2, 1857. THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS NORTH TO THE 25" X 13" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 1, 2, 11 & 12-16-11
 - 2) 40.00 CHAINS SOUTH TO THE 22" X 11" X 6" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 11, 12, 13 & 14-16-11

- 2) MARTIN G. LONG, L.S 1081, IN A REPORT DATED AUGUST 17, 1998, FOR KDOT PROJECT 56-56-K-1088-01, THE BRIDGE REPLACEMENT ON HILL CREEK ON HIGHWAY 56, PLAT OF SURVEY 97-22S AND SURVEY F11001 IN THE SURVEY FILE FOR TOWNSHIP 16-11, APPARENTLY DID **NOT** FIND THE STONE AT THE WEST 1/4 CORNER OF SECTION 12-16-11 ON THIS SURVEY AS HE RAN THE SECTION LINES FROM THE NORTHWEST CORNER OF SECTION 12-16-11 SOUTH TO THE SOUTHWEST CORNER OF SECTION 12-16-11.

- 3) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JANUARY 26, 2001, FOR PROJECT NUMBER 00548-02, A SURVEY FOR THE ALLEN/ADMIRE CITY LAKE, SURVEY SR #14001 IN THE SURVEY DRAWER FOR TOWNSHIP 16-11, SAID THAT **HE FOUND A 1/2" REBAR** OF UNCERTAIN ORIGIN BUT IN A REASONABLE POSITION FOR THE EAST 1/4 CORNER OF SECTION 11-16-11. HE SAID THAT HE ACCEPTED THE FOUND REBAR AS THE EAST 1/4 CORNER OF SECTION 11-16-11.
 - 1) 0.6' DEEP IN THE GRAVEL ROAD
 - 2) IN LINE WITH A FENCE TO THE WEST
 - 3) IN THE CENTERLINE TRAVELED WAY OF THE GRAVEL ROAD NORTH-SOUTH
 - 4) 26.2' NW TO A METAL GATE POST
 - 5) 31.6' WEST TO A METAL GATE POST
 - 6) 27.7' SW TO A METAL GATE POST
 - 7) 48.1' NE TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POSTHIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,652.43' SOUTH TO THE 1/2" REBAR HE FOUND AT THE SOUTHEAST CORNER OF SECTION 11-16-11

- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED AUGUST 16, 2002, FOR PROJECT NUMBER 02233-02, SURVEY F11002 IN THE SURVEY FILE FOR TOWNSHIP 16-11 FOR A 76.71 ACRE TRACT LOCATED IN THE SOUTHEAST AND SOUTHWEST QUARTERS OF SECTION 11-16-11, SAID THAT **HE FOUND THE 1/2" REBAR** AT THE EAST 1/4 CORNER OF SECTION 11-16-11 FROM HIS EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE DATED JANUARY 2001.
 - 1) 0.6' DEEP IN A GRAVEL ROAD
 - 2) IN THE CENTERLINE TRAVELED WAY OF THE ROAD NORTH-SOUTH
 - 3) IN LINE WITH A FENCE TO THE WEST
 - 4) 26.2' NW TO A METAL GATE POST
 - 5) 31.6' WEST TO A METAL GATE POST
 - 6) 27.7' SW TO A METAL GATE POST
 - 7) 48.1' NE TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POSTHIS DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 5,280.81' WEST TO THE 1/2" REBAR HE FOUND AT THE NORTHWEST CORNER OF THE SW1/4 OF SECTION 11-16-11
 - 2) 2,652.43' SOUTH TO THE 1/2" REBAR HE FOUND AT THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 11-16-11

- 5) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED AUGUST 22, 2016, FOR PROJECT NUMBER 16205-02-02, SURVEY F11003 IN THE SURVEY FILE FOR TOWNSHIP 16-11, TO SURVEY A TRACT IN THE NORTH HALF OF SECTION 11-16-11 FOR PETE WHEAT, SAID THAT **HE FOUND THE EXISTING RECORD 5/8" REBAR WITH THE TOP BENT TO THE SOUTH** AT THE EAST 1/4 CORNER OF SECTION 11-16-11 FROM HIS EXISTING REFERENCE TIES ON FILE AT THE COUNTY SURVEYOR'S OFFICE. HE NOTED THAT HE HAD PREVIOUSLY IDENTIFIED THIS MONUMENT AS A 1/2" REBAR IN 2001.
- 1) 36.4' ESE TO THE NEAR FACE OF A PIPE GATE POST
 - 2) 47.9' NE TO THE NEAR FACE OF A PIPE CORNER POST
 - 3) 26.2' NW TO THE NEAR FACE OF A PIPE CORNER POST
 - 4) 27.8' SW TO THE NEAR FACE OF A PIPE CORNER POST
 - 5) IN THE TRAVELED WAY OF THE GRAVEL ROAD NORTH-SOUTH [COUNTY ROAD "M"]
 - 6) IN LINE WITH A FENCE TO THE WEST
- HIS REPORT OF SURVEY SHOWS THE FOLLOWING INFORMATION:
- 1) 2,653.16' NORTH TO THE 1/2" REBAR WITH "CLS 27" CAP HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 11-16-11 FROM REFERENCE TIES
 - 2) 2,266.66' WEST 1/2" X 24" REBAR WITH HIS "PS 752" CAP HE SET FOR THE SOUTHEAST CORNER OF THE SURVEYED TRACT
 - 3) 5,280.66' WEST TO THE 5/8" REBAR HE FOUND AT THE SOUTHWEST CORNER OF THE NW1/4 OF SECTION 11-16-11 FROM REFERENCE TIES, BEING THE SOUTHWEST CORNER OF THE SURVEYED TRACT.

WEST QUARTER CORNER SECTION 12-16-11