

**NORTH 1/4 CORNER SECTION 16, TOWNSHIP 16 SOUTH, RANGE 11 EAST**

- 1) ON PAGE 298 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 11" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 9 & 16-16-11.  
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 40.10 CHAINS EAST TO THE 20" X 11" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 9 & 16-16-11
  - 2) 80.20 CHAINS EAST TO THE 18" X 15" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 9, 10, 15 & 16-16-11
  
- 2) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN SURVEY NUMBER 179, A **PERMANENT SURVEY** AT THE REQUEST OF JAMES W. WORSTELL TO ESTABLISH THE LINES AND CORNERS OF THE SOUTHEAST 1/4 OF SECTION 14 AND THE NORTHEAST 1/4 OF SECTION 23, ALL IN TOWNSHIP 16, RANGE 11 RECORDED IN SURVEY BOOK "F" ON PAGE 133 DATED JUNE 18 TO JULY 7, 1888, APPARENTLY DID **NOT** FIND THE STONE AT THE NORTH 1/4 CORNER OF SECTION 16-16-11 ON THIS **PERMANENT SURVEY** AS HE RAN THE SECTION LINES FROM THE NORTHWEST CORNER OF SECTION 16-16-11 EAST TO THE NORTH 1/4 CORNER OF SECTION 13-16-11.

NORTH QUARTER CORNER SECTION 16-16-11