

NORTHWEST CORNER SECTION 16, TOWNSHIP 16 SOUTH, RANGE 11 EAST

- 1) ON PAGE 298 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 26" X 12" X 4"** FOR THE CORNER TO SECTIONS 8, 9, 16 & 17-16-11.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.10 CHAINS EAST TO THE 20" X 11" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 9 & 16-16-11
 - 2) 80.20 CHAINS EAST TO THE 18" X 15" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 9, 10, 15 & 16-16-11
 - 3) 23.00 CHAINS WEST TO THE 14" X 11" X 4" LIMESTONE SET ON THE EAST BOUNDARY OF THE KANSAS INDIAN RESERVATION

- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 79 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 318 TO 320 PETITIONED BY JOHN T. HYDE AND OTHERS FOR TWO COUNTY ROADS IN TOWNSHIP 16-11 [PACKET 223 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON SEPTEMBER 15, 1880, WAS ESTABLISHED AS 40 FOOT WIDE EAST-WEST ROADS AND 60 FOOT WIDE NORTH-SOUTH ROADS ON OCTOBER 5, 1880, AND WAS RECORDED ON OCTOBER 12, 1880 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 17-16-11 FOR THE TERMINUS OF THE SECOND ROAD OF THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THE SECOND ROAD EXTENDS WEST ON THE SECTION LINES TO THE NORTHWEST CORNER OF SECTION 18-16-11 ON THE RANGE LINE TO COMMENCE THE SECOND ROAD ON THIS ROAD SURVEY

- 3) MATTHEW BROWN, DEPUTY COUNTY SURVEY, IN A ROAD SURVEY FOR ROAD NUMBER 320 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 239 TO 232 PETITIONED BY MANLY B. SMITH AND OTHERS FOR TWO ROADS IN TOWNSHIPS 15-11 AND 16-11 [PACKET 573 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON DECEMBER 2, 1885, WITH THE FIRST ROAD ESTABLISHED AS A 50 FOOT WIDE ROAD ON APRIL 20, 1886 AND THE SECOND ROAD **REJECTED** AS NOTED BY T. E. McMILLAN, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON MAY 6, 1886 BY ROLAND LAKIN, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 16-16-11 TO BEGIN THE FIRST ROAD ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS FIRST ROAD EXTENDS EAST ON THE SECTION LINES FOR 5,280 FEET TO THE 8" X 8" X 12" STONE MARKED "R/1M" HE SET AT OR NEAR THE NORTHWEST CORNER OF SECTION 15-16-11, THEN CONTINUES EAST ON THE SECTION LINES FOR 5,280 FEET TO THE 3" X 6" X 12" STONE MARKED "R/2M" ON THE WEST FACE, I.E. THE NORTHEAST CORNER OF SECTION 15-16-11, TO END THE FIRST ROAD ON THIS ROAD SURVEY

- 4) MATTHEW BROWN, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 75 OF THE 7TH TERM, A ROAD SURVEY RECORDED IN SURVEY BOOK "B" ON PAGE 227 DATED FEBRUARY 23, 1886 FOR A ROAD IN TOWNSHIP 16, RANGE 11 FOR MANLY B. SMITH AND OTHERS, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 16-16-11 TO BEGIN THIS ROAD SURVEY FOR A 50 FOOT WIDE ROAD.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 5,280 FEET TO THE 8" X 8" X 12" STONE MARKED "R/1M" HE SET AT OR NEAR THE NORTHWEST CORNER OF SECTION 15-16-11, THEN CONTINUES EAST ON THE SECTION LINES FOR 5,280 FEET TO THE 3" X 6" X 12" STONE MARKED "R/2M" ON THE WEST

FACE, I.E. THE NORTHEAST CORNER OF SECTION 15-16-11, TO END THE FIRST ROAD ON THIS ROAD SURVEY

- 5) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, BY MATTHEW BROWN, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 77 RECORDED IN SURVEY BOOK "F" ON PAGES 100 TO 103 DATED APRIL 26 THROUGH JUNE 22, 1886, TO SUBDIVIDE SECTIONS 7, 8, 17 & 18 AND THE SOUTH 1/2 OF SECTION 5, ALL IN TOWNSHIP 16, RANGE 10, SAID THAT **HE SET A STAKE** FOR THE NORTHEAST CORNER OF SECTION 17-16-11 ON THIS SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 22.77 CHAINS WEST TO THE 19" X 8" X 5" STONE MARKED "RL" ON THE EAST FACE HE SET ON THE BOUNDARY OF THE KANSAS INDIAN RESERVATION FOR THE SOUTHEAST CORNER OF GOVERNMENT LOT 8 IN THE SE1/4 OF SEC. 8-16-11
- 2) 37.09 CHAINS WEST TO THE STAKE HE SET FOR THE NORTH 1/4 CORNER OF SECTION 17-16-11
- 3) 57.09 CHAINS WEST TO THE 16" X 10" X 4" STONE MARKED "1/8" ON THE SOUTH FACE HE SET FOR THE NORTH 1/8TH CORNER OF THE NW1/4 OF SECTION 17-16-11
- 4) 77.09 CHAINS WEST TO THE STAKE HE SET FOR THE NORTHWEST CORNER OF SECTION 17-16-11
- 5) 97.09 CHAINS WEST TO THE 20" X 10" X 6" STONE MARKED "1/8" ON THE SOUTH FACE HE SET FOR THE NORTH 1/8TH CORNER OF THE NE1/4 OF SECTION 18-16-11
- 6) 137.09 CHAINS WEST TO THE 15" X 8" X 6" STONE MARKED "1/8" ON THE SOUTH FACE HE SET FOR THE NORTH 1/8TH CORNER OF THE NW1/4 OF SECTION 18-16-11
- 7) 154.94 CHAINS WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 18-16-11 ON THE RANGE LINE

- 6) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN SURVEY NUMBER 179, A **PERMANENT SURVEY** AT THE REQUEST OF JAMES W. WORSTELL TO ESTABLISH THE LINES AND CORNERS OF THE SOUTHEAST 1/4 OF SECTION 14 AND THE NORTHEAST 1/4 OF SECTION 23, ALL IN TOWNSHIP 16, RANGE 11 RECORDED IN SURVEY BOOK "F" ON PAGE 133 DATED JUNE 18 TO JULY 7, 1888, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 16-16-11 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 18,410' EAST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 13-16-11

NORTHWEST CORNER SECTION 16-16-11