

WEST 1/4 CORNER SECTION 16, TOWNSHIP 16 SOUTH, RANGE 11 EAST

- 1) ON PAGE 298 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 13" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 16 & 17-16-11.
- 2) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, BY MATTHEW BROWN, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 77 RECORDED IN SURVEY BOOK "F" ON PAGES 100 TO 103 DATED APRIL 26 THROUGH JUNE 22, 1886, TO SUBDIVIDE SECTIONS 7, 8, 17 & 18 AND THE SOUTH 1/2 OF SECTION 5, ALL IN TOWNSHIP 16, RANGE 10, SAID THAT **HE SET A STAKE** FOR THE EAST 1/4 CORNER OF SECTION 17-16-11 ON THIS SURVEY.
- 3) KDOT PLANS FOR PROJECT 50N-56-419 DATED 1941; SHOWS AN **IRON PIN** AT THE WEST 1/4 CORNER OF SECTION 16-16-11.
 - 1) 11.8' LEFT [NORTH] OF STATION 427 + 29.0
 - 2) 179.5' SE TO A SPIKE & WASHER IN A COTTONWOOD TREE
 - 3) 226.4' NNE TO A SPIKE & WASHER IN A HEDGE TREE
 - 4) 136.5' NORTH TO A SPIKE & WASHER IN THE TOP OF A FENCE POST

WEST QUARTER CORNER SECTION 16-16-11