

WEST 1/4 CORNER SECTION 18, TOWNSHIP 16 SOUTH, RANGE 11 EAST

- 1) ON PAGE 58 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 16" X 12" X 3"** FOR THE WEST 1/4 CORNER OF SECTION 18-16-11 ON THE WEST TOWNSHIP BOUNDARY.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS NORTH ON THE WEST TOWNSHIP BOUNDARY TO THE 20" X 10" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 7 & 18-16-11
- 2) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 20" X 12" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 18 & 19-16-11

- 2) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, BY MATTHEW BROWN, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 77 RECORDED IN SURVEY BOOK "F" ON PAGES 100 TO 103 DATED APRIL 26 THROUGH JUNE 22, 1886, TO SUBDIVIDE SECTIONS 7, 8, 17 & 18 AND THE SOUTH 1/2 OF SECTION 5, ALL IN TOWNSHIP 16, RANGE 10, SAID THAT **HE FOUND THE STONE IN GOOD CONDITION** AT THE WEST 1/4 CORNER OF SECTION 18-16-11 ON THE RANGE LINE ON THIS SURVEY.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 39.53 CHAINS NORTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 18-16-11
- 2) 79.62 CHAINS NORTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 7-16-11
- 3) 119.74 CHAINS NORTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 7-16-11
- 4) 40.28 CHAINS SOUTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 18-16-11
- 5) 17.79 CHAINS EAST TO THE 16" X 12" X 4" STONE MARKED "1/8" ON THE WEST FACE HE SET FOR THE NORTH 1/8TH CORNER OF THE SW1/4 OF SEC. 18-16-11
- 6) 37.79 CHAINS EAST TO THE 16" X 8" X 6" STONE MARKED "+" ON TOP AND NEAR THE BOTTOM ON THE EAST SIDE HE SET FOR THE CENTER CORNER OF SECTION 18-16-11
- 7) 57.79 CHAINS EAST TO THE 17" X 7" X 4" STONE MARKED "1/8" ON THE WEST FACE HE SET FOR THE NORTH 1/8TH CORNER OF THE SE1/4 OF SECTION 18-16-11
- 8) 77.79 CHAINS EAST TO THE 16" X 8" X 5" STONE MARKED "1/4" HE SET FOR THE EAST 1/4 CORNER OF SECTION 18-16-11

- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 177 AND DATED JUNE 1904, SAID THAT **HE FOUND THE GOVERNMENT 1/4 STONE AT 20 FEET WEST OF A FENCE** AT THE WEST 1/4 CORNER OF SECTION 18-16-11 ON THE RANGE LINE ON THIS **PERMANENT SURVEY**.

- 4) KDOT PLANS FOR PROJECT 50N-56-419 DATED 1941, SHOWS AN **IRON PIN** AT THE WEST 1/4 CORNER OF SECTION 18-16-11 ON THE RANGE LINE.

- 1) 10.0' LEFT [NORTH] OF STATION 324 + 29.8
- 2) 70.3' NNW TO A 5/8" IRON BAR [BM #40]
- 3) 79.1' NNE TO A SPIKE & WASHER IN THE TOP OF A FENCE POST
- 4) 211.7' SSW TO A SPIKE & WASHER IN A HEDGE TREE
- 5) 109.2' SSE TO A SPIKE & WASHER IN A HEDGE TREE

WEST QUARTER CORNER SECTION 18-16-11