

NORTH 1/4 CORNER SECTION 20, TOWNSHIP 16 SOUTH, RANGE 11 EAST

- 1) ON PAGE 302 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 14" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 17 & 20-16-11.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS WEST TO THE 18" X 14" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 17, 18, 19 & 20-16-11
 - 2) 17.30 CHAINS EAST TO THE 15" X 10" X 3" LIMESTONE THEY SET ON THE EAST BOUNDARY OF THE KANSAS INDIAN RESERVATION
 - 3) 39.90 CHAINS EAST TO THE 22" X 18" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 16, 17, 20 & 21-16-11

- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, BY FRANK P. MACLEMAN, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 208 DATED MAY 7-9, 1878 ORDERED BY J. K. PETERMAN AND HENRY HAAS TO SUBDIVIDE THE NORTHEAST 1/4 OF SECTION 19-16-11 AND THE NORTHWEST 1/4 OF SECTION 20-16-11, SAID THAT **HE FOUND THE STONE AT THE NORTH 1/4 CORNER OF SECTION 20-16-11 ON THIS PERMANENT SURVEY.**
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 81 RODS, 3-1/2 LINKS WEST TO THE STONE HE SET FOR THE PERMANENT NORTHEAST CORNER OF THE NW1/4 OF THE NW1/4 OF SECTION 20-16-11
 - 2) 162 RODS, 7 LINKS WEST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 19-16-11
 - 3) 161 RODS, 18.4 LINKS SOUTH TO THE STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 20-16-11

- 3) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, BY MATTHEW BROWN, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 77 RECORDED IN SURVEY BOOK "F" ON PAGES 100 TO 103 DATED APRIL 26 THROUGH JUNE 22, 1886, TO SUBDIVIDE SECTIONS 7, 8, 17 & 18 AND THE SOUTH 1/2 OF SECTION 5, ALL IN TOWNSHIP 16, RANGE 10, SAID THAT **HE FOUND THE STONE IN GOOD CONDITION** AT THE SOUTH 1/4 CORNER OF SECTION 17-16-11 ON THIS SURVEY.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 19.91-1/2 CHAINS WEST TO THE STAKE HE SET FOR THE SOUTH 1/8TH CORNER OF THE SOUTHWEST 1/4 OF SECTION 17-16-11
 - 2) 39.83 CHAINS WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 17-16-11
 - 3) 79.83 CHAINS WEST TO THE 15" X 10" X 5" STONE MARKED "1/4" ON THE SOUTH SIDE FOR THE SOUTH 1/4 CORNER OF SECTION 18-16-11
 - 4) 99.83 CHAINS WEST TO THE 16" X 12" X 5" STONE MARKED "1/8" ON THE SOUTH FACE HE SET FOR THE SOUTH 1/8TH CORNER OF THE SW1/4 OF SECTION 18-16-11
 - 5) 117.53 CHAINS WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 18-16-11 ON THE RANGE LINE
 - 6) 14.35 CHAINS EAST TO THE 19" X 11" X 5" STONE MARKED "RL" ON THE EAST SIDE HE SET ON THE BOUNDARY OF THE KANSAS INDIAN RESERVATION AT THE SOUTHEAST CORNER OF GOVERNMENT LOT 8 IN THE SE1/4 OF SECTION 17-16-11
 - 7) 37.12 CHAINS EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 17-16-11, AND THE SOUTHEAST CORNER OF GOVERNMENT LOT 4

- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 16, 2004, FOR PROJECT NUMBER 04070-02 FOR THE LYON COUNTY ROAD & BRIDGE DEPARTMENT FOR BRIDGE REPLACEMENT PROJECT 04-EF, SAID THAT **HE FOUND A 5/8" REBAR WITH A LYON COUNTY CAP**

AT THE NORTH 1/4 CORNER OF SECTION 20-16-11 FROM A PRIOR SURVEY BY POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR.

- 1) 28.3' NORTH TO A 40 D NAIL IN A STEEL FENCE POST
- 2) 29.0' SW TO A 40 D NAIL IN A STEEL FENCE POST
- 3) 26.55' SE TO A 40 D NAIL IN A STEEL FENCE POST
- 4) 92.4' WEST TO A FENCE TO THE NORTH
- 5) 97.4' WNW TO A PK NAIL IN A CORNER FENCE POST
- 6) 3.0' NORTH TO THE CENTERLINE OF ROAD 340 EAST-WEST

HIS DRAWING ON HIS REFERENCE REPORT SHOWS THE FOLLOWING:

- 1) 1,324.12' WEST TO THE RAILROAD SPIKE HE FOUND AT THE NORTHEAST CORNER OF THE NW1/4 OF THE NW1/4 OF SECTION 20-16-11
- 2) 2,648.23' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHWEST CORNER OF THE NW1/4 OF THE NW1/4 OF SECTION 20-16-11

NORTH QUARTER CORNER SECTION 20-16-11