

WEST 1/4 CORNER SECTION 20, TOWNSHIP 16 SOUTH, RANGE 11 EAST

- 1) ON PAGE 302 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 16" X 16" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 19 & 20-16-11.

- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, BY FRANK P. MACLEMAN, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 208 DATED MAY 7-9, 1878 ORDERED BY J. K. PETERMAN AND HENRY HAAS TO SUBDIVIDE THE NORTHEAST 1/4 OF SECTION 19-16-11 AND THE NORTHWEST 1/4 OF SECTION 20-16-11, SAID THAT **HE SET A STONE** FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 19-16-11 ON LINE AND AT THE MIDWAY POINT BETWEEN THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 19-16-11 AND THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 19-16-11 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 162 RODS, 11.6 LINKS NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 19-16-11
 - 2) 162 RODS, 11.6 LINKS SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 19-16-11
 - 3) 78 RODS, 15 LINKS WEST TO THE STONE HE SET FOR THE PERMANENT SOUTHWEST CORNER OF THE SE1/4 OF THE NE1/4 OF SECTION 19-16-11
 - 4) 157 RODS, 5 LINKS WEST TO THE STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 19-16-11
 - 5) 79 RODS, 13 LINKS EAST TO THE STONE SET FOR THE PERMANENT SOUTHEAST CORNER OF THE SW1/4 OF THE SW1/4 OF SECTION 20-16-11
 - 6) 159 RODS, 1 LINK EAST TO THE STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 20-16-11

- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 79 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 318 TO 320 PETITIONED BY JOHN T. HYDE AND OTHERS FOR TWO COUNTY ROADS IN TOWNSHIP 16-11 [PACKET 223 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON SEPTEMBER 15, 1880, WAS ESTABLISHED AS 40 FOOT WIDE EAST-WEST ROADS AND 60 FOOT WIDE NORTH-SOUTH ROADS ON OCTOBER 5, 1880, AND WAS RECORDED ON OCTOBER 12, 1880 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 19-16-11 ON THE FIRST ROAD OF THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THE FIRST ROAD EXTENDS EAST ON THE 1/2 SECTION LINE TO THE SOUTHEAST CORNER OF THE W1/2 OF THE SW1/4 OF SECTION 20-16-11; THEN CONTINUES NORTH ON THE 1/2 OF 1/4 LINE TO INTERSECT THE SANTA FE ROAD FOR THE TERMINUS OF THE FIRST ROAD ON THIS ROAD SURVEY
 - 2) THE FIRST ROAD EXTENDS SOUTH ON THE SECTION LINES TO THE SOUTHEAST CORNER OF SECTION 19-16-11 TO COMMENCE THE FIRST ROAD ON THIS ROAD SURVEY

- 4) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE RIGHT SIDE PAGE 189 DATED SEPTEMBER 15, 1880, FOR A COUNTY ROAD IN TOWNSHIP 16-11, APPARENTLY **FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 19-19-11 ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS EAST ON THE 1/2 SECTION LINE FOR 1,320' TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE W1/2 OF THE SW1/4 OF SECTION 20-16-11; THEN CONTINUES NORTH ON THE 1/2 OF 1/4 LINE TO

INTERSECT THE SANTA FE ROAD FOR THE TERMINUS OF THE FIRST ROAD ON THIS ROAD SURVEY

- 2) THIS ROAD EXTENDS SOUTH ON THE SECTION LINE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 19-16-11 TO COMMENCE THIS ROAD SURVEY

- 5) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 47, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 47 DATED JULY 21, 1884 AT THE REQUEST OF M. L. WILLARD AND J. K. PETERMAN TO LOCATE THE CORNER TO SECTIONS 19, 20, 29 & 30-16-11 AND RESURVEYED SEPTEMBER 30, 1884 BY MATTHEW BROWN, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 19-16-11 ON THIS **PERMANENT SURVEY**. HE USED THIS STONE AND THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 30-16-11 TO SET A 3" X 8" X 2' STONE FOR THE PERMANENT CORNER TO SECTIONS 19, 20, 29 & 30-16-11. THIS SURVEY WAS DATED JULY 21, 1884 AND RESURVEYED SEPTEMBER 30, 1884 AND RECORDED IN MISCELLANEOUS VOLUME 41 ON PAGE 23 IN THE REGISTER OF DEEDS OFFICE ON JANUARY 27, 1887, AND SURVEY F19001 IN THE SURVEY FILE FOR TOWNSHIP 16-11 IS A COPY OF THIS SURVEY.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,657' SOUTH TO THE 3" X 8" X 2' STONE HE SET FOR THE PERMANENT CORNER TO SECTIONS 19, 20, 29 & 30-16-11
 - 2) 7,970' SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 30-16-11
-
- 6) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN A ROAD SURVEY FOR ROAD NUMBER 397 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 530 TO 532 PETITION BY S. A. GOULD AND OTHERS FOR A ROAD IN TOWNSHIPS 16-10 AND 16-11 [PACKET 656A IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON DECEMBER 13, 1893, WAS ESTABLISHED AS 40 FEET WIDE ROAD, **EXCEPT** THAT IT SHALL CONFORM IN WIDTH TO THE OF 3RD STREET AND OTHER STREETS IN BUSHONG, ON JANUARY 16, 1894, AS NOTED BY W. N. D. BIRD, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON APRIL 25, 1984 BY MATTHEW BROWN, COUNTY SURVEYOR, SAID THAT **HE FOUND THE 1/4 CORNER** ON THE EAST LINE OF SECTION 19-16-11 TO END THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS WEST ON THE 1/2 SECTION LINE TO A ROAD STONE HE SET ON THE NORTH LINE OF THE SW1/4 OF SECTION 24-16-1, THEN SOUTH FOR 560 FEET TO A ROAD STONE HE SET IN THE CENTER OF 3RD STREET IN BUSHONG, THEN WEST ON THE CENTERLINE OF 3RD STREET IN BUSHONG FOR 2,330-1/2 FEET TO THE ROAD STONE HE SET IN THE NORTH-SOUTH ROAD TO BEGIN THIS ROAD SURVEY
-
- 4) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN A ROAD SURVEY FOR ROAD NUMBER 398 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 530 TO 532 PETITION BY S. A. GOULD AND OTHERS FOR A ROAD IN TOWNSHIPS 16-10 AND 16-11 [PACKET 656 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON SEPTEMBER 28, 1894, WAS ESTABLISHED AS 40 FEET WIDE ROAD ON OCTOBER 3, 1894, 1894, AS NOTED BY J. A. MILLER, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON OCTOBER 22, 1894 BY MATTHEW BROWN, COUNTY SURVEYOR, SAID THAT **HE FOUND THE STONE** AT THE 1/4 CORNER ON THE EAST LINE OF SECTION 19-16-11 AT THE TERMINUS OF THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

HIS INFORMATION IS CONTINUED ON PAGE 3

- 1) THIS ROAD EXTENDS WEST ON THE 1/2 SECTION LINE FOR 1 MILE TO THE STONE HE FOUND AT THE 1/4 CORNER ON THE RANGE LINE BETWEEN SECTIONS 19 & 24, THEN NORTH ON THE RANGE LINE IN A ROAD ALREADY ESTABLISHED TO A ROAD STONE HE SET ON THE NORTH RIGHT-OF-WAY OF THE RAILROAD, THEN SOUTHWESTERLY ON THE NORTH SIDE OF THE RAILROAD RIGHT-OF-WAY TO THE ROAD STONE HE SET ON THE 1/2 SECTION LINE, THEN THE WEST ON THE 1/2 SECTION LINE TO THE ROAD STONE HE SET ON THE NORTH LINE OF THE SW1/4 OF SECTION 24-16-1, THEN SOUTH FOR 560 FEET TO A ROAD STONE HE SET IN THE CENTER OF 3RD STREET IN BUSHONG, THEN WEST ON THE CENTERLINE OF 3RD STREET IN BUSHONG FOR 2,330-1/2 FEET TO THE ROAD STONE HE SET IN THE NORTH-SOUTH ROAD TO BEGIN THIS ROAD SURVEY

WEST CORNER SECTION 20-16-11