

WEST 1/4 CORNER SECTION 25, TOWNSHIP 16 SOUTH, RANGE 11 EAST

- 1) ON PAGE 285 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 19" X 8" X 5"** FOR THE 1/4 CORNER BETWEEN SECTIONS 25 & 26-16-11.
- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 91, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 171 DATED MARCH 1 & 2, 1904 AT THE REQUEST OF W. W. BAYLAND FOR A SURVEY FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE SOUTHEAST CORNER AND THE SOUTH 1/4 CORNER OF SECTION 23-16-11 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, APPARENTLY DID **NOT** FIND THE STONE AT THE EAST 1/4 CORNER OF SECTION 26-16-11 ON THIS **PERMANENT SURVEY** AS HE RAN THE SECTION LINES FROM THE STONE THAT HE FOUND AT THE EAST 1/4 CORNER OF SECTION 23-16-11 SOUTH TO THE STONE THAT FOUND AT THE SOUTHEAST CORNER OF SECTION 26-16-11. HIS FIELD NOTES ARE IN BOOK 2 ON PAGE 28 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 121" IN MISCELLANEOUS DRAWER NUMBER 5 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.
- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 97, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 177 DATED JUNE 28, 1904 BY THE ORDER OF T. G. WISDOM FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE SOUTHWEST 1/4 OF SECTION 24-16-11 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE SET A 20" X 8" X 5" STONE WITH WIRE AROUND IT** FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 25-16-11 ON TRANSIT LINE AND HALFWAY BETWEEN THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 25-16-11 AND THE STONE THAT HE FOUND AT THE NORTHWEST CORNER OF SECTION 25-16-11 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK 2 ON PAGE 60 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 158" IN MISCELLANEOUS DRAWER NUMBER 8 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.26 CHAINS SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 25-16-11
 - 2) 40.26 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 25-16-11
 - 3) 80.52 CHAINS NORTH TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 24-16-11
 - 4) 120.87 CHAINS NORTH TO THE GOVERNMENT STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 24-16-11
- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN THE *REPORT OF SURVEY* FOR PROJECT NUMBER 90524 DATED AUGUST 27, 1990 FOR SURVEY F26001 IN THE SURVEY FILES FOR TOWNSHIP 16-11, TO SURVEY A PREVIOUSLY DESCRIBED 5.0 ACRE TRACT LOCATED IN THE SOUTHWEST 1/4 OF SECTION 26-16-11, SAID THAT THE EAST 1/4 CORNER OF SECTION 26-16-11 WAS NOT SEARCHED FOR OR MONUMENTED AS THIS CORNER WAS DEEMED **LOST** BY ALVA J. SMITH IN A 1909 SURVEY. HE CONSIDERED THAT THIS CORNER WAS **LOST**. HE DETERMINED THE **THEORETICAL POSITION** FOR THE EAST 1/4 CORNER OF SECTION 26-16-11 TO BE ON TRUE LINE AND HALFWAY BETWEEN THE NORTHEAST AND SOUTHEAST CORNERS OF SAID SECTION 26-16-11. THIS SURVEY IS FILED IN

VOLUME 455 ON PAGE 423 IN THE REGISTER OF DEEDS OFFICE ON SEPTEMBER 17, 1990.

HIS SURVEY DRAWING SHOWED THE FOLLOWING INFORMATION:

- 1) 2,654.17' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHEAST CORNER OF SECTION 26-16-11
- 2) 2,654.16' SOUTH TO THE 5/8" REBAR DRIVEN THROUGH THE REMAINS OF THE BROKEN STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 26-16-11
- 3) 5,265.54' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE WEST 1/4 CORNER OF SECTION 26-16-11

WEST QUARTER CORNER SECTION 25-16-11