

NORTH 1/4 CORNER SECTION 26, TOWNSHIP 16 SOUTH, RANGE 11 EAST

- 1) ON PAGE 289 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 15" X 12" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 23 & 26-16-11.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS WEST TO THE 17" X 16" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 22, 23, 26 & 27-16-11
 - 2) 40.00 CHAINS EAST TO THE 23" X 11" X 8" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 23, 24, 25 & 26-16-11

- 2) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN SURVEY NUMBER 179, A **PERMANENT SURVEY** AT THE REQUEST OF JAMES W. WORSTELL TO ESTABLISH THE LINES AND CORNERS OF THE SOUTHEAST 1/4 OF SECTION 14 AND THE NORTHEAST 1/4 OF SECTION 23, ALL IN TOWNSHIP 16, RANGE 11 RECORDED IN SURVEY BOOK "F" ON PAGE 133 DATED JUNE 18 TO JULY 7, 1888, SAID THAT HE DID **NOT** FIND THE STONE AT THE SOUTH 1/4 CORNER OF SECTION 23-16-11. HE RAN THE SECTION LINES FROM THE GOVERNMENT STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 23-16-11 EAST TO THE TEMPORARY STAKE HE SET FOR THE SOUTHEAST CORNER OF SECTION 24-16-11 ON THE RANGE LINE. **HE SET A TEMPORARY POINT** FOR THE SOUTH 1/4 CORNER OF SECTION 23-16-11 ON THIS **PERMANENT SURVEY**.

- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 91, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 171 DATED MARCH 1 & 2, 1904 AT THE REQUEST OF W. W. BAYLAND FOR A SURVEY FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE SOUTHEAST CORNER AND THE SOUTH 1/4 CORNER OF SECTION 23-16-11 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE SET A 15" X 9" X 3" STONE WITH A PIECE OF PLOW SHARE ON THE NORTH SIDE OF THE STONE** FOR THE SOUTH 1/4 CORNER OF SECTION 23-16-11 ON LINE AND HALFWAY BETWEEN THE STONE THAT HE SET FOR THE SOUTHWEST CORNER OF SECTION 23-16-11 AND THE STONE THAT HE SET FOR THE SOUTHEAST CORNER OF SECTION 23-16-11 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN BOOK 2 ON PAGE 28 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 121" IN MISCELLANEOUS DRAWER NUMBER 5 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.86 CHAINS WEST TO THE 18" X 8" X 4" STONE HE SET FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 23-16-11, AT A POINT PREVIOUSLY LOCATED BY THE AFFIDAVIT OF W. M. PORTER [SEE SURVEY RECORD "E" ON PAGE 224] AT 33 LINKS EAST AND 33 LINKS NORTH OF A LARGE CORNER POST
 - 2) 39.86 CHAINS EAST TO THE 18" X 6" X 6" STONE HE SET FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 23-16-11
 - 3) 119.34 CHAINS EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 24-16-11 ON THE RANGE LINE

- 4) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED SEPTEMBER 15, 1983, SAID THAT HE EXCAVATED WITH A COUNTY MAINTAINER FOR THE STONE SET BY ALVA J. SMITH IN 1904 AT THE NORTH 1/4 CORNER OF SECTION 26-16-11, BUT HE DID **NOT** FIND THE STONE. HE DID **NOT** RESET THE NORTH 1/4 CORNER OF SECTION 26-16-11 AT THIS TIME, BUT HE COMMENTED THAT "FENCES TO THE NORTH & SOUTH ARE IN A REASONABLE POSITION".

CONTINUED ON PAGE 2

- 5) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED AUGUST 27, 1990 FOR PROJECT NUMBER 90524, SURVEY F26001 IN THE SURVEY FILES FOR TOWNSHIP 16-11 TO SURVEY A PREVIOUSLY DESCRIBED 5.0 ACRE TRACT LOCATED IN THE SOUTHWEST 1/4 OF SECTION 26-16-11, SAID THAT HE DID **NOT** FIND OR RESET THE NORTH 1/4 CORNER OF SECTION 26-16-11 ON THIS SURVEY AS HE RAN THE SECTION LINE FROM THE NORTHWEST CORNER OF SECTION 26-16-11 TO THE NORTHEAST CORNER OF SECTION 26-16-11. THIS SURVEY WAS FILED IN VOLUME 455 ON PAGE 423 IN THE REGISTER OF DEEDS OFFICE ON SEPTEMBER 17, 1990.

NORTH QUARTER CORNER SECTION 26-16-11