

NORTH 1/4 CORNER SECTION 27, TOWNSHIP 16 SOUTH, RANGE 11 EAST

- 1) ON PAGE 293 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 9" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 22 & 27-16-11.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS WEST TO THE 24" X 7" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 21, 22, 27 & 28-16-11
 - 2) 40.00 CHAINS EAST TO THE 17" X 16" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 22, 23, 26 & 27-16-11

- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 43, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 224 DATED APRIL 2, 1902 ORDERED BY L. D. DeCAMP TO LOCATE AND PERMANENTLY ESTABLISH THE EAST 1/4 CORNER AND THE CENTER CORNER OF SECTION 27-16-11 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE SET A FLAG** FOR THE NORTH 1/4 CORNER OF SECTION 27-16-11 ON TRUE LINE AND MIDWAY BETWEEN THE STONE THAT HE FOUND AT THE NORTHWEST CORNER OF SECTION 27-16-11 AND THE LOCATION FOR THE NORTHEAST CORNER OF SECTION 27-16-11 AS DETERMINED BY THE AFFIDAVIT OF W. M. PORTER ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 38, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 48" IN MISCELLANEOUS DRAWER 2 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.06-1/2 CHAINS WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 27-16-11
 - 2) 40.06-1/2 CHAINS EAST TO THE LOCATION FOR THE NORTHEAST CORNER OF SECTION 27-16-11, BY THE AFFIDAVIT OF W. M. PORTER

NORTH QUARTER CORNER SECTION 27-16-11