

**NORTH 1/4 CORNER SECTION 29, TOWNSHIP 16 SOUTH, RANGE 11 EAST**

- 1) ON PAGE 301 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 14" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 20 & 29-16-11.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS WEST TO THE 30" X 12" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 19, 20, 29 & 30-16-11
- 2) 17.31 CHAINS EAST TO THE 20" X 11" X 6" LIMESTONE THEY SET ON THE EAST BOUNDARY OF THE KANSAS INDIAN RESERVATION
- 3) 39.61 CHAINS EAST TO THE 25" X 11" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 20, 21, 28 & 29-16-11

- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, BY FRANK P. MACLEMAN, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 207 DATED MAY 6-9, 1878 ORDERED BY GARRETT De BAUN AND A. L. SANDERS TO SUBDIVIDE THE NORTHWEST 1/4 OF SECTION 29-16-11, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 29-16-11 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 78 RODS, 23-1/2 LINKS WEST TO THE 4" X 4" X 1.5' STONE HE SET FOR THE PERMANENT MIDDLE CORNER ON THE NORTH SIDE OF THE NW1/4 OF SECTION 29-16-11
- 2) 157 RODS, 22 LINKS WEST TO THE STONE HE RESET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 29-16-11
- 3) 81 RODS, 21 LINKS SOUTH TO THE THIN TRIANGULAR STONE HE SET FOR THE PERMANENT MIDDLE CORNER ON THE EAST SIDE OF THE NW1/4 OF SECTION 29-16-11
- 4) 163 RODS, 17 LINKS SOUTH TO THE STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 29-16-11

- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, BY FRANK P. MACLEMAN, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 208 DATED MAY 7-9, 1878 ORDERED BY J. K. PETERMAN AND HENRY HAAS TO SUBDIVIDE THE NORTHEAST 1/4 OF SECTION 19-16-11 AND THE NORTHWEST 1/4 OF SECTION 20-16-11, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 20-16-11 ON THIS **PERMANENT SURVEY**.

- 4) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 47, A SURVEY RECORDED IN SURVEY BOOK "E" ON PAGE 47 DATED JULY 21, 1884 AT THE REQUEST OF M. L. WILLARD AND J. K. PETERMAN TO LOCATE THE CORNER TO SECTIONS 19, 20, 29 & 30-16-11 AND RESURVEYED SEPTEMBER 30, 1884 BY MATTHEW BROWN, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 29-16-11. HE USED THIS STONE TO SET THE NORTHEAST CORNER OF SECTION 30-16-11 ON THIS SURVEY. THIS SURVEY WAS DATED JULY 21, 1884 AND RESURVEYED SEPTEMBER 30, 1884 AND RECORDED IN MISCELLANEOUS VOLUME 41 ON PAGE 23 IN THE REGISTER OF DEEDS OFFICE ON JANUARY 27, 1887, AND SURVEY F19001 IN THE SURVEY FILE FOR TOWNSHIP 16-11 IS A COPY OF THIS SURVEY.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,327.5' WEST TO THE STONE HE FOUND AT THE NORTH 1/2/4 CORNER OF THE NW1/4 OF SECTION 29-16-11
- 2) 2,655' WEST TO THE STONE HE SET FOR THE NORTHEAST CORNER OF SECTION 30-16-11

HIS INFORMATION IS CONTINUED ON PAGE 2

- 3) 5,309.5' WEST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 30-16-11
- 4) 7,618.5' WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 30-16-11 ON THE RANGE LINE

NORTH QUARTER CORNER SECTION 29-16-11