

**NORTH 1/4 CORNER SECTION 30, TOWNSHIP 16 SOUTH, RANGE 11 EAST**

- 1) ON PAGE 302 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 16" X 14" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 19 & 30-16-11.  
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 35.00 CHAINS WEST TO THE 22" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 19 & 30-16-11 ON THE WEST TOWNSHIP BOUNDARY
  - 2) 40.00 CHAINS EAST TO THE 30" X 12" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 19, 20, 29 & 30
  
- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, BY FRANK P. MACLEMAN, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 207 DATED MAY 6-9, 1878 ORDERED BY GARRETT De BAUN AND A. L. SANDERS TO SUBDIVIDE THE NORTHWEST 1/4 OF SECTION 29-16-11, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 30-16-11 ON THIS **PERMANENT SURVEY**. HE USED THIS STONE TO RESET THE STONE HE FOUND AND HE RESET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 29-16-11.  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 161 RODS, 21 LINKS EAST TO THE STONE HE FOUND AND **HE RESET** FOR THE PERMANENT NORTHWEST CORNER OF SECTION 29-16-11
  
- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, BY FRANK P. MACLEMAN, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 208 DATED MAY 7-9, 1878 ORDERED BY J. K. PETERMAN AND HENRY HAAS TO SUBDIVIDE THE NORTHEAST 1/4 OF SECTION 19-16-11 AND THE NORTHWEST 1/4 OF SECTION 20-16-11, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 19-16-11 ON THIS **PERMANENT SURVEY**.  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 161 RODS, 21 LINKS EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 19-16-11
  - 2) 161 RODS, 8 LINKS NORTH TO THE STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 19-16-11
  - 3) 322 RODS, 17 LINKS NORTH TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 19-16-11
  
- 4) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 27 DATED AUGUST 22 & 31, 1882, FOR A ROAD IN TOWNSHIP 16, RANGE 11 FOR M. HAAS, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 19-16-11 TO COMMENCE THIS ROAD SURVEY.  
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
  - 1) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 40.33 CHAINS EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 19-16-11; THEN CONTINUES EAST ON THE SECTION LINES FOR 27.48 CHAINS TO A DEVIATION TO THE NORTH DUE TO ALLEN CREEK; THEN RETURNS TO THE SECTION LINE AND CONTINUES EAST ON THE SECTION LINES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 25-16-11 ON THE RANGE LINE AT THE TERMINUS OF THIS ROAD SURVEY
  
- 5) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY FOR ROAD NUMBER 104 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 402 TO 404 PETITION BY M. HAAS AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 16-11 [PACKET 481 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON AUGUST 23, 1882, WAS

ESTABLISHED AS A 40 FOOT WIDE ROAD ON JANUARY 6, 1883 AS NOTED BY HUGH F. HOLMES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON JANUARY 23, 1883 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 19-16-11 TO COMMENCE THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

1) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 40.33 CHAINS EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 19-16-11; THEN CONTINUES EAST ON THE SECTION LINES FOR 27.48 CHAINS TO A DEVIATION TO THE NORTH DUE TO ALLEN CREEK; THEN RETURNS TO THE SECTION LINE AND CONTINUES EAST ON THE SECTION LINES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 25-16-11 ON THE RANGE LINE AT THE TERMINUS OF THIS ROAD SURVEY

6) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 47, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 47 DATED JULY 21, 1884 AT THE REQUEST OF M. L. WILLARD AND J. K. PETERMAN TO LOCATE THE CORNER TO SECTIONS 19, 20, 29 & 30-16-11 AND RESURVEYED SEPTEMBER 30, 1884 BY MATTHEW BROWN, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 30-16-11 ON THIS **PERMANENT SURVEY**. HE USED THIS STONE AND THE STONES THAT HE FOUND AT THE NORTHWEST CORNER OF SECTION 30-16-11 ON THE RANGE LINE AND AT THE NORTH 1/4/4 CORNER OF THE NORTHWEST 1/4 OF SECTION 29-16-11 TO SET A 3" X 8" X 2' STONE FOR THE PERMANENT NORTHEAST CORNER OF SECTION 30-16-11 ON THIS **PERMANENT SURVEY**. THIS SURVEY WAS DATED JULY 21, 1884 AND RESURVEYED SEPTEMBER 30, 1884 AND RECORDED IN MISCELLANEOUS VOLUME 41 ON PAGE 23 IN THE REGISTER OF DEEDS OFFICE ON JANUARY 27, 1887, AND SURVEY F19001 IN THE SURVEY FILE FOR TOWNSHIP 16-11 IS A COPY OF THIS SURVEY.

HIS NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

1) 2,345.5' WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 30-16-11 ON THE RANGE LINE  
2) 2,654.5' EAST TO THE 3" X 8" X 2' STONE HE SET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 30-16-11  
3) 3,982' EAST TO THE STONE HE FOUND AT THE NORTH 1/4/4 CORNER OF THE NW1/4 OF SECTION 29-16-11

7) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT FOR PROJECT NUMBER 84-95, SURVEY F30001 IN THE SURVEY FILE FOR TOWNSHIP 16-11, DATED AUGUST 10, 1984 FOR A 84.75 ACRE TRACT AND A 20.0 ACRE TRACT LOCATED IN THE NORTHWEST 1/4 OF SECTION 30-16-11, SAID THAT HE TRAVERSED THE SECTION AND EXCAVATED WITH A COUNTY MAINTAINER OVER A WIDE AREA FOR THE GLO STONE AT THE NORTH 1/4 CORNER OF SECTION 30-16-11, BUT HE DID **NOT** FIND THE STONE. HE DEEMED THAT THIS CORNER WAS **OBLITERATED**. HE SET A 1/2" X 24" REBAR WITH A RED PLASTIC "LS 752" CAP FOR THE NORTH 1/4 CORNER OF SECTION 30-16-11 IN LINE WITH THE REMAINS OF THE FENCE TO THE SOUTH, AND 25' NORTH & SOUTH OF THE RIGHT-OF-WAY FENCES.

1) IN LINE WITH THE REMAINS OF A FENCE TO THE SOUTH  
2) 25.0' NORTH & SOUTH OF TO THE FENCES EAST AND WEST  
3) 20.0' NORTH TO A LINE OF POWER POLES TO THE EAST AND WEST  
4) 20.0' EAST TO A LINE OF FENCE TO THE NORTH  
5) IN THE TRAVELED WAY OF THE ROAD EAST-WEST

HIS SURVEY DRAWING SHOWED THE FOLLOWING INFORMATION:

1) 171.05' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF THE 84.75 ACRE TRACT

HIS INFORMATION IS CONTINUED ON PAGE 3

- 2) 2,329.65' WEST TO THE 1/2" REBAR WITH HIS "LS 752" HE SET FOR THE NORTHWEST CORNER OF SECTION 30-16-11
- 8) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT FOR PROJECT NUMBER 84104, SURVEY F30002 IN THE SURVEY FILE FOR TOWNSHIP 16-11 FOR A PLAT OF SURVEY FOR A 40.0 ACRE TRACT LOCATED IN THE NORTH 1/2 OF SECTION 30-16-11, DATED AUGUST 30, 1984, SAID THAT **HE FOUND THE 1/2" REBAR WITH HIS PLASTIC "LS 752" CAP** AT THE NORTH 1/4 CORNER OF SECTION 30-16-11 FROM HIS PREVIOUS SURVEY. SEE HIS "REPORT OF SURVEY" FOR ADDITIONAL INFORMATION.
- 1) IN LINE WITH THE REMAINS OF A FENCE TO THE SOUTH
  - 2) 25.0' NORTH & SOUTH TO THE FENCES EAST AND WEST
  - 3) 20.0' NORTH TO A LINE OF POWER POLES EAST AND WEST
  - 4) 20.0' EAST TO A LINE OF FENCE TO THE NORTH
  - 5) IN THE TRAVELED WAY OF THE ROAD EAST-WEST
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 171.05' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE FOUND THE NORTHEAST CORNER OF THE 84.75 ACRE TRACT FROM A PREVIOUS SURVEY
  - 2) 2,329.65' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE FOUND AT THE NORTHWEST CORNER OF SECTION 30-16-11 ON THE RANGE LINE
  - 3) 847.08' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF THE 40.0 ACRE TRACT
  - 4) 2,649.00' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF SECTION 30-16-11
- 9) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED SEPTEMBER 2, 2010 FOR PROJECT NUMBER 10238-02, SURVEY F19002 IN THE SURVEY FILE FOR TOWNSHIP 16-11 FOR THE SURVEY OF A 6.7 ACRE TRACT IN THE SOUTHEAST 1/4 OF SECTION 19-16-11 FOR RONALD HAYES, SAID THAT **HE FOUND THE 1/2" REBAR WITH HIS RED "LS 752" CAP** AT THE SOUTH 1/4 CORNER OF SECTION 19-16-11 FROM HIS EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE FROM HIS 1984 SURVEY RECORDED IN VOLUME 411 ON PAGE 177 AT THE REGISTER OF DEEDS OFFICE.
- 1) 21' EAST TO A LINE OF FENCE TO THE NORTH
  - 2) 53.0' SE TO A 40 D NAIL & BOTTLE CAP IN THE TOP OF A BRACE POST
  - 3) 22.4' SSW TO A 16 D NAIL & BOTTLE CAP IN A 26" ELM TREE
  - 4) 35.15' NE TO A MAG NAIL & BOTTLE CAP IN A CORNER FENCE POST
  - 5) 2.0' SOUTH TO THE TRAVELED WAY OF COUNTY ROAD 330 EAST-WEST
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,648.88' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 19-16-11

NORTH QUARTER CORNER SECTION 30-16-11