

NORTHWEST CORNER SECTION 30, TOWNSHIP 16 SOUTH, RANGE 11 EAST

- 1) ON PAGE 57 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 22" X 12" X 3"** FOR THIS CORNER TO SECTIONS 19 & 30-16-11 ON THE WEST TOWNSHIP BOUNDARY.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 35.00 CHAINS EAST TO THE 16" X 14" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 19 & 30-16-11
 - 2) 75.00 CHAINS EAST TO THE 30" X 12" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 19, 20 29 & 30-16-11
 - 3) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 17" X 13" X 3" LIMESTONE THEY SET FOR THE WEST 1/4 CORNER OF SECTION 30-16-11
 - 4) 80.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 18" X 14" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 30 & 31-16-11
- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, BY FRANK P. MACLEMAN, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 207 DATED MAY 6-9, 1878 ORDERED BY GARRETT De BAUN AND A. L. SANDERS TO SUBDIVIDE THE NORTHWEST 1/4 OF SECTION 29-16-11, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 30-16-11 ON THE RANGE LINE ON THIS **PERMANENT SURVEY**. HE USED THIS STONE TO RESET THE STONE THAT HE FOUND AND **HE RESET** FOR THE PERMANENT NORTHWEST CORNER COMMON OF SECTION 29-16-11.
- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 28 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 110 TO 112 PETITIONED BY W. R. COLGAN AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 16-10 AND 17-10 [PACKET 116 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JUNE 13, 1879, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD ON JULY 7, 1879, AND WAS RECORDED ON JULY 15, 1879 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 25-16-10 ON THE RANGE LINE ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS NORTH ON THE RANGE LINE TO THE NORTHEAST CORNER OF SECTION 6-16-10 ON THE 3RD STANDARD PARALLEL TO COMMENCE THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS SOUTH ON THE RANGE LINE TO THE NORTHEAST CORNER OF SECTION 24-17-10 FOR THE TERMINUS OF THIS ROAD SURVEY
- 4) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 47, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 47 DATED JULY 21, 1884 AT THE REQUEST OF M. L. WILLARD AND J. K. PETERMAN TO LOCATE THE CORNER TO SECTIONS 19, 20, 29 & 30-16-11 AND RESURVEYED SEPTEMBER 30, 1884 BY MATTHEW BROWN, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER SECTION 30-16-11 ON THE RANGE LINE ON THIS **PERMANENT SURVEY**. HE USED THIS STONE AND THE STONES THAT HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 30-16-11 AND THE NORTH 1/4/4 CORNER ON THE NORTH SIDE OF THE NORTHWEST CORNER OF SECTION 29-16-11 TO SET A 3" X 8" X 2' STONE FOR THE PERMANENT NORTHEAST CORNER OF SECTION 30-16-11 ON THIS **PERMANENT SURVEY**. THE SURVEY WAS DATED JULY 21, 1884 AND RESURVEYED SEPTEMBER 30, 1884 AND RECORDED IN MISCELLANEOUS VOLUME 41 ON PAGE 23 IN THE REGISTER OF DEEDS OFFICE ON JANUARY 27, 1887, AND SURVEY F19001 IN THE SURVEY FILE FOR TOWNSHIP 16-11 IS A COPY OF THIS SURVEY.

HIS INFORMATION IS CONTINUED ON PAGE 2

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,345.5' EAST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 30-16-11
 - 2) 5,000' EAST TO THE 3" X 8" X 2' STONE HE SET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 30-16-11
 - 3) 6,327.5' EAST TO THE STONE HE FOUND AT THE NORTH 1/4/4 CORNER OF THE NW1/4 OF SECTION 29-16-11
- 5) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT FOR PROJECT NUMBER 84-95, SURVEY F30001 IN THE SURVEY FILE FOR TOWNSHIP 16-11, DATED AUGUST 10, 1984 FOR A 84.75 ACRE TRACT AND A 20.0 ACRE TRACT LOCATED IN THE NORTHWEST 1/4 OF SECTION 30-16-11, SAID THAT HE TRAVERSED THE SECTION AND HE EXCAVATED WITH A COUNTY MAINTAINER OVER A WIDE AREA FOR THE GLO STONE AT THE NORTHWEST CORNER OF SECTION 30-16-11 ON THE RANGE LINE, BUT HE DID **NOT** FIND THE STONE. HE CONSIDERED THAT THIS CORNER WAS **OBLITERATED**. **HE SET A 1/2" X 24" REBAR WITH A RED "LS 752" CAP** FOR THE NORTHWEST CORNER OF SECTION 30-16-11 ON THE RANGE LINE FROM THE CALLS FOR THE CEMETERY LOCATED IN THE NORTHEAST CORNER OF SECTION 25-16-10; I.E., 330 FEET EAST OF THE WEST FENCE AND 528' NORTH OF THE SOUTH CEMETERY FENCE.
- 1) 30.5' NW TO A SPIKE & WASHER IN A POWER POLE
 - 2) 29.6' SW TO THE NEAR FACE OF A STEEL FENCE POST
 - 3) 23.0' WEST TO A LINE OF FENCE TO THE SOUTH
 - 4) 330' WEST TO A LINE OF CEMETERY FENCE TO THE NORTH
 - 5) 528' SOUTH TO A LINE OF CEMETERY FENCE TO THE WEST

HIS SURVEY DRAWING SHOWED THE FOLLOWING INFORMATION:

- 1) 2,156.8' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF THE 84.75 ACRE TRACT
 - 2) 2,329.65' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTH 1/4 CORNER OF SECTION 30-16-11
 - 3) 1,170.05' SOUTH ON THE RANGE LINE TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHWEST CORNER OF THE 84.75 ACRE TRACT
 - 4) 2,644.05' SOUTH ON THE RANGE LINE TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHWEST CORNER OF THE NW1/4 OF SECTION 30-16-11
- 6) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT FOR PROJECT NUMBER 84104, SURVEY F30002 IN THE SURVEY FILE FOR TOWNSHIP 16-11 FOR A PLAT OF SURVEY FOR A 40.0 ACRE TRACT LOCATED IN THE NORTH 1/2 OF SECTION 30-16-11, DATED AUGUST 30, 1984, SAID THAT **HE FOUND THE 1/2" REBAR WITH HIS PLASTIC "LS 752" CAP** AT THE NORTHWEST CORNER OF SECTION 30-16-11 ON THE RANGE LINE FROM HIS PREVIOUS SURVEY. SEE HIS "REPORT OF SURVEY" FOR ADDITIONAL INFORMATION.
- 1) 30.5' NW TO A SPIKE & WASHER IN A POWER POLE
 - 2) 29.6' SW TO THE NEAR FACE OF A STEEL FENCE POST
 - 3) 23.0' WEST TO A LINE OF FENCE TO THE SOUTH
 - 4) 330' WEST TO A LINE OF CEMETERY FENCE TO THE NORTH
 - 5) 528' SOUTH TO A LINE OF CEMETERY FENCE TO THE WEST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,158.6' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE FOUND AT THE NORTHEAST CORNER OF AN 84.75 ACRE TRACT FROM A PREVIOUS SURVEY
- 2) 2,329.65' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 30-16-11
- 3) 3,176.73' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF THE 40.0 ACRE TRACT
- 4) 4,978.65' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF SECTION 30-16-11

NORTHWEST CORNER SECTION 30-16-11