

WEST 1/4 CORNER SECTION 30, TOWNSHIP 16 SOUTH, RANGE 11 EAST

- 1) ON PAGE 57 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 17" X 13" X 3"** AT THE WEST 1/4 CORNER OF SECTION 30-16-11 ON THE WEST TOWNSHIP BOUNDARY.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS NORTH ON THE WEST TOWNSHIP BOUNDARY TO THE 22" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 19 & 30-16-11
 - 2) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 18" X 14" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 30 & 31-16-11
- 2) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT FOR PROJECT NUMBER 84-95, SURVEY F30001 IN THE SURVEY FILE FOR TOWNSHIP 16-11, DATED AUGUST 10, 1984 FOR A 84.75 ACRE TRACT AND A 20.0 ACRE TRACT LOCATED IN THE NORTHWEST 1/4 OF SECTION 30-16-11, SAID THAT HE TRAVERSED THE SECTION AND THEN HE EXCAVATED WITH A COUNTY MAINTAINER OVER A WIDE AREA FOR THE GLO STONE AT THE WEST 1/4 CORNER OF SECTION 30-16-11 ON THE RANGE LINE, BUT HE DID **NOT** FIND THE STONE. HE COMMENTED THAT "THERE IS APPARENT GLO ERROR AT THIS CORNER, AS A LINE BETWEEN THE NORTHWEST CORNER AND THE APPARENT SOUTHWEST CORNER FALLS ABOUT 30' WEST OF THE POSITION INDICATED BY THE ROAD AND ROAD RECORD." HE DEEMED THAT THIS CORNER WAS **OBLITERATED**. **HE SET A 1/2" X 24" REBAR WITH HIS RED "LS 752" CAP** FOR THE WEST 1/4 CORNER OF SECTION 30-16-11 IN LINE WITH THE HEDGE TO THE WEST AND IN LINE WITH THE FENCE TO THE EAST, AND IN THE CENTER OF THE ROAD, AS PER THE ROAD RECORD.
- 1) 29.0' EAST & WEST TO A NORTH-SOUTH FENCE
 - 2) IN LINE WITH A HEDGE TO THE WEST
 - 3) IN LINE WITH A FENCE TO THE EAST
 - 4) 2.0' EAST TO THE TRAVELED WAY OF THE ROAD NORTH-SOUTH
- HIS SURVEY DRAWING SHOWED THE FOLLOWING INFORMATION:
- 1) 934.0' NORTH ON THE RANGE LINE TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHWEST CORNER OF THE 20.0 ACRE TRACT
 - 2) 2,644.05' NORTH ON THE RANGE LINE TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHWEST CORNER OF SECTION 30-16-11
 - 3) 934.0' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHEAST CORNER OF THE 20.0 ACRE TRACT
 - 4) 4,956.90' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE EAST 1/4 CORNER OF SECTION 30-16-11
- 3) STEVEN S. BROSEMER, L.S. 752, IN SURVEY F30002 IN THE SURVEY FILE FOR TOWNSHIP 16-11 DATED AUGUST 30, 1984 FOR PROJECT NUMBER 84104, FOR A PLAT OF SURVEY FOR A 40.0 ACRE TRACT LOCATED IN THE NORTH 1/2 OF SECTION 30-16-11, DATED AUGUST 30, 1984, SHOWS ON THIS DRAWING THAT **HE FOUND THE 1/2" REBAR WITH HIS RED "LS 752" PLASTIC CAP** THAT HE SET ON A PREVIOUS SURVEY AT THE WEST 1/4 CORNER OF SECTION 30-16-11 ON THE RANGE LINE.
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 934.0' NORTH ON THE RANGE LINE TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE FOUND FROM A PREVIOUS SURVEY AT THE NORTHWEST CORNER OF A 20.0 ACRE TRACT
 - 2) 934.0' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE FOUND FROM A PREVIOUS SURVEY AT THE SOUTHEAST CORNER OF A 20.0 ACRE TRACT

WEST QUARTER CORNER SECTION 30-16-11