

**NORTHWEST CORNER SECTION 31, TOWNSHIP 16 SOUTH, RANGE 11 EAST**

- 1) ON PAGE 57 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 14" X 3"** FOR THE CORNER TO SECTIONS 30 & 31-16-11 ON THE WEST TOWNSHIP BOUNDARY.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 35.20 CHAINS EAST TO THE 20' X 14" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 30 & 31-16-11
- 2) 75.20 CHAINS EAST TO THE 30' X 16" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 29, 30, 31 & 32-16-11
- 3) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 16" X 12" X 3" LIMESTONE THEY SET FOR THE WEST 1/4 CORNER OF SECTION 31-16-11
- 4) 80.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 20" X 10" X 8" LIMESTONE THEY SET FOR THE CORNER TO TOWNSHIPS 16 & 17 SOUTH, RANGES 10 & 11 EAST AT THE SOUTHWEST CORNER OF SECTION 31-16-11

- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 28 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 110 TO 112 PETITIONED BY W. R. COLGAN AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 16-10 AND 17-10 [PACKET 116 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JUNE 13, 1879, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD ON JULY 7, 1879, AND WAS RECORDED ON JULY 15, 1879 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 36-16-10 ON THE RANGE LINE ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS NORTH ON THE RANGE LINE TO THE NORTHEAST CORNER OF SECTION 6-16-10 ON THE 3<sup>RD</sup> STANDARD PARALLEL TO COMMENCE THIS ROAD SURVEY
- 2) THIS ROAD EXTENDS SOUTH ON THE RANGE LINE TO THE NORTHEAST CORNER OF SECTION 24-17-10 FOR THE TERMINUS OF THIS ROAD SURVEY

- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN AN AGREEMENT SURVEY DATED APRIL 15, 1880 FILED IN THE REGISTER OF SEEDS OFFICE ON PAGE 553 FOR HORN R. MAYS, JESSE FOSTER, AND REBECCA M. CURTIS TO ESTABLISH THE LINE BETWEEN THE EAST 1/2 OF THE SOUTHEAST 1/4 AND THE WEST 1/2 OF THE SOUTHEAST 1/4, ALSO THE SOUTHEAST CORNER OF THE WEST 1/2 OF THE SOUTHEAST 1/4, AND THE NORTHEAST CORNER OF THE WEST 1/2 OF THE SOUTHEAST 1/4, ALSO THE NORTHWEST CORNER OF THE SOUTHEAST 1/4, ALSO THE NORTHWEST CORNER OF THE SOUTHWEST 1/4, ALL IN SECTION 31-16-11, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 31-16-11 ON THE RANGE LINE ON THIS AGREEMENT SURVEY. THIS SURVEY IS FILED AT SURVEY F31001 IN THE SURVEY FILE FOR TOWNSHIP 16-11.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 40.06-1/4 CHAINS SOUTH ON THE RANGE LINE TO THE GOVERNMENT 1/4 SECTION CORNER STONE HE FOUND AND **HE RESET** FOR THE WEST 1/4 CORNER OF SECTION 31-16-11
- 2) 80.12-1/2 CHAINS SOUTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 31-16-11

- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 95 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 382 TO 384 PETITIONED BY JESSE FOSTER AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 16-10 AND 16-11 [PACKET 231 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON NOVEMBER 27, 1880, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD ON JANUARY 5, 1881, AND WAS RECORDED ON JANUARY 5, 1881 BY

WILLIAM F. EWING, COUNTY CLERK SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 31-16-11 ON THE RANGE LINE ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 4,964 FEET TO THE NORTHEAST CORNER OF SECTION 31-16-11, AT WHICH POINT THE VIEWERS CAUSED THE SURVEY TO TERMINATE
  - 2) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 5,280' TO THE NORTHWEST CORNER OF SECTION 36-16-10 TO COMMENCE THIS ROAD SURVEY
- 5) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON PAGE 197 DATED NOVEMBER 27, 1880, FOR A ROAD SURVEY IN TOWNSHIPS 16-10 & 16-11 APPARENTLY **FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 36-16-10 ON THE RANGE LINE ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 4,964 FEET TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 31-16-11; AND CONTINUES EAST ON THE SECTION LINE OVER SEVERAL ANGLE POINTS TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 32-16-11
  - 2) THIS ROAD EXTENDS WEST ON THE SECTION LINE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 36-16-10 TO COMMENCE THIS ROAD SURVEY
- 6) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F", ON PAGE 75 DATED NOVEMBER 27, 1883 FOR A ROAD IN TOWNSHIP 16, RANGES 10, 11, 12 & 13 FOR L. W. HUTCHINSON, PRINCIPAL PETITIONER, APPARENTLY **FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 25-16-10 ON THE RANGE LINE ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 2 MILES TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 26-16-10; THEN NORTH ON THE SECTION LINES FOR 1/4 OF A MILE TO THE STONE HE FOUND OR SET; THEN EXTENDS WEST ON THE SOUTH SIDE OF THE LINE TO THE STONE HE SET AT 1/4 OF A MILE NORTH OF THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 28-16-10; THEN SOUTH ON THE EAST SIDE OF THE SECTION LINE FOR 1/4 OF A MILE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 28-16-10; THEN WEST ON THE SECTION LINES FOR 1-1/2 MILES TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 29-16-10 TO BEGIN THIS ROAD SURVEY
  - 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 6 MILES TO THE SOUTHWEST CORNER OF SECTION 30-16-12 ON THE RANGE LINE; THEN EAST ON THE SECTION LINES FOR 2 MILES TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 28-16-12; THEN SEE THE SURVEY FOR THE ALIGNMENT ON THE SOUTH LINE OF SECTION 28-16-12 TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 28-16-12; THENCE EAST ON THE SECTION LINES OVER A ROAD ALREADY LAID OUT FOR 4-3/4 MILES TO THE SOUTHEAST CORNER OF THE SW1/4 OF THE SE1/4 OF SECTION 29-16-13 AT THE TERMINUS OF THE ROAD ALLOWED ON THIS ROAD SURVEY.
- 7) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY FOR ROAD NUMBER 248 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 578 TO 580 PETITION BY L. W. HUTCHASON AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 16-10, 16-11, 16-12 AND 16-13 [PACKET 483 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED IN NOVEMBER

1884, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD, **EXCEPT** ON THE SOUTH LINE OF SECTION 28-16-12 ITS WIDTH IS TO BE 80 FEET FOR 8 RODS, ON JANUARY 11, 1884 AS NOTED BY JOHN E. JONES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON JANUARY 30, 1884 BY ROLAND LARKIN, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 25-16-10 ON THE RANGE LINE THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 2 MILES TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 26-16-10; THEN NORTH ON THE SECTION LINES FOR 1/4 OF A MILE TO THE STONE HE FOUND OR SET; THEN EXTENDS WEST ON THE SOUTH SIDE OF THE LINE TO THE STONE HE SET AT 1/4 OF A MILE NORTH OF THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 28-16-10; THEN SOUTH ON THE EAST SIDE OF THE SECTION LINE FOR 1/4 OF A MILE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 28-16-10; THEN WEST ON THE SECTION LINES FOR 1-1/2 MILES TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 29-16-10 TO BEGIN THIS ROAD SURVEY
- 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 6 MILES TO THE SOUTHWEST CORNER OF SECTION 30-16-12 ON THE RANGE LINE; THEN EAST ON THE SECTION LINES FOR 2 MILES TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 28-16-12; THEN SEE THE SURVEY FOR THE ALIGNMENT ON THE SOUTH LINE OF SECTION 28-16-12 TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 28-16-12; THENCE EAST ON THE SECTION LINES OVER A ROAD ALREADY LAID OUT FOR 4-3/4 MILES TO THE SOUTHEAST CORNER OF THE SW1/4 OF THE SE1/4 OF SECTION 29-16-13 AT THE TERMINUS OF THE ROAD ALLOWED ON THIS ROAD SURVEY.

NORTHWEST CORNER SECTION 31-16-11