

NORTHWEST CORNER SECTION 34, TOWNSHIP 16 SOUTH, RANGE 11 EAST

- 1) ON PAGE 292 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 12" X 4"** FOR THE CORNER TO SECTIONS 27, 28, 33 & 34-16-11.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 40.25 CHAINS EAST TO THE 19" X 10" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 27 & 34-16-11
- 2) 80.50 CHAINS EAST TO THE 27" X 11" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 26, 27, 34 & 35-16-11

- 2) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN AN **INFORMAL SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 150 DATED MARCH 30, 1883 AT THE REQUEST OF GRANT, ET. AL. TO ESTABLISH THE CENTER CORNER SECTION 33-16-11 AND THE 1/8TH CORNERS ON THE NORTH, EAST & WEST LINES OF THE NORTHEAST 1/4 OF SAID SECTION 33-16-11, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 33-16-11 ON THIS **INFORMAL SURVEY**.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 20.13-1/2 CHAINS WEST TO THE STONE HE SET FOR THE NORTH 1/8TH CORNER OF THE NE1/4 OF SECTION 33-16-11
- 2) 40.27 CHAINS WEST TO THE STONE HE FOUND AT THE 1/4 CORNER ON THE NORTH LINE OF SECTION 33-16-11
- 3) 20.01-1/2 CHAINS SOUTH TO THE STONE HE SET FOR THE EAST 1/8TH CORNER OF THE NE1/4 OF SECTION 33-16-11
- 4) 40.03 CHAINS SOUTH TO THE STONE HE FOUND AT THE 1/4 CORNER ON THE EAST LINE OF SECTION 33-16-11

- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F", ON PAGE 75 DATED NOVEMBER 27, 1883 FOR A ROAD IN TOWNSHIP 16, RANGES 10, 11, 12 & 13 FOR L. W. HUTCHINSON, PRINCIPAL PETITIONER, APPARENTLY **FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 28-16-11 ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 27-16-10 AT A TURN TO THE NORTH ON THIS ROAD SURVEY
- 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 28-16-12, AND THEN CONTINUES EAST ON THE SECTION LINES FROM THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF THE SW1/4 OF SECTION 29-16-13 TO THE STONE HE FOUND ON THE EAST LINE OF LYON COUNTY AT THE SOUTHEAST CORNER OF SECTION 27-16-13 AT THE TERMINUS OF THIS ROAD SURVEY

- 4) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY FOR ROAD NUMBER 248 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 578 TO 580 PETITION BY L. W. HUTCHASON AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 16-10, 16-11, 16-12 AND 16-13 [PACKET 483 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED IN NOVEMBER 1884, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD, **EXCEPT ON THE SOUTH LINE OF SECTION 28-16-12 ITS WIDTH IS TO BE 80 FEET FOR 8 RODS**, ON JANUARY 11, 1884 AS NOTED BY JOHN E. JONES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON JANUARY 30, 1884 BY ROLAND LARKIN, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 28-16-11 THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

HIS INFORMATION IS CONTINUED ON PAGE 2

- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 5 MILES TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 26-16-10; THEN NORTH ON THE SECTION LINE FOR 1/4 OF A MILE TO THE STONE HE FOUND OR SET; THEN EXTENDS WEST ON THE SOUTH SIDE OF THE LINE TO THE STONE HE SET A 1/4 OF A MILE NORTH OF THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 28-16-10; THEN SOUTH ON THE EAST SIDE OF THE SECTION LINE FOR 1/4 OF A MILE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 28-16-10; THEN WEST ON THE SECTION LINES FOR 1-1/2 MILE TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 29-16-10 TO BEGIN THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 3 MILES TO THE SOUTHWEST CORNER OF SECTION 30-16-12 ON THE RANGE LINE; THEN EAST ON THE SECTION LINES FOR 2 MILES TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 28-16-12; THEN SEE THE SURVEY FOR THE ALIGNMENT ON THE SOUTH LINE OF SECTION 28-16-12 TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 28-16-12; THENCE EAST ON THE SECTION LINES OVER A ROAD ALREADY LAID OUT FOR 4-3/4 MILES TO THE SOUTHEAST CORNER OF THE SW1/4 OF THE SE1/4 OF SECTION 29-16-13 AT THE TERMINUS OF THE ROAD ALLOWED ON THIS ROAD SURVEY.
- 5) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 177, A ROAD SURVEY RECORDED IN SURVEY BOOK "E" ON PAGE 177 DATED MAY 31, 1887 FOR BY WILLIAM PORTER, PRINCIPAL PETITIONER, FOR A COUNTY ROAD IN TOWNSHIP 16-11, **APPARENTLY FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 33-16-11 ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINES "AS PER GOVERNMENT SURVEY" TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 16-16-11 TO END THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS SOUTH ON THE SECTION LINES "AS PER GOVERNMENT SURVEY" TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 33-16-11 ON THE TOWNSHIP LINE TO END THIS ROAD SURVEY
 - 3) **NOTE:** THE PORTION OF ROAD BETWEEN THE NORTHEAST CORNER OF SECTION 21-16-11 EXTENDING NORTH ON THE SECTION LINE FOR 1/2 MILE TO THE WEST 1/4 CORNER OF SECTION 15-16-11 WAS **REJECTED** BY THE BOARD OF COUNTY COMMISSIONERS – SEE ROAD RECORD BOOK "C" ON PAGE 352 – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR
- 6) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A ROAD SURVEY FOR ROAD NUMBER 360 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 350 TO 352 PETITIONED BY WILLIAM PORTER AND OTHERS FOR A ROAD IN TOWNSHIP 16-11 [PACKET 594 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON MAY 31, 1887, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD FROM THE SOUTHEAST CORNER OF SECTION 33-16-11 TO THE NORTHEAST CORNER OF SECTION 21-16-11, AND FROM THE WEST 1/4 CORNER OF SECTION 15-16-11 TO THE NORTHEAST CORNER OF SECTION 16-16-11, AS NOTED BY T. E. McMILLAN, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS ON JULY 6, 1887, AND RECORDED ON SEPTEMBER 19, 1887 BY ROLAND LAKIN, COUNTY CLERK, **APPARENTLY FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 33-16-11 ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THE ROAD AS SURVEYED EXTENDS NORTH ON THE SECTION LINES FOR 3 MILES "AS PER THE GOVERNMENT SURVEY" TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 16-16-11 AT THE TERMINUS OF THIS ROAD AS SURVEYED

- 2) THE ROAD AS SURVEYED EXTENDS SOUTH ON THE SECTION LINES FOR 1 MILE “AS PER THE GOVERNMENT SURVEY” TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 33-16-11 ON THE TOWNSHIP LINE TO COMMENCE THIS ROAD AS SURVEYED
 - 3) THE PORTION OF ROAD PETITIONED BETWEEN THE WEST 1/4 CORNER OF SECTION 15-16-11 EXTENDING SOUTH FOR 1/2 MILE TO THE NORTHEAST CORNER OF SECTION 21-16-11 WAS **REJECTED** BY THE BOARD OF COUNTY COMMISSIONERS
- 7) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN SURVEY NUMBER 180 SURVEYED JULY 15 & 16, 1889 AND RECORDED IN MISCELLANEOUS VOLUME 41 ON PAGE 522 IN THE REGISTER OF DEEDS OFFICE ON OCTOBER 14, 1889 TO ESTABLISH THE CORNERS OF THE SOUTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 34-16-11, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 34-16-11 ON THIS SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) 2,641.3’ EAST TO THE FLAG HE SET FOR THE NORTH 1/4 CORNER OF SECTION 34-16-11
 - 2) 5,282.6’ EAST TO THE TEMPORARY STAKE HE SET FOR THE NORTHEAST CORNER OF SECTION 34-16-11
 - 3) 7,888’ EAST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 35-16-11
 - 4) 1,324’ SOUTH TO THE STONE HE SET FOR THE WEST 1/16TH CORNER OF THE NW1/4 OF SECTION 34-16-11
 - 5) 2,648’ SOUTH TO THE STONE HE SET FOR THE WEST 1/4 CORNER OF SECTION 34-16-11
 - 6) 5,296’ SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 34-16-11
- 8) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 43, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK “E” ON PAGE 224 DATED APRIL 2, 1902 ORDERED BY L. D. DeCAMP TO LOCATE AND PERMANENTLY ESTABLISH THE EAST 1/4 CORNER AND THE CENTER CORNER OF SECTION 27-16-11 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 27-16-11 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 38, AND THERE IS ADDITIONAL INFORMATION IN PACKET “M 48” IN MISCELLANEOUS DRAWER 2 IN THE VAULT IN THE COUNTY ENGINEER’S OFFICE.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 40.05 CHAINS EAST TO THE FLAG HE SET FOR THE SOUTH 1/4 CORNER OF SECTION 27-16-11
 - 2) 80.10 CHAINS EAST TO THE FRAGMENTS OF STONE HE FOUND AND HE ACCEPTED FOR THE TRUE SOUTHEAST CORNER OF SECTION 27-16-11
 - 3) 119.26 CHAINS EAST TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 26-16-11 THAT WAS OUT OF LINE TO THE NORTH
- 9) COMMISSIONER’S ROAD JOURNAL BOOK “B”, PAGE 87
ON APRIL 22, 1952 A PETITION SIGNED BY LEE L. LOWDER FOR THE **VACATION** OF A ROAD IN TOWNSHIP 16-11 WAS PRESENTED TO GEORGE K. JACKSON, COUNTY CLERK. THE ROAD WAS VIEWED BY THE COUNTY COMMISSIONERS ON MAY 15, 1952 AND THE FINAL ORDER OF THE BOARD OF COUNTY COMMISSIONERS ON MAY 16, 1952 **VACATED** THE FOLLOWING ROAD:
- 1) BEGINNING AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 27-16-11 AND EAST ONE HALF MILE AND ENDING THERE

CONTINUED ON PAGE 4

- 10) COMMISSIONER'S ROAD JOURNAL BOOK "B", PAGE 115
 ON FEBRUARY 29, 1959, A PETITION SIGNED BY EDWARD W. FREDERIKSEN AND OTHERS FOR THE **VACATION** OF A ROAD IN TOWNSHIP 16-11 WAS PRESENTED TO W. A. STOLFUS, COUNTY CLERK. THE ROAD WAS VIEWED BY THE COUNTY COMMISSIONERS ON MARCH 20, 1959 AND THE FINAL ORDER OF THE BOARD OF COUNTY COMMISSIONERS ON MARCH 20, 1959 **VACATED** THE FOLLOWING ROAD:
 2) BEGINNING AT THE NORTHWEST CORNER OF THE NORTHEAST 1/4 OF SECTION 33-16-11, AND RUNNING THENCE EAST 1/2 MILE TO THE NORTHEAST CORNER OF SAID SECTION 33-16-11 AND THERE ENDING.
- 11) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 7, 1982, SAID THAT **HE FOUND A 3" X 3" LIMESTONE AT 3" DEEP WITH THE TOP 4" FRACTURED** AT THE NORTHWEST CORNER OF SECTION 34-16-11. **HE PLACED 1/2" REBARS ON THE EAST AND WEST SIDES OF THE CENTER OF THE STONE.** HIS TIES ARE MISSING FROM THE SURVEY TIE FILES.
- 12) GREGORY A. MILES, L.S. 667, IN A SURVEY DATED JUNE 9, 1982 AND FILED IN VOLUME 397 ON PAGE 245 IN THE REGISTER OF DEEDS OFFICE ON MARCH 9, 1983, FOR PROJECT NUMBER 82-75, AND SURVEY F28001 IN THE SURVEY FILE FOR TOWNSHIP 16-11 FOR A 10.00 ACRE TRACT OF LAND IN THE NORTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 28-16-11, SHOWED ON HIS DRAWING THAT **HE FOUND THE GLO STONE** AT THE SOUTHEAST CORNER OF SECTION 28-16-11. THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES.
HIS SURVEY DRAWING SHOWED THE FOLLOWING INFORMATION:
- 1) 1,322.72' NORTH TO THE 1/2" REBAR HE SET FOR THE "POINT OF BEGINNING" OF THE 10.00 ACRE TRACT [**NOTE:** HE DOES **NOT** CALL THIS 1/2" REBAR THE 1/16TH CORNER BUT THE REBAR IS LOCATED ON LINE AND HALFWAY BETWEEN THE GLO STONE THAT HE FOUND AT THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 28-16-11 AND THE GLO STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 28-16-11 – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]
 - 2) 2,316.96' NORTH TO THE 1/2" REBAR HE SET FOR THE NORTHEAST CORNER OF THE 10.00 ACRE TRACT
 - 3) 2,645.44' NORTH TO THE GLO STONE HE FOUND AT THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 28-16-11

NORTHWEST CORNER SECTION 34-16-11