

NORTH 1/4 CORNER SECTION 35, TOWNSHIP 16 SOUTH, RANGE 11 EAST

- 1) ON PAGE 289 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 15" X 12" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 26 & 35-16-11.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.70 CHAINS WEST TO THE 27" X 11" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 26, 27, 34 & 35-16-11
 - 2) 39.70 CHAINS EAST TO THE 24" X 11" X 6" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 25, 26, 35 & 36-16-11

- 2) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN SURVEY NUMBER 180 SURVEYED JULY 15 & 16, 1889 AND RECORDED IN MISCELLANEOUS VOLUME 41 ON PAGE 522 IN THE REGISTER OF DEEDS OFFICE ON OCTOBER 14, 1889 TO ESTABLISH THE CORNERS OF THE SOUTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 34-16-11, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 35-16-11 ON THIS SURVEY.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,605.4' WEST TO THE TEMPORARY STAKE HE SET FOR THE NORTHEAST CORNER OF SECTION 34-16-11
 - 2) 5,246.7' NORTH TO THE TEMPORARY FLAG HE SET FOR THE NORTH 1/4 CORNER OF SECTION 35-16-11
 - 3) 7,888' WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 34-16-11

- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 43, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 224 DATED APRIL 2, 1902 ORDERED BY L. D. DeCAMP TO LOCATE AND PERMANENTLY ESTABLISH THE EAST 1/4 CORNER AND THE CENTER CORNER OF SECTION 27-16-11 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE OUT OF LINE TO THE NORTH** AT THE SOUTH 1/4 CORNER OF SECTION 26-16-11 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 38, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 48" IN MISCELLANEOUS DRAWER 2 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.66 CHAINS WEST TO THE FRAGMENTS OF STONE THAT HE FOUND AND HE ACCEPTED AS THE TRUE SOUTHEAST CORNER OF SECTION 27-16-11
 - 2) 79.71 CHAINS WEST TO THE FLAG HE SET FOR THE SOUTH 1/4 CORNER OF SECTION 27-16-11
 - 3) 119.76 CHAINS WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 27-16-11

- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED AUGUST 27, 1990 FOR PROJECT NUMBER 90524, SURVEY F26001 IN THE SURVEY FILES FOR TOWNSHIP 16-11 TO SURVEY A PREVIOUSLY DESCRIBED 5.0 ACRE TRACT LOCATED IN THE SOUTHWEST 1/4 OF SECTION 26-16-11, SAID THAT HE DID **NOT** FIND OR RESET THE SOUTH 1/4 CORNER OF SECTION 26-16-11 ON THIS SURVEY AS HE RAN THE SECTION LINES FROM THE SOUTHWEST CORNER OF SECTION 26-16-11 EAST TO THE SOUTHEAST CORNER OF SECTION 26-16-11. THIS SURVEY WAS FILED IN VOLUME 455 ON PAGE 423 IN THE REGISTER OF DEEDS OFFICE ON SEPTEMBER 17, 1990.

NORTH QUARTER CORNER SECTION 35-16-11