

WEST 1/4 CORNER SECTION 35, TOWNSHIP 16 SOUTH, RANGE 11 EAST

- 1) ON PAGE 288 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 14" X 10" X 5"** FOR THE 1/4 CORNER BETWEEN SECTIONS 34 & 35-16-11.

- 2) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN SURVEY NUMBER 180 SURVEYED JULY 15 & 16, 1889 AND RECORDED IN MISCELLANEOUS VOLUME 41 ON PAGE 522 IN THE REGISTER OF DEEDS OFFICE ON OCTOBER 14, 1889 TO ESTABLISH THE CORNERS OF THE SOUTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 34-16-11, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 34-16-11 ON THIS SURVEY.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,659.8' NORTH TO THE TEMPORARY STAKE HE SET FOR THE NORTHEAST CORNER OF SECTION 34-16-11
 - 2) 7,912' NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 26-16-11

- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 43, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 224 DATED APRIL 2, 1902 ORDERED BY L. D. DeCAMP TO LOCATE AND PERMANENTLY ESTABLISH THE EAST 1/4 CORNER AND THE CENTER CORNER OF SECTION 27-16-11 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, APPARENTLY DID **NOT** FIND THE STONE AT THE EAST 1/4 CORNER OF SECTION 34-16-11 AS HE RAN THE SECTION LINES FROM THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 34-16-11 NORTH TO THE LOCATION OF THE NORTHEAST CORNER OF SECTION 27-16-11 AS LOCATED BY THE AFFIDAVIT OF W. M. PORTER ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 38, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 48" IN MISCELLANEOUS DRAWER 2 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

WEST QUARTER CORNER SECTION 35-16-11