

**WEST 1/4 CORNER SECTION 36, TOWNSHIP 16 SOUTH, RANGE 11 EAST**

- 1) ON PAGE 285 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 16" X 12" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 35 & 36-16-11.
  
- 2) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN SURVEY NUMBER 179, A **PERMANENT SURVEY** AT THE REQUEST OF JAMES W. WORSTELL TO ESTABLISH THE LINES AND CORNERS OF THE SOUTHEAST 1/4 OF SECTION 14 AND THE NORTHEAST 1/4 OF SECTION 23, ALL IN TOWNSHIP 16, RANGE 11 RECORDED IN SURVEY BOOK "F" ON PAGE 133 DATED JUNE 18 TO JULY 7, 1888, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 36-16-11 ON THIS **PERMANENT SURVEY**.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 15,878' NORTH TO THE GOVERNMENT STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 14-16-11
  - 2) 23,794' NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 11-16-11
  
- 3) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED FEBRUARY 12, 2008, FOR PROJECT NUMBER 07415-02, SURVEY F36001 IN THE SURVEY FILE FOR TOWNSHIP 16-11, FOR A SURVEY OF TWO TRACTS IN THE SOUTHWEST 1/4 OF SECTION 36-16-11 FOR MARK & TAMMY DENTON, SAID THAT HE SEARCHED FOR THE STONE AT THE WEST 1/4 CORNER OF SECTION 36-16-11, BUT HE DID **NOT** FIND THE STONE. HE CONSIDERED THAT THIS CORNER WAS **OBLITERATED**. HE DETERMINED THAT THE CORNER FENCE POST TO BE THE BEST EVIDENCE OF THE ORIGINAL LOCATION OF THE CORNER. **HE SET A 5/8" X 30" REBAR WITH A LYON COUNTY CAP ON THE WEST SIDE OF THE CORNER FENCE POST** FOR THE WEST 1/4 CORNER OF SECTION 36-16-11.
  - 1) 30.85' WNW TO A CONCRETE NAIL & WASHER IN A 20" HEDGE TREE
  - 2) 46.90' SW TO A CONCRETE NAIL & WASHER IN A 15" HEDGE TREE
  - 3) IN A LINE OF FENCE RUNNING NORTH AND SOUTH
  - 4) IN A LINE OF FENCE RUNNING EAST
  - 5) ON THE WEST SIDE OF A CORNER FENCE POST
  - 6) 17.35' SOUTH TO A 40 D NAIL & WASHER IN THE TOP OF A STEEL FENCE POSTHIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 2,648.30' NORTH TO THE 5/8" REBAR THROUGH THE STONE HE FOUND AT THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 36-16-11
  - 2) 2,662.81' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 36-16-11 ON THE TOWNSHIP LINE
  - 3) 1,321.07' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHWEST CORNER OF THE E1/2 OF THE SW1/4 OF SECTION 36-16-11
  - 4) 2,642.14' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHEAST CORNER OF THE SW1/4 OF SECTION 36-16-11
  - 5) 5,282.52' EAST TO THE 3/4" REBAR HE FOUND AT THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 36-16-11

WEST QUARTER CORNER SECTION 36-16-11