

NORTHWEST CORNER SECTION 01, TOWNSHIP 16 SOUTH, RANGE 12 EAST

- 1) ON PAGES 450 & 451 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 22" X 12" X 3"** FOR THE CORNER TO SECTIONS 1 & 2-16-12 ON THE 3RD STANDARD PARALLEL SOUTH OF THE BASE LINE AT 12 CHAINS 37 LINKS WEST OF THE CORNER TO SECTIONS 35 & 36, T. 15 S., R. 12 E. ON JANUARY 14, 1857.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 41.06 CHAINS SOUTH TO THE 12" X 8" X 6" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 1 & 2-16-12
 - 2) 81.06 CHAINS SOUTH TO THE 24" X 12" X 8" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 1, 2, 11 & 12-16-12

- 2) IN NOTES FOR THE STATE ROAD FROM DRAGON CREEK ON THE WYANDOTTE AND SANTA FE ROAD IN OSAGE COUNTY TO ALLEN IN BRECKENRIDGE COUNTY AS RECORDED IN ROAD RECORD BOOK "A" ON PAGE 36; THEY APPARENTLY **FOUND** THE NORTHWEST CORNER OF SECTION 1-16-12 ON THE 3RD STANDARD PARALLEL ON THIS ROAD SURVEY. THE ROAD WAS 66 FEET WIDE.
THE SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS WEST ON THE 3RD STANDARD PARALLEL WITH A DEVIATION BETWEEN SECTION 36-15-12 AND SECTION 1-16-12 TO THE SOUTHWEST CORNER OF THE TOWNSHIP [SOUTHWEST CORNER SECTION 31-15-11]; THENCE ??
 - 2) THIS ROAD EXTENDS EAST ON THE 3RD STANDARD PARALLEL TO THE SOUTHEAST CORNER OF SECTION 34-15-13 AT THE CORNER WHERE THE COUNTY LINE BETWEEN BRECKENRIDGE AND OSAGE COUNTIES INTERSECT THE 3RD STANDARD PARALLEL

- 3) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 111 RECORDED IN SURVEY BOOK "A" ON PAGE 202 DATED MAY 4, 1869 FOR A SURVEY OF SECTION 1-16-12, TO ESTABLISH THE CENTER CORNER, AND SUBDIVIDE THE SOUTHEAST 1/4, AND TO ESTABLISH THE 1/4 CORNER ON THE NORTHERN BOUNDARY OF SECTION 1, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 1-16-12 ON THE 3RD STANDARD PARALLEL ON THIS SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 157 RODS EAST ON THE 3RD STANDARD PARALLEL TO THE STONE HE SET FOR THE NORTH 1/4 CORNER OF SECTION 1-16-12
 - 2) 317 RODS EAST ON THE 3RD STANDARD PARALLEL TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 1-16-12

- 4) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 112 RECORDED IN SURVEY BOOK "A" ON PAGE 203 DATED MAY 5, 1869 FOR A SURVEY OF SECTION 2-16-12, TO ESTABLISH THE CENTER CORNER AND THE 1/4 CORNER ON THE NORTHERN BOUNDARY, AND TO REESTABLISH THE 1/4 CORNERS ON THE SOUTHERN AND EASTERN BOUNDARIES OF SECTION 2-16-12, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 2-16-12 ON THE 3RD STANDARD PARALLEL ON THIS SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 160 RODS WEST ON THE 3RD STANDARD PARALLEL TO THE STONE HE SET FOR THE NORTH 1/4 CORNER OF SECTION 2-16-12
 - 2) 317 RODS, 12 LINKS WEST ON THE 3RD STANDARD PARALLEL TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 2-16-12
 - 3) 163 RODS, 12 LINKS SOUTH TO THE STONE HE SET FOR THE EAST 1/4 CORNER OF SECTION 2-16-12

HIS INFORMATION IS CONTINUED ON PAGE 2

- 4) 323 RODS, 12 LINKS SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 2

- 5) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE RIGHT PAGE 152 DATED FEBRUARY 20, 1878, APPARENTLY **FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 1-16-12 ON THE 3RD STANDARD PARALLEL ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,640' SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF THE NW1/4 OF SECTION 1-16-12

NORTHWEST CORNER 01-16-12