

NORTH 1/16 CORNER SOUTHEAST QUARTER OF SECTION 03, TOWNSHIP 16 SOUTH, RANGE 12 EAST

- 1) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 23 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 90 TO 92 FOR A PETITION BY SIDNEY PUTMAN AND OTHERS COR A COUNTY ROAD IN TOWNSHIPS 15-12 AND 16-12 [PACKET 128 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JUNE 4, 1879, WAS ESTABLISHED ON JULY 7, 1879, AND WAS RECORDED ON JULY 11, 1879 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF THE WEST 1/2 OF THE NORTHEAST 1/4 OF SECTION 3-16-12 AT A TURN TO THE NORTH DUE TO ELM CREEK ON THIS ROAD SURVEY. FROM THE BEGINNING OF SAID ROAD TO THE NORTHWEST CORNER OF THE SOUTHEAST 1/4 OF SECTION 3-16-12 THE ROAD SHALL BE 50 FEET WIDE, AND THE BALANCE OF SAID ROAD IS TO BE 60 FEET WIDE.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS 50 FOOT WIDE ROAD EXTENDS WEST FOR 80 RODS TO THE SOUTHWEST CORNER OF THE W1/2 OF THE NE1/4 OF SECTION 3-16-12 AT A TURN TO THE SOUTH
- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 38, A ROAD SURVEY RECORDED IN SURVEY BOOK "E" ON PAGE 219 DATED FEBRUARY 25, 1902 FOR A COUNTY ROAD IN TOWNSHIP 16-12 FOR D. C. HOUCK, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF THE EAST 1/2 OF THE SOUTHEAST 1/4 OF SECTION 3-16-12 FOR THE NORTH END OF THIS ROAD SURVEY FOR A 50 FOOT WIDE ROAD LYING 25 FEET EACH SIDE OF THE LINE AS SURVEYED.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,627' SOUTH TO THE 3" X 12" X 15" STONE HE SET FOR THE SOUTHWEST CORNER OF THE E1/2 OF THE SE1/4 OF SECTION 3-16-12 AT THE SOUTH END OF THIS ROAD SURVEY
- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A ROAD SURVEY FOR ROAD NUMBER 570 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 145 THROUGH 148 BY A PETITION BY D. L. HOUCK AND OTHERS FOR THE VACATION AND RELOCATION OF A ROAD IN SECTION 3-16-12 [PACKET 720 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON FEBRUARY 25, 1902, WAS ESTABLISHED AS A 50 FOOT WIDE ROAD, 25 FEET ON EACH SIDE OF THE LINE SURVEYED, ON MARCH 6, 1902, AND RECORDED ON MARCH 23, 1902 BY ALVA J. SMITH, COUNTY SURVEYOR, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF THE EAST 1/2 OF THE SOUTHEAST 1/4 SECTION 3-16-12 TO BEGIN BOTH THE ROAD RELOCATED AND THE ROAD VACATED ON THIS ROAD SURVEY.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) THE ROAD RELOCATED EXTENDS SOUTH FOR 2,627 FEET TO THE 3" X 12" X 15" STONE HE SET AT THE SOUTHWEST CORNER OF THE E1/2 OF THE SE1/4 OF SECTION 3-16-12 TO END THE ROAD RELOCATED ON THIS ROAD SURVEY
- 2) THE ROAD **VACATED** EXTENDS WEST FOR 1/4 MILE TO THE NORTHWEST CORNER OF THE SE1/4 OF SECTION 3-16-1, THEN EXTENDS SOUTH FOR 1/2 MILE TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 3-16-12 TO END THE ROAD **VACATED** ON THIS ROAD SURVEY

NORTH SIXTEENTH CORNER SOUTHEAST QUARTER 03-16-12