

NORTH 1/16 CORNER NORTHEAST QUARTER OF SECTION 06, TOWNSHIP 16 SOUTH, RANGE 12 EAST

- 1) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 29 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 114 TO 116 PETITIONED BY JAMES JONES AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 16-12 AND 17-12 [PACKET 124 IN THE VAULT IN THE COUNTY ENGINEERS OFFICE] THAT HE SURVEYED ON JULY 10, 1879, WAS ESTABLISHED AS A 50 FOOT WIDE ROAD ON JULY 12, 1879, AND RECORDED ON JULY 16, 1879, SAID THAT **HE SET A STONE AT 80 RODS WEST ON THE 3RD STANDARD PARALLEL FROM THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 6-16-12 TO COMMENCE THIS ROAD SURVEY.**

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 80 RODS EAST ON THE 3RD STANDARD PARALLEL TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 6-16-12
 - 2) THIS ROAD EXTENDS SOUTH TO THE SOUTHWEST CORNER OF THE E1/2 OF THE NE1/4 OF SECTION 7-16-12 AT A TURN TO THE EAST
- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE RIGHT SIDE PAGE 166 BUT DATED JULY 10, 1879, FOR A COUNTY ROAD IN TOWNSHIPS 16-12 AND 17-12, APPARENTLY **FOUND OR SET A STONE ON THE 3RD STANDARD PARALLEL AT 80 RODS WEST OF THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 6-16-12 TO COMMENCE THIS ROAD SURVEY.**

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 80 RODS EAST ON THE 3RD STANDARD PARALLEL TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 6-16-12
- 2) 5,280' SOUTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF THE NW1/4 OF THE NE1/4 OF SECTION 7-16-12

- 3) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 113, RECORDED IN SURVEY BOOK "E" ON PAGE 113 DATED AUGUST 17-19, 1885, AND RECORDED IN VOLUME 41 ON PAGE 34 IN THE REGISTER OF DEEDS OFFICE ON JANUARY 27, 1887 AND SURVEY F06001 IN THE SURVEY FILE FOR TOWNSHIP 16-11, SURVEYED PER THE ORDER OF THE **DISTRICT COURT OF LYON COUNTY TO SURVEY AND SUBDIVIDE SECTION 6-16-12, SAID THAT HE SET A 3" X 6" X 12" LIMESTONE PROPERLY NOTCHED MARKED "1/8"** FOR THE PERMANENT NORTH 1/8TH CORNER OF THE NORTHEAST 1/4 OF SECTION 6-16-12 ON THE 3RD STANDARD PARALLEL AT 1,320 FEET WEST OF THE STONE THAT HE SET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 6-16-12 ON THIS **DISTRICT COURT ORDERED SURVEY.**

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,320' EAST ON THE 3RD STANDARD PARALLEL TO THE STONE HE SET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 6-16-12
- 2) 2,112' EAST ON THE 3RD STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 31-15-12
- 3) 3,963' EAST ON THE 3RD STANDARD PARALLEL TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 5-16-12
- 4) 4,752' EAST ON THE 3RD STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 32-15-12
- 5) 6,606.6.6' EAST ON THE 3RD STANDARD PARALLEL TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 5-16-12
- 6) 1,426' SOUTH TO THE 2" X 8" X 12" LIMESTONE HE SET FOR THE PERMANENT CENTER CORNER OF THE NE1/4 OF SECTION 6-16-12

HIS INFORMATION IS CONTINUED ON PAGE 2

- 7) 2,746' SOUTH TO THE 3" X 6" X 12" LIMESTONE HE SET FOR THE PERMANENT SOUTH 1/8TH CORNER OF THE NE1/4 OF SECTION 6-16-12
- 8) 528' WEST ON THE 3RD STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 31-15-12
- 9) 1,320' WEST ON THE 3RD STANDARD PARALLEL TO THE 3" X 8" X 14" LIMESTONE HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SEC. 6-16-12
- 10) 2,640' WEST ON THE 3RD STANDARD PARALLEL TO THE 3" X 6" X 12" LIMESTONE HE SET FOR THE PERMANENT NORTH 1/8TH CORNER OF THE NW1/4 OF SECTION 6-16-12
- 11) 3,168' WEST ON THE 3RD STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 31-15-12
- 12) 3,768' WEST ON THE 3RD STANDARD PARALLEL TO THE STONE HE FOUND AT THE TOWNSHIP CORNER AT THE NORTHWEST CORNER OF SECTION 6-16-12

NORTH SIXTEENTH CORNER NORTHEAST QUARTER 06-16-12