

**NORTH 1/16 CORNER OF NORTHWEST QUARTER OF SECTION 06, TOWNSHIP 16 SOUTH, RANGE 12 EAST**

- 1) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A SURVEY RECORDED IN SURVEY BOOK "E" ON PAGE 25 AND DATED APRIL 1884, SAID THAT **HE SET THE NORTH 1/8<sup>TH</sup> CORNER ON THE NORTH SIDE OF THE NORTHWEST 1/4 OF SECTION 6-16-12 ON THE 3<sup>RD</sup> STANDARD PARALLEL ON THIS SURVEY. HE DID NOT DESCRIBE THE MONUMENT THAT HE SET FOR THIS 1/8<sup>TH</sup> CORNER.**
  
- 2) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 113, RECORDED IN SURVEY BOOK "E" ON PAGE 113 DATED AUGUST 17-19, 1885, AND RECORDED IN VOLUME 41 ON PAGE 34 IN THE REGISTER OF DEEDS OFFICE ON JANUARY 27, 1887 AND SURVEY F06001 IN THE SURVEY FILE FOR TOWNSHIP 16-11, SURVEYED PER THE ORDER OF THE **DISTRICT COURT OF LYON COUNTY TO SURVEY AND SUBDIVIDE SECTION 6-16-12, SAID THAT HE SET A 3" X 6" X 12" LIMESTONE PROPERLY NOTCHED MARKED "1/8"** FOR THE PERMANENT NORTH 1/8<sup>TH</sup> CORNER OF THE NORTHWEST 1/4 OF SECTION 6-16-12 ON THE 3<sup>RD</sup> STANDARD PARALLEL AND 1,320' WEST TO THE STONE THAT HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 6-16-12 ON THIS **DISTRICT COURT ORDERED SURVEY.**  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 528' WEST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 31-15-12
  - 2) 1,128' WEST IN THE 3<sup>RD</sup> STANDARD PARALLEL TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 6-16-12 AT THE TOWNSHIP CORNER ON THE RANGE LINE
  - 3) 1,320' EAST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE 3" X 8" X 14" LIMESTONE HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 6-16-12
  - 4) 2,112' EAST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 31-15-12
  - 5) 2,640' EAST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE 3" X 6" X 12" LIMESTONE HE SET FOR THE PERMANENT NORTH 1/8<sup>TH</sup> CORNER OF THE NE1/4 OF SECTION 6-16-12
  - 6) 3,960' EAST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE STONE HE SET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 6-16-12
  - 7) 4,752' EAST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 31-15-12
  - 8) 6,603' EAST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 5-16-12
  - 9) 7,392' EAST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 32-15-12
  - 10) 9,246.6' EAST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 5-16-12
  - 11) 1,650' SOUTH TO THE 4" X 17" X 12" LIMESTONE HE SET ON LINE WITH THE WITNESS STONE THAT HE SET FOR THE PERMANENT SOUTH 1/8<sup>TH</sup> CORNER OF THE SW1/4 OF SECTION 6-16-12
  
- 10) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 30, 2013, FOR PROJECT NUMBER 13262-02 TO LOCATE A CERTAIN BRIDGE IN THE SOUTHWEST 1/4 OF SECTION 36-15-11 FOR THE LYON COUNTY ROAD & BRIDGE DEPARTMENT FOR BRIDGE REPLACEMENT PROJECT 13-37, SURVEY F36004 IN THE SURVEY FILE FOR TOWNSHIP 15-11, SAID THAT HE EXCAVATED WITH A LYON COUNTY BACKHOE AND **HE FOUND THE 3" X 6" YELLOW LIMESTONE** AT THE NORTH 1/16<sup>TH</sup> CORNER OF THE NORTHWEST 1/4 OF SECTION 6-16-12 FROM THE DISTRICT COURT ORDERED SURVEY RECORDED IN VOLUME 41 ON PAGE 34 IN 1887 IN THE REGISTER OF DEEDS OFFICE, AND SURVEY

NUMBER 113 RECORDED IN SURVEY BOOK "E" ON PAGE 113 IN 1885 IN THE COUNTY SURVEYORS OFFICE.

- 1) **5/8" X 24" IRON PIN WITH A LYON COUNTY CAP SET OVER THE CENTER OF THE STONE**
- 2) **1/2" X 24" IRON PINS WITH "S. BROSEMER" CAPS SET ON THE NORTH AND SOUTH SIDES OF THE STONE**
- 3) 26.70' SSE TO A CONCRETE NAIL & BOTTLE CAP IN THE NORTH FACE OF A BRACE POST
- 4) 25.50' SOUTH TO A CONCRETE NAIL & BOTTLECAP IN THE NORTH FACE OF A TIE POST
- 5) 28.00' SSW TO A CONCRETE NAIL & BOTTLECAP IN THE NORTH FACE OF A BRACE POST
- 6) 2.50' SOUTH TO THE CENTERLINE OF THE TRAVELED WAY OF COUNTY ROAD 370 EAST-WEST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 526.77' WEST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE 5/8" X 30" IRON PIN WITH A LYON COUNTY CAP HE SET FOR THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 35-15-11
- 2) 1,127.17' WEST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE 6" X 9" LIMESTONE HE FOUND AT THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 6-16-12 AT THE TOWNSHIP CORNER ON THE RANGE LINE
- 3) 3,168.79' WEST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE 5/8" X 24" IRON PIN WITH A LYON COUNTY CAP HE SET FOR THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 36-15-11
- 4) 4,482.81' WEST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE 1/2" X 24" IRON PIN WITH HIS "S. BROSEMER" CAP HE SET FOR P. I. STATION 13+28.00 FOR AN ANGLE TO THE NORTHEASTERLY
- 5) 5,810.81' WEST ON THE 3<sup>RD</sup> STANDARD PARALLEL TO THE SQUARE 5/8" IRON PIN [AND STONE] HE FOUND AT THE SOUTHWEST CORNER OF SECTION 36-15-11 AT STATION 0+00.00

NORTH SIXTEENTH CORNER NORTHWEST QUARTER 06-16-12