

NORTHWEST CORNER SECTION 06, TOWNSHIP 16 SOUTH, RANGE 12 EAST

- 1) ON PAGE 83 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT THEY INTERSECTED THE 3RD STANDARD PARALLEL AT 9 CHAINS & 70 LINKS WEST OF THE CORNER TO TOWNSHIP 15 SOUTH, RANGES 11 & 12 EAST ON DECEMBER 18,1856, BUT THE NOTES DO NOT STATE THAT THEY SET THIS TOWNSHIP CORNER.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 42.75 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 16" X 14" X 6" LIMESTONE THEY SET AT THE WEST 1/4 CORNER OF SECTION 6-16-12
 - 2) 82.75 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 14" X 14" X 3" LIMESTONE THEY SET AT THE CORNER TO SECTIONS 6 & 7-16-12
- 2) IN NOTES FOR THE STATE ROAD FROM DRAGON CREEK ON THE WYANDOTTE AND SANTA FE ROAD IN OSAGE COUNTY TO ALLEN IN BRECKENRIDGE COUNTY AS RECORDED IN ROAD RECORD BOOK "A" ON PAGE 36; THEY APPARENTLY **FOUND** THE NORTHWEST CORNER OF SECTION 6-16-12 ON THE 3RD STANDARD PARALLEL ON THIS ROAD SURVEY. THE ROAD WAS 66 FEET WIDE.

THE SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS WEST ON THE 3RD STANDARD PARALLEL WITH A DEVIATION BETWEEN SECTION 36-15-12 AND SECTION 1-16-12 TO THE SOUTHWEST CORNER OF THE TOWNSHIP [SOUTHWEST CORNER SECTION 31-15-11]; THENCE ??
- 2) THIS ROAD EXTENDS EAST ON THE 3RD STANDARD PARALLEL TO THE SOUTHEAST CORNER OF SECTION 34-15-13 AT THE CORNER WHERE THE COUNTY LINE BETWEEN BRECKENRIDGE AND OSAGE COUNTIES INTERSECT THE 3RD STANDARD PARALLEL

- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 19 FOR A ROAD IN TOWNSHIPS 15 & 16, RANGE 11 FOR J. S. GRIMSLEY, PRINCIPAL PETITIONER, DATED AUGUST 8, 1882, SAID THAT **HE FOUND THE STONE** AT THE CORNER TO RANGES 11 & 12, TOWNSHIP 16 ON THE 3RD STANDARD PARALLEL ON THIS ROAD SURVEY.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS EAST ON THE 3RD STANDARD PARALLEL FOR 640 FEET TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 31-15-12; THEN NORTH ON THE RANGE LINE FOR 3 MILES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 19-15-12 ON THE LYON AND WABAUNSEE COUNTY LINE TO BEGIN THIS ROAD SURVEY
- 2) THIS ROAD EXTENDS SOUTH ON THE RANGE LINE FOR 1 MILE TO THE SOUTHEAST CORNER OF SECTION 1-16-11; THEN WEST ON THE SECTION LINES FOR 350 FEET TO AN ANGLE POINT; THEN N. 80° W. FOR 300 FEET TO AN ANGLE POINT; THEN S. 70° W. FOR 300 FEET TO INTERSECT THE SECTION LINE ON THE SOUTH SIDE OF SECTION 1-16-11 AND CONTINUES WEST ON THE SECTION LINES TO THE SOUTHWEST CORNER OF SECTION 2-16-11 AT THE TERMINUS OF THIS ROAD SURVEY

- 4) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY FOR ROAD NUMBER 186 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 330 TO 332 PETITIONED BY J. S. GRIMSLEY AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 15-11 & 16-11 [PACKET 401 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON AUGUST 8, 1882, AND WAS ESTABLISHED AS A 50 FOOT ROAD, **EXCEPT** FOR THE DISTANCE OF 80 RODS SOUTH OF THE NORTHEAST CORNER OF THE SOUTHEAST 1/4 OF SECTION 1-16-11 WHICH SHALL BE 35 FEET, ON OCTOBER 5, 1882 AS NOTED BY HUGH F. HOLMES,

CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON OCTOBER 24, 1882 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE TOWNSHIP CORNER BETWEEN RANGES 11 & 12 AT THE NORTHEAST CORNER OF SECTION 1-16-11 ON THE 3RD STANDARD PARALLEL ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS EAST ON THE 3RD STANDARD PARALLEL FOR 640 FEET TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 31-15-12; THEN NORTH ON THE RANGE LINE FOR 3 MILES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 19-15-12 ON THE LYON AND WABAUNSEE COUNTY LINE TO BEGIN THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS SOUTH ON THE RANGE LINE FOR 1 MILE TO THE SOUTHEAST CORNER OF SECTION 1-16-11; THEN WEST ON THE SECTION LINES FOR 350 FEET TO AN ANGLE POINT; THEN N. 80° W. FOR 300 FEET TO AN ANGLE POINT; THEN S. 70° W. FOR 300 FEET TO INTERSECT THE SECTION LINE ON THE SOUTH SIDE OF SECTION 1-16-11 AND CONTINUES WEST ON THE SECTION LINES TO THE SOUTHWEST CORNER OF SECTION 2-16-11 AT THE TERMINUS OF THIS ROAD SURVEY
- 5) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 113, RECORDED IN SURVEY BOOK "E" ON PAGE 113 DATED AUGUST 17-19, 1885, AND RECORDED IN VOLUME 41 ON PAGE 34 IN THE REGISTER OF DEEDS OFFICE ON JANUARY 27, 1887 AND SURVEY F06001 IN THE SURVEY FILE FOR TOWNSHIP 16-11, SURVEYED PER THE ORDER OF THE **DISTRICT COURT OF LYON COUNTY** TO SURVEY AND SUBDIVIDE SECTION 6-16-12, SAID THAT **HE FOUND THE STONE** AT THE TOWNSHIP CORNER AT THE NORTHWEST CORNER OF SECTION 6-16-12 ON THE 3RD STANDARD PARALLEL ON THIS **DISTRICT COURT ORDERED SURVEY**.
- HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 600' EAST ON THE 3RD STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 31-15-12
 - 2) 1,128' EAST ON THE 3RD STANDARD PARALLEL TO THE 3" X 6" X 12" LIMESTONE HE SET FOR THE PERMANENT NORTH 1/8TH CORNER OF THE NW1/4 OF SECTION 6-15-12
 - 3) 2,448' EAST ON THE 3RD STANDARD PARALLEL TO THE 3" X 8" X 14" LIMESTONE HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 6-16-12
 - 4) 3,240' EAST ON THE 3RD STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 31-15-12
 - 5) 3,768' EAST ON THE 3RD STANDARD PARALLEL TO THE 3" X 6" X 12" LIMESTONE HE SET FOR THE PERMANENT NORTH 1/8TH CORNER OF THE NE1/4 OF SECTION 6-16-12
 - 6) 5,088' EAST ON THE 3RD STANDARD PARALLEL TO THE STONE HE SET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 6-16-12
 - 7) 5,880' EAST ON THE 3RD STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 31-15-12
 - 8) 7,731.0' EAST ON THE 3RD STANDARD PARALLEL TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 5-16-12
 - 9) 8,520' EAST ON THE 3RD STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 32-15-12
 - 10) 10,374.6' EAST ON THE 3RD STANDARD PARALLEL TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 5-16-12
 - 11) 1,650' SOUTH ON THE RANGE LINE TO A 3" X 7" X 12" LIMESTONE HE SET ON LINE WITH THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SEC. 5-16-12
- 6) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 155 OF TERM 2, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGES 78 & 79 DATED

MARCH 4-6, 1909 AT THE ORDER OF LeMONT DeCAMP TO ESTABLISH THE CORNERS AND BOUNDARIES OF LOTS 3 & 4 OF SECTION 1-16-11 AND ANY OTHER CORNERS THAT MIGHT BE NECESSARY IN SAID SECTION TO ESTABLISH THE SAID CORNERS AND BOUNDARIES OF SAID LOTS, SAID THAT **HE PLANTED A STONE** FOR THE NORTHEAST CORNER OF SECTION 1-16-11 FOR THE TOWNSHIP CORNER ON THE 3RD STANDARD PARALLEL. HE SET THIS STONE ON LINE BETWEEN THE STONES THAT HE FOUND AT THE SOUTHEAST AND SOUTHWEST CORNERS OF SECTION 36-15-11 ON THE 3RD STANDARD PARALLEL AND AT 600.4' WEST OF THE STONE THAT HE FOUND AT THE TOWNSHIP CORNER BETWEEN SECTIONS 36-15-11 AND 31-15-12, AND ON THE RANGE LINE FROM THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 12-16-11 THROUGH THE ORIGINAL GOVERNMENT STONE THAT HE FOUND AT THE EAST 1/4 CORNER OF SECTION 12-16-11 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 600.4' EAST ON THE 3RD STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 36-15-11

- 7) SURVEY SR #1001 IN THE LARGE SURVEY DRAWER FOR TOWNSHIP 16-11, A SKETCH OF **RABOURN ROAD** THRU SECTION 1-16-11, DATED MARCH 10, 1920, SHOWS THAT THE SURVEYOR **FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 1-16-11 AT THE TOWNSHIP CORNER ON THE 3RD STANDARD PARALLEL ON THIS ROAD SURVEY. THE SURVEY IS NOT SIGNED. THERE IS A NOTE ON THE SURVEY THAT THE ROAD IS TO BE 20 FEET ON EACH SIDE OF THE CENTERLINE SHOWN ON THE DRAWING.

THE SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,264 FEET SOUTH ON THE RANGE LINE TO THE POINT OF BEGINNING OF THIS ROAD SURVEY; THENCE S. 13°50' W. FOR 262 FEET; THENCE S. 80° 40' W. RO 1,275 FEET; THENCE S. 13°20' E. FOR 431 FEET; THENCE S. 23°40' W. FOR 220.6 FEET; THENCE S. 53°00' W. FOR 239.5 FEET; THENCE N. 74°40' W. FOR 1,030.7 FEET TO THE STONE HE FOUND AT THE CENTER OF SECTION 1-16-11; THENCE S, 81°10' W. ON THE 1/2 SECTION LINE FOR 2,583 FEET TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 1-16-11 TO END THIS ROAD SURVEY
- 2) THIS ROAD SURVEY IS RECORDED IN ROAD RECORD BOOK "E" ON PAGE 73 AS ROAD NUMBER 716 [PACKET 835 IN THE VAULT IN THE COUNTY ENGINEERS OFFICE

- 8) COMMISSIONER'S ROAD JOURNAL BOOK "A", PAGE 63
ON JANUARY 5, 1920 A PETITION SIGNED BY J. A. RABOURN AND OTHERS FOR THE VACATION AND RELOCATION OF A ROAD IN TOWNSHIP 16-11 WAS PRESENTED TO THE BOARD OF COUNTY COMMISSIONERS. THE ROAD WAS VIEWED ON MARCH 1, 1920, AND THE FINAL ORDER WAS ISSUED ON MARCH 5, 1920 TO ACCEPT THE VIEWERS REPORT AS FOLLOWS:
 - 1) THAT THE PART OF THE PETITION REQUESTING THE VACATION OF THE ROAD BE **NOT** GRANTED FOR THE REASON THAT THE ROAD MAY BE NEEDED IN THE FUTURE
 - 2) THAT THE ROAD BE LOCATED AT AS FOLLOWS: BEGINNING AT A POINT ON THE EAST LINE OF SECTION 1-16-11 A FEW RODS NORTH OF THE SOUTHEAST CORNER OF MRS. WITHINGTON LAND; THENCE SOUTHWESTERLY ALONG THE SAID OF SAID RAVINE TO MRS. BURNS LAND; THENCE WEST ALONG THE NORTH PART OF MRS. BURNS LAND BUT 20 FEET SOUTH THEREOF TO A POINT NORTHWEST OF J. A. RABOURN HOUSE; THENCE IN A SOUTHERLY AND SOUTHWESTERLY DIRECTION ACROSS 142 CREEK; THENCE IN A NORTHWESTERLY DIRECTION TO THE CENTER OF SAID SECTION 1; THENCE WEST ON THE 1/2 SECTION LINE TO THE WEST LIND OF SAID SECTION 1-16-11.
 - 3) ROAD TO BE 40 FEET WIDE, 20 FEET EACH SIDE OF THE SURVEYED LINE

CONTINUED ON PAGE 4

- 9) W. G. RUGGLES, COUNTY ENGINEER FROM 1915 TO 1928, IN A ROAD SURVEY FOR ROAD NUMBER 716 RECORDED IN ROAD RECORD BOOK "E" ON PAGE 73 PETITIONED BY J. A. RABOURN AND OTHERS FOR THE VACATION AND RELOCATION OF A ROAD IN TOWNSHIPS 16-11 AND 16-12 [PACKET 835 IN THE VAULT IN THE COUNTY ENGINEERS OFFICE] WAS VIEWED BY THE COUNTY COMMISSIONERS AND THE COUNTY SURVEYOR ON FEBRUARY 7, 1920, SAID THAT HE FOUND THE STONE AT THE CENTER CORNER OF SECTION 1-16-11 ON THIS ROAD SURVEY. THE VIEWERS RECOMMENDED THAT THE PART OF THE PETITION REQUESTING THE VACATION OF THE ROAD BE **NOT** GRANTED FOR THE REASON THAT THE ROAD MAY BE NEEDED IN THE FUTURE. THEY ALSO RECOMMENDED THAT THE ROAD BE LOCATED AT 40 FEET IN WIDTH, 20 FEET EACH SIDE OF THE SURVEYED LINE, AS FOLLOWS: BEGINNING AT A POINT ON THE EAST LINE OF SECTION 1-16-11 A FEW RODS NORTH OF THE SOUTHEAST CORNER OF MRS. WITHINGTON LAND; THENCE SOUTHWESTERLY ALONG THE SAID OF SAID RAVINE TO MRS. BURNS LAND; THENCE WEST ALONG THE NORTH PART OF MRS. BURNS LAND BUT 20 FEET SOUTH THEREOF TO A POINT NORTHWEST OF J. A. RABOURN HOUSE; THENCE IN A SOUTHERLY AND SOUTHWESTERLY DIRECTION ACROSS 142 CREEK; THENCE IN A NORTHWESTERLY DIRECTION TO THE CENTER OF SAID SECTION 1; THENCE WEST ON THE 1/2 SECTION LINE TO THE WEST LIND OF SAID SECTION 1-16-11.

ON MARCH 20, 1920 IN THE NOTES IN THE *RETURN OF SURVEY AND PLAT* IT STATES: THE ABOVE REPORT OF VIEWERS HAVING BEEN READ BEFORE THE BOARD OF COUNTY COMMISSIONERS, AND SAID REPORT BEING FAVORABLE AND NO LEGAL OBJECTIONS APPEARING AGAINST SAID REPORT, AND THE BOARD BEING SATISFIED THAT THE CONFORMATION OF SUCH REPORT WILL BE OF PUBLIC UTILITY, DO ORDER THAT SAID ROAD SURVEY BE RECORDED AS RECOMMENDED IN SAID REPORT. IT IS ALSO ORDERED THAT THE TRUSTEES OF THE RESPECTIVE TOWNSHIPS BE DIRECTED TO CAUSE THE SAME TO BE OPENED FOR PUBLIC TRAVEL.

- 10) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 10, 2003, FOR PROJECT NUMBER 03097-02 TO DETERMINE THE 3RD STANDARD PARALLEL IN THE VICINITY OF SECTION 36-15-11 FOR THE LYON COUNTY ROAD & BRIDGE DEPARTMENT FOR BANK STABILIZATION PROJECT 03-BW, SAID THAT **HE FOUND A 6" X 9" LIMESTONE** AT THE NORTHEAST CORNER OF SECTION 1-16-11 AT THE TOWNSHIP CORNER ON THE 3RD STANDARD PARALLEL FROM A SURVEY RECORDED IN PERMANENT SURVEY BOOK "D" ON PAGE 78. **HE DROVE A 5/8" X 24" REBAR WITH A LYON COUNTY CAP ON THE SOUTH SIDE OF THE STONE.**

- 1) 27.5' EAST TO A FENCE TO THE SOUTH
- 2) 34.0' SOUTH TO A LINE OF FENCE TO THE EAST [EXTENDED]
- 3) 58.2' SSE TO A 40 D NAIL & WASHER IN A GATE POST
- 4) 42.5' SE TO A 40 D NAIL & WASHER IN A CORNER FENCE POST
- 5) 46.8' SE TO A CONCRETE NAIL & WASHER IN A BRACE POST

HIS SURVEY NOTES GIVES THE FOLLOWING INFORMATION:

- 1) 4,683.62' WEST ON THE 3RD STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 36-15-11

- 11) KIM LOUIS HUXMAN, L.S. 975, IN A LAND SURVEY REFERENCE REPORT DATED MAY 12, 2004, FOR KDOT PROJECT 99-56-K7443-01, SAID THAT **HE FOUND THE 6" X 9" LIMESTONE WITH A 5/8" X 24" REBAR WITH A LYON COUNTY CAP ON THE SOUTH SIDE OF THE STONE** AT THE NORTHWEST CORNER OF SECTION 6-16-12 AT THE TOWNSHIP CORNER ON THE 3RD STANDARD PARALLEL FROM RECORDED TIES BY STEVEN S. BROSEMER, L.S. 752, DATED FEBRUARY 2003. KDOT CORNER NUMBER 63006

HIS TIES ARE ON PAGE 5

- 1) 27.5' EAST TO A FENCE TO THE SOUTH
 - 2) 34.0' SOUTH TO A LINE OF FENCE TO THE EAST [EXTENDED]
 - 3) 58.2' SSE TO A 40 D NAIL & WASHER IN A GATE POST
 - 4) 42.5' SE TO A 40 D NAIL & WASHER IN A CORNER FENCE POST
 - 5) 46.8' SE TO A CONCRETE NAIL & WASHER IN A BRACE POST
- 12) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED MAY 9, 2012 FOR PROJECT NUMBER 12098-02 FOR SURVEY F06002 IN THE SURVEY FILE FOR TOWNSHIP 16-12, A SURVEY FOR A TRACT IN THE SOUTHWEST QUARTER OF SECTION 6-20-12 FOR BILL MARTIN, SAID THAT **HE FOUND THE 6" X 9" LIMESTONE** AT THE NORTHWEST CORNER OF SECTION 6-16-12 AT THE TOWNSHIP CORNER ON THE 3RD STANDARD PARALLEL FROM HIS EXISTING REFERENCE TIES ON FILE AT THE COUNTY SURVEYOR'S OFFICE. HE NOTED THAT HE HAD FOUND THIS STONE IN 2003.
- 1) 5/8" IRON PIN ON THE SOUTH SIDE CENTER OF THE STONE
 - 2) 27.5' EAST TO A FENCE TO THE SOUTH
 - 3) 34' SOUTH TO A FENCE TO THE EAST
 - 4) 58.25' SSE TO A CONCRETE NAIL & WASHER IN A GATE POST SET
 - 5) 42.5' SE TO A 40 D NAIL & WASHER IN A CORNER FENCE POST FOUND
 - 6) 46.8' SE TO A CONCRETE NAIL & WASHER IN A BRACE POST FOUND
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 5,448.36' SOUTH ON THE RANGE LINE TO THE 13" BOLT WITH A GEAR ON TOP HE SET FOR THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 6-16-12
 - 2) 8,091.45' SOUTH ON THE RANGE LINE TO THE 5/8" REBAR WITH THE REMAINS OF A CAP HE FOUND AT THE SOUTHEAST CORNER OF THE NW1/4 OF SECTION 7-16-12
 - 3) 10,734.54' SOUTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 7-16-12
- 13) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 30, 2013, FOR PROJECT NUMBER 13262-02 TO LOCATE A CERTAIN BRIDGE IN THE SOUTHWEST 1/4 OF SECTION 36-15-11 FOR THE LYON COUNTY ROAD & BRIDGE DEPARTMENT FOR BRIDGE REPLACEMENT PROJECT 13-37, SURVEY F36004 IN THE SURVEY FILE FOR TOWNSHIP 15-11, SAID THAT **HE FOUND THE 6" X 9" LIMESTONE** AT THE NORTHWEST CORNER OF SECTION 6-16-12 AT THE TOWNSHIP CORNER ON THE 3RD STANDARD PARALLEL FROM HIS EXISTING REFERENCES FOR PROJECT NUMBER 12098 DATED MAY 9, 2012 ON FILE AT THE LYON COUNTY ENGINEERS OFFICE.
- 1) THIS CORNER NOW FALLS ON THE NORTHWEST SIDE OF A CORNER FENCE POST
 - 2) 0.50' SOUTH TO A LINE OF FENCE TO THE EAST
 - 3) 0.50' EAST TO A LINE OF FENCE TO THE SOUTH
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 600.40' EAST ON THE 3RD STANDARD PARALLEL TO THE 5/8" X 30" IRON PIN WITH A LYON COUNTY CAP HE SET FOR THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 36-15-11
 - 2) 1,127.17' EAST ON THE 3RD STANDARD PARALLEL TO THE 3" X 6" LIMESTONE HE FOUND AT THE NORTHWEST CORNER OF LOT 3 ON THE NORTH LINE OF THE NW1/4 OF SECTION 6-16-12
 - 3) 2,041.62' WEST ON THE 3RD STANDARD PARALLEL TO THE 5/8" X 24" IRON PIN WITH A LYON COUNTY CAP HE SET FOR THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 36-15-11
 - 4) 3,355.64' WEST ON THE 3RD STANDARD PARALLEL TO THE 1/2" X 24" IRON PIN WITH HIS "S. BROSEMER" CAP HE SET FOR P. I. STATION 13+28.00 FOR AN ANGLE TO THE NORTHEASTERLY
- HIS INFORMATION IS CONTINUED ON PAGE 6

- 5) 4,683.64' WEST TO THE SQUARE #5 IRON PIN [AND STONE] HE FOUND AT THE
SOUTHWEST CORNER OF SECTION 36-15-11 AT STATION 0+00.00

NORTHWEST CORNER SECTION 06-16-12