

NORTH 1/4 CORNER SECTION 07, TOWNSHIP 16 SOUTH, RANGE 12 EAST

- 1) ON PAGE 468 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 14" X 11" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 6 & 7-16-12.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 33.50 CHAINS WEST TO THE 14" X 14" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 7 & 12 ON THE WEST TOWNSHIP BOUNDARY
 - 2) 40.00 CHAINS EAST TO THE 17" X 12" X 6" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 5, 6, 7 & 8-16-12

- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, BY D. W. BOWMAN, DEPUTY, IN SURVEY NUMBER 58 RECORDED IN SURVEY BOOK "A" ON PAGE 157 DATED MAY 22, 1868 FOR A SURVEY OF LAND OWNED BY JONES AND OTHERS, BEING SECTION 7-16-12, TO ESTABLISH THE NORTHEAST, NORTHWEST AND SOUTHEAST CORNERS OF THE WEST 1/2 OF THE NORTHEAST 1/4 OF SECTION 7, SAID THAT **HE SET A STONE** FOR THE NORTH 1/4 CORNER OF SECTION 7-16-12 AT 160 RODS WEST OF THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 7-16-12 ON THIS SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 80 CHAINS EAST TO THE STONE HE SET FOR THE NORTHEAST CORNER OF THE W1/2 OF THE NE1/4 OF SECTION 7-16-12
 - 2) 160 RODS EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 7-16-12

- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, PER C. H. RICE, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 147 DATED MARCH 6-8, 1883 AT THE ORDER OF GEORGE W. DeCAMP TO PERMANENTLY ESTABLISH THE SOUTHEAST AND NORTHEAST CORNERS OF SECTION 6-16-12, SAID THAT AFTER RUNNING THE SOUTH LINE OF SECTION 6-17-12, **HE FOUND THE STONE** "SET BY SOME FORMER SURVEYOR WHERE I WOULD HAVE PUT THE 1/4 SECTION CORNER" ON THE SOUTH LINE OF SECTION 6-16-12 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 20.00 CHAINS EAST TO THE STONE HE SET FOR THE PERMANENT SOUTH 1/8TH CORNER OF THE SE1/4 OF SECTION 6-16-12
 - 2) 40.00 CHAINS EAST TO THE STONE HE SET FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 6-16-12
 - 3) 20.00 CHAINS WEST TO THE **TRUE POSITION** FOR THE PERMANENT SOUTH 1/8TH CORNER OF THE SOUTHWEST 1/4 OF SECTION 6-16-12, MARKED BY THE **WITNESS STONE 1 ROD NORTH DUE TO 142 MILE CREEK**
 - 4) 32.15 CHAINS WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 6-16-12 ON THE RANGE LINE
 - 5) 40.00 CHAINS NORTH TO THE STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 6-16-12
 - 6) 82.05 CHAINS NORTH TO THE STONE HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 6-16-12 ON THE 3RD STANDARD PARALLEL

- 4) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 113, RECORDED IN SURVEY BOOK "E" ON PAGE 113 DATED AUGUST 17-19, 1885, AND RECORDED IN VOLUME 41 ON PAGE 34 IN THE REGISTER OF DEEDS OFFICE ON JANUARY 27, 1887 AND SURVEY F06001 IN THE SURVEY FILE FOR TOWNSHIP 16-11, SURVEYED PER THE ORDER OF THE **DISTRICT COURT OF LYON COUNTY** TO SURVEY AND SUBDIVIDE SECTION 6-16-12, SAID THAT **HE SET A 4" X 10" X 14" STONE PROPERLY NOTCHED MARKED "1/4" CLOSE TO THE SMALL STONE HE**

FOUND FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 6-16-12 ON THIS DISTRICT COURT ORDERED SURVEY.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,320' WEST TO THE LOCATION FOR THE SOUTH 1/8TH CORNER OF THE SW1/4 OF SECTION 6-16-12. [**NOTE:** HE SET THE LIMESTONE THAT WAS 3" X 3" AT THE TOP, 4" X 12" AT THE BASE AND 24" LONG AT 16' NORTH OF THE SECTION LINE DUE TO A CREEK – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]
 - 2) 2,113' WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 6-16-12 ON THE RANGE LINE
 - 3) 1,320.5' EAST TO THE LOCATION FOR THE PERMANENT SOUTH 1/8TH CORNER OF THE SE1/4 OF SECTION 6-16-12. [**NOTE:** THE 3" X 8" X 16" LIMESTONE WAS OFFSET 12' NORTH OF THE SECTION LINE – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]
 - 4) 2,641' EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 6-16-12
 - 5) 5,293' EAST TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 5-16-12
 - 6) 7,945' EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 5-16-12
 - 7) 2,640' NORTH TO THE 3" X 10" X 16" LIMESTONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 6-16-12
- 5) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN SURVEY F07001 IN THE SURVEY FILE FOR TOWNSHIP 16-12 DATED SEPTEMBER 9, 1986 FOR PROJECT NUMBER 86084 AND RECORDED IN VOLUME 429 ON PAGE 121 IN THE REGISTER OF DEEDS OFFICE ON DECEMBER 3, 1986, SAID THAT THIS SECTION SHOWS EVIDENCE OF GLO FRAUD, AS THE DISTANCES EAST & WEST AND THE ALIGNMENT ALONG THE EAST SIDE ARE NOT IN HARMONY WITH THE GOVERNMENT NOTES. HE SAID THAT **HE FOUND A LIMESTONE WITH A 4" FLAT TOP WITH AN 18" WIDE BOTTOM AND 18" LONG AT THE NORTH 1/4 CORNER OF SECTION 7-16-12. HE DROVE A 1" PIPE UNDER THE STONE AND HE DROVE A 1/2" CAPPED REBAR ON THE NORTH SIDE OF THE STONE.**
- 1) 14.8' NNE TO A PK NAIL IN A 30" ASH TREE
 - 2) 31.75' EAST TO A PK NAIL IN A 36" HEDGE TREE
 - 3) 29.5' SOUTH TO A LINE OF FENCE TO THE EAST AND WEST
 - 4) 22.8' NW TO A PK NAIL IN A 22" BOX ELDER TREE
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**
- 1) 2,638.50' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE CENTER CORNER OF SECTION 7-16-12
 - 2) 3,952.60' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE WEST 1/16TH CORNER OF THE SE1/4 OF SECTION 7-16-12
 - 3) 5,266.69' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTH 1/4 CORNER OF SECTION 7-16-12
- 6) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED MAY 9, 2012 FOR PROJECT NUMBER 12098-02 FOR SURVEY F06002 IN THE SURVEY FILE FOR TOWNSHIP 16-12, A SURVEY FOR A TRACT IN THE SOUTHWEST QUARTER OF SECTION 6-20-12 FOR BILL MARTIN, SAID THAT **HE FOUND THE 4" FLAT AT THE TOP LIMESTONE AT THE SOUTH 1/4 CORNER OF SECTION 6-16-12 FROM HIS EXISTING REFERENCE TIES ON FILE AT THE COUNTY SURVEYOR'S OFFICE. HE NOTED THAT HE HAD FOUND THIS STONE IN 1986.**
- 1) 1/2" IRON PIN WITH CAP ON THE NORTH SIDE CENTER OF THE STONE
 - 2) 29.5' SOUTH TO A FENCE EAST-WEST
 - 3) 31.15' SE T A CONCRETE NAIL & WASHER IN A 24" HEDGE TREE
 - 4) 14.9' NNE TO A CONCRETE NAIL & WASHER IN A 36" ASH TREE

HIS TIES ARE CONTINUED ON PGE 3

5) IN LINE WITH A FENCE TO THE SOUTH EXTENDED

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,126.25' WEST TO THE 13" BOLT WITH A GEAR WHEEL ON TOP HE SET FOR THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 6-16-12 ON THE RANGE LINE
- 2) 2,650.43' NORTH TO THE 1" IRON PIN HE FOUND AT THE CENTER CORNER OF SECTION 6-16-12

NORTH QUARTER CORNER SECTION 07-16-12