

NORTHWEST CORNER SECTION 07, TOWNSHIP 16 SOUTH, RANGE 12 EAST

- 1) ON PAGE 82 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 14" X 14" X 3"** FOR THE CORNER TO SECTIONS 6 & 7-16-12 ON THE WEST TOWNSHIP BOUNDARY ON DECEMBER 18, 1856, FROM WHICH:
 - 1) AN OAK TREE 36" IN DIAMETER BEARS S. 35-1/2° W. AT 16 LINKS DISTANCE
 - 2) A WALNUT TREE 6" IN DIAMETER BEARS S. 66° E. AT 27 LINKS DISTANCE
 - 3) A HACKBERRY TREE 5" IN DIAMETER BEARS N. 32° E. AT 73 LINKS DISTANCE
 - 4) AN ELM TREE 6" IN DIAMETER BEARS N. 35° E. AT 73 LINKS DISTANCE

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

 - 1) 33.50 CHAINS EAST TO THE 14" X 11" X 4" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 6 & 7-16-12
 - 2) 73.50 CHAINS EAST TO THE 17" X 12" X 6" LIMESTONE SET FOR THE CORNER TO SECTIONS 5, 6, 7 & 8-16-12
 - 3) 40.00 CHAINS NORTH ON THE WEST TOWNSHIP BOUNDARY TO THE 16" X 14" X 6" LIMESTONE THEY SET FOR THE WEST 1/4 CORNER OF SECTION 6-17-12
 - 4) 82.75 CHAINS NORTH ON THE WEST TOWNSHIP BOUNDARY TO INTERSECT THE 3RD STANDARD PARALLEL AT 9 CHAINS & 70 LINKS WEST OF THE CORNER TO TOWNSHIP 15 SOUTH, RANGES 11 & 12 EAST – NO MONUMENT DESCRIBED
 - 5) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 15" X 12" X 4" LIMESTONE THEY SET FOR THE WEST 1/4 CORNER OF SECTION 7-16-12
 - 6) 80.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 18" X 15" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 7 & 18-16-12

- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, BY D. W. BOWMAN, DEPUTY, IN SURVEY NUMBER 58 RECORDED IN SURVEY BOOK "A" ON PAGE 157 DATED MAY 22, 1868 FOR A SURVEY OF LAND OWNED BY JONES AND OTHERS, BEING SECTION 7-16-12, TO ESTABLISH THE NORTHEAST, NORTHWEST AND SOUTHEAST CORNERS OF THE WEST 1/2 OF THE NORTHEAST 1/4 OF SECTION 7-17-12, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 7-16-12 ON THE RANGE LINE ON THIS SURVEY.

- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 19 FOR A ROAD IN TOWNSHIPS 15 & 16, RANGE 11 FOR J. S. GRIMSLEY, PRINCIPAL PETITIONER, DATED AUGUST 8, 1882, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 1-16-1 ON THE RANGE LINE AT A TURN ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

 - 1) THIS ROAD EXTENDS NORTH ON THE RANGE LINE TO THE TOWNSHIP CORNER AT THE NORTHEAST CORNER OF SECTION 1-16-11 ON THE 3RD STANDARD PARALLEL; THEN EAST ON THE 3RD STANDARD PARALLEL FOR 640 FEET TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 31-15-12; THEN NORTH ON THE RANGE LINE FOR 3 MILES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 19-15-12 ON THE LYON AND WABAUNSEE COUNTY LINE TO BEGIN THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 350 FEET TO AN ANGLE POINT; THEN N. 80° W. FOR 300 FEET TO AN ANGLE POINT; THEN S. 70° W. FOR 300 FEET TO INTERSECT THE SECTION LINE ON THE SOUTH SIDE OF SECTION 1-16-11 AND CONTINUES WEST ON THE SECTION LINES TO THE SOUTHWEST CORNER OF SECTION 2-16-11 AT THE TERMINUS OF THIS ROAD SURVEY

CONTINUED ON PAGE 2

- 4) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY FOR ROAD NUMBER 186 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 330 TO 332 PETITIONED BY J. S. GRIMSLEY AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 1511 & 16-11 [PACKET 401 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON AUGUST 8, 1882, AND WAS ESTABLISHED AS A 50 FOOT ROAD, **EXCEPT** FOR THE DISTANCE OF 80 RODS SOUTH OF THE NORTHEAST CORNER OF THE SOUTHEAST 1/4 OF SECTION 1-16-11 WHICH SHALL BE **35 FEET**, ON OCTOBER 5, 1882 AS NOTED BY HUGH F. HOLMES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON OCTOBER 24, 1882 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 1-16-11 ON THE RANGE LINE ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 3) THIS ROAD EXTENDS NORTH ON THE RANGE LINE TO THE TOWNSHIP CORNER AT THE NORTHEAST CORNER OF SECTION 1-16-11 ON THE 3RD STANDARD PARALLEL; THEN EAST ON THE 3RD STANDARD PARALLEL FOR 640 FEET TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 31-15-12; THEN NORTH ON THE RANGE LINE FOR 3 MILES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 19-15-12 ON THE LYON AND WABAUNSEE COUNTY LINE TO BEGIN THIS ROAD SURVEY
- 4) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 350 FEET TO AN ANGLE POINT; THEN N. 80° W. FOR 300 FEET TO AN ANGLE POINT; THEN S. 70° W. FOR 300 FEET TO INTERSECT THE SECTION LINE ON THE SOUTH SIDE OF SECTION 1-16-11 AND CONTINUES WEST ON THE SECTION LINES TO THE SOUTHWEST CORNER OF SECTION 2-16-11 AT THE TERMINUS OF THIS ROAD SURVEY
- 5) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, PER C. H. RICE, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 147 DATED MARCH 6-8, 1883 AT THE ORDER OF GEORGE W. DeCAMP TO PERMANENTLY ESTABLISH THE SOUTHEAST AND NORTHEAST CORNERS OF SECTION 6-16-12, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 6-16-12 ON THE RANGE LINE ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 12.15 CHAINS EAST TO THE **TRUE POSITION** FOR THE PERMANENT SOUTH 1/8TH CORNER SIDE OF THE SW1/4 OF SECTION 6-16-12, AND MARKED BY A **WITNESS STONE THAT HE SET 1 ROD NORTH DUE TO 142 MILE CREEK**
- 2) 32.15 CHAINS EAST TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 6-16-12 "SET BY SOME FORMER SURVEYOR WHERE I WOULD HAVE SET THE 1/4 CORNER ON THE SOUTH LINE OF SECTION 6"
- 3) 52.15 CHAINS EAST TO THE STONE HE SET FOR THE PERMANENT SOUTH 1/8TH CORNER OF THE SE1/4 OF SECTION 6-16-12
- 4) 72.15 CHAINS EAST TO THE STONE HE SET FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 6-16-12
- 6) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 113, RECORDED IN SURVEY BOOK "E" ON PAGE 113 DATED AUGUST 17-19, 1885, AND RECORDED IN VOLUME 41 ON PAGE 34 IN THE REGISTER OF DEEDS OFFICE ON JANUARY 27, 1887 AND SURVEY F06001 IN THE SURVEY FILE FOR TOWNSHIP 16-11, SURVEYED PER THE ORDER OF THE **DISTRICT COURT OF LYON COUNTY** TO SURVEY AND SUBDIVIDE SECTION 6-16-12, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 6-16-12 ON THE RANGE LINE ON THIS **DISTRICT COURT ORDERED SURVEY**.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

HIS INFORMATION IS CONTINUED ON PAGE 3

- 1) 793' EAST TO THE LOCATION FOR THE SOUTH 1/8TH CORNER OF THE SW1/4 OF SECTION 6-16-12. [**NOTE:** THE LIMESTONE 3" X 3" AT THE TOP, 4" X 12" AT THE BASE, AND 24" LONG WAS SET **16' NORTH** OF THE SECTION LINE DUE TO A CREEK – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]
 - 2) 2,113' EAST TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 6-16-12
 - 3) 3,433.5' EAST TO THE LOCATION FOR THE SOUTH 1/8TH CORNER OF THE SE1/4 OF SECTION 6-16-12. [**NOTE:** THE 3" X 8" X 16" LIMESTONE WAS OFFSET **12' NORTH** OF THE SECTION LINE DUE TO A CREEK – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]
 - 4) 4,764' EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 6-16-12
 - 5) 7,406' EAST TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 5-16-12
 - 6) 10,058' EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 5-16-12
- 7) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "E" ON PAGE 155 DATED DECEMBER 6 & 7, 1886 FOR A ROAD IN TOWNSHIP 16-11 FOR D. L. SAYLOR, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 12-16-11 ON THE RANGE LINE TO BEGIN THE FIRST ROAD ON THIS ROAD SURVEY ON THE RANGE LINE.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THE FIRST ROAD EXTENDS SOUTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 25-16-11 TO END THIS FIRST ROAD ON THIS ROAD SURVEY
 - 2) **NOTE:** SEE ROAD RECORD BOOK "C" ON PAGE 372 – THE ROAD WAS GRANTED FOR ONE MILE BETWEEN SECTIONS 13-17-11 AND 18-17-12 – THE BALANCE OF THE ROAD WAS **REJECTED** – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR
- 8) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A ROAD SURVEY FOR ROAD NUMBER 355 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 370 TO 372 PETITIONED BY D. L. SAYLORS AND OTHERS COMMENCING AT THE NORTHEAST CORNER OF SECTION 12-16-11, THENCE SOUTH AS NEARLY AS PRACTICABLE ON THE SECTION LINES TO THE SOUTHEAST CORNER OF SECTION 25-16-12, THENCE SOUTH OVER A ROAD ALREADY LOCATED TO THE SOUTHEAST CORNER OF SECTION 12-17-11, THENCE SOUTH AS NEARLY AS PRACTICABLE ON THE SECTION LINES TO THE SOUTHEAST CORNER OF SECTION 25-17-11 [PACKET 604 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON DECEMBER 6, 1886, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 12-16-11 ON THE RANGE LINE. ON JANUARY 5, 1887 THE BOARD OF COUNTY COMMISSIONERS GRANTED THE ROAD FOR ONE MILE BETWEEN SECTIONS 13-17-11 AND 18-17-12, AND THE BALANCE OF THE ROAD WAS **REJECTED** AS NOTED BY T. E. McMILLAN, CHAIRMAN, AND RECORDED ON JANUARY 18, 1887 BY ROLAND LAKIN, COUNTY CLERK.
- 9) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN SURVEY NUMBER 179, A **PERMANENT SURVEY** AT THE REQUEST OF JAMES W. WORSTELL TO ESTABLISH THE LINES AND CORNERS OF THE SOUTHEAST 1/4 OF SECTION 14 AND THE NORTHEAST 1/4 OF SECTION 23, ALL IN TOWNSHIP 16, RANGE 11 RECORDED IN SURVEY BOOK "F" ON PAGE 133 DATED JUNE 18 TO JULY 7, 1888, SAID THAT **HE FOUND THE ORIGINAL GOVERNMENT STONE** AT THE NORTHWEST CORNER OF SECTION 7-16-12 ON THE RANGE LINE ON THIS **PERMANENT SURVEY**. HE FOUND THE OAK, ELM AND HACKBERRY TREE STUMPS

THAT WERE THE ORIGINAL WITNESS TREES TO VERIFY THAT THE STONE WAS IN THE PROPER PLACE.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 10,553.8' SOUTH ON THE RANGE LINE TO THE TEMPORARY STAKE HE SET FOR THE NORTHEAST CORNER OF SECTION 24-16-11
- 2) 26,384.8' SOUTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE TOWNSHIP CORNER AT THE SOUTHEAST CORNER OF SECTION 36-16-11

- 10) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 118, A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 199 DATED JANUARY 3, 1905 FOR TWO ROADS ON THE RANGE LINE BETWEEN TOWNSHIP 16, RANGES 11 & 12 FOR J. A. RABOURN, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 7-16-12 ON THE RANGE LINE TO BEGIN THE FIRST ROAD ON THIS ROAD SURVEY FOR A 40 FOOT WIDE ROAD.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THE FIRST ROAD APPROVED ON THIS ROAD SURVEY EXTENDS EAST ON THE SECTION LINE FOR 233 FEET, THENCE S. 57°50' W. FOR 242-1/2 FEET, THENCE S. 11°15' W. FOR 440-1/2 FEET TO THE SECTION LINE, THENCE SOUTH ON THE SECTION LINE FOR 719 FEET TO THE STONE 20 FEET WEST OF A FENCE, BEING THE SOUTHWEST CORNER OF THE NW1/4 OF THE NW1/4 OF SAID SECTION 7, THENCE SOUTH ON THE SECTION LINE FOR 3/4 OF A MILE TO THE SOUTHWEST CORNER OF SECTION 7-16-12 AT THE TERMINUS OF THE FIRST MILE APPROVED ON THIS ROAD SURVEY

- 11) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A ROAD SURVEY FOR ROAD NUMBER 598 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 261 THROUGH 264 PETITION BY J. A. RABOURN AND OTHERS FOR A ROAD ON THE RANGE LINE BETWEEN TOWNSHIPS 16-11 AND 16-12 AS FOLLOWS: BEGINNING AT THE NORTHEAST CORNER OF SECTION 12-16-11, THENCE SOUTH ON THE SECTION LINE OR AS NEAR AS PRACTICABLE 4 MILES TO THE SOUTHEAST CORNER OF SECTION 25-16-11 AND THERE ENDING [PACKET 748 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JANUARY 3, 1905, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 7-16-12 ON THE RANGE LINE TO BEGIN THIS ROAD SURVEY. THE FINAL ORDER OF THE BOARD OF COUNTY COMMISSIONERS GRANTED THE NORTH MILE AND THE SOUTH MILE ONLY AT 40 FEET WIDE, 20 FEET ON EACH SIDE OF THE LINE AS SURVEYED, ON APRIL 6, 1905 AS NOTED BY W. H. MAPES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, ATTESTED BY W. F. EGGERS, COUNTY CLERK, AND RECORDED ON MAY 9, 1905 BY ALVA J. SMITH, COUNTY SURVEYOR. THE REMAINDER OF THE ROAD AS PETITIONED WAS **REJECTED.**

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THE FIRST ROAD APPROVED ON THIS ROAD SURVEY EXTENDS EAST ON THE SECTION LINE FOR 233 FEET, THENCE S. 57°50' W. FOR 242-1/2 FEET, THENCE S. 11°15' W. FOR 440-1/2 FEET TO THE SECTION LINE, THENCE SOUTH ON THE SECTION LINE FOR 719 FEET TO THE STONE 20 FEET WEST OF A FENCE, BEING THE SOUTHWEST CORNER OF THE NW1/4 OF THE NW1/4 OF SAID SECTION 7, THENCE SOUTH ON THE SECTION LINE FOR 3/4 OF A MILE TO THE SOUTHWEST CORNER OF SECTION 7-16-12 AND ENDING THE FIRST MILE APPROVED ON THIS ROAD SURVEY

- 12) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 155 OF TERM 2, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGES 78 & 79 DATED MARCH 4-6, 1909 AT THE ORDER OF LeMONT DeCAMP TO ESTABLISH THE CORNERS AND BOUNDARIES OF LOTS 3 & 4 OF SECTION 1-16-11 AND ANY OTHER CORNERS

THAT MIGHT BE NECESSARY IN SAID SECTION TO ESTABLISH THE SAID CORNERS AND BOUNDARIES OF SAID LOTS, SAID THAT **HE PLANTED A 20" X 10" X 6" LIMESTONE ROCK AT 4" BELOW THE GROUND** FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 1-16-11 ON THE RANGE LINE. HE RAN THE RANGE LINE FROM THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 12-16-11 THROUGH THE ORIGINAL GOVERNMENT STONE THAT HE FOUND AT THE EAST 1/4 CORNER OF SECTION 12-16-11 TO THE STONE THAT HE PLANTED FOR THE PERMANENT NORTHEAST CORNER OF SECTION 1-16-11 ON THE 3RD STANDARD PARALLEL ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,640' SOUTH ON THE RANGE LINE TO THE ORIGINAL GOVERNMENT STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 12-16-11
 - 2) 5,279.6' SOUTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 12-16-11
 - 3) 2,617.5' WEST TO THE 14" X 8" X 4" STONE HE PLANTED FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 1-16-11
 - 4) 5,235' WEST TO THE 18" X 10" X 4" LIMESTONE ROCK HE PLANTED FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 1-16-11
- 13) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN SURVEY F07001 IN THE SURVEY FILE FOR TOWNSHIP 16-12 DATED SEPTEMBER 9, 1986 FOR PROJECT NUMBER 86084 AND RECORDED IN VOLUME 429 ON PAGE 121 IN THE REGISTER OF DEEDS OFFICE ON DECEMBER 3, 1986, SAID THAT THIS SECTION SHOWS EVIDENCE OF GLO FRAUD, AS THE DISTANCES EAST & WEST AND THE ALIGNMENT ALONG THE EAST SIDE ARE NOT IN HARMONY WITH THE GOVERNMENT NOTES. HE SEARCHED FOR THE STONE AT THE NORTHWEST CORNER OF SECTION 7-16-12 ON THE RANGE LINE, BUT HE DID **NOT** FIND THE STONE. HE CONSIDERED THAT THIS CORNER WAS **LOST**. HE DID **NOT** RESET THE NORTHWEST CORNER OF SECTION 7-16-12 ON THE RANGE LINE ON THIS SURVEY.
- 14) STEVEN S. BROSEMER, L.S. 752, IN LAND SURVEY REFERENCE REPORT DATED MAY 9, 2012 FOR PROJECT NUMBER 12098-02 FOR SURVEY F06002 IN THE SURVEY FILE FOR TOWNSHIP 16-12, A SURVEY FOR A TRACT IN THE SOUTHWEST QUARTER OF SECTION 6-20-12 FOR BILL MARTIN, SAID THAT BASED ON HIS 1986 SURVEY HE DEEMED THAT THE NORTHWEST CORNER OF SECTION 7-16-12 ON THE RANGE LINE WAS **LOST**. **HE SET A 13" BOLT WITH A GEAR ON TOP DUE TO ROCK LEDGE IN THE TRAIL AREA** FOR THE NORTHWEST CORNER OF SECTION 7-16-12 ON THE RANGE LINE. HE RESET THIS CORNER ON THE RANGE LINE BETWEEN THE SOUTHWEST CORNER OF SECTION 7-16-12 AND THE NORTHWEST CORNER OF SECTION 6-16-12 ON THE 3RD STANDARD PARALLEL, AND AT DOUBLE THE DISTANCE FROM THE SOUTHWEST CORNER OF SECTION 7-16-12 TO THE WEST 1/4 CORNER OF SECTION 7-16-12 BASED ON RETRACEMENTS OF THE SURVEYS BY MILLIKEN IN 1883, EDMISTON IN 1885, AND HIS 1986 SURVEY.
- 1) IN LINE WITH A FENCE TO THE SOUTH
 - 2) 18.85' SOUTH TO THE NEAR FACE OF A 4" PIPE GATE POST
 - 3) 29.15' SE TO A CONCRETE NAIL & WASHER IN A BRACE POST
 - 4) 20' SOUTH TO A FENCE WESTERLY-EASTERLY
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,643.09' SOUTH ON THE RANGE LINE TO THE 5/8" IRON PIN WITH THE REMAINS OF A CAP HE FOUND AT THE SOUTHWEST CORNER OF THE NW1/4 OF SECTION 7-16-12
 - 2) 5,286.18' SOUTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 7-16-12
 - 3) 5,448.36' NORTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 6-16-12 ON THE 3RD STANDARD PARALLEL

HIS INFORMATION IS CONTINUED ON PAGE 6

- 4) 2,126.25' EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF THE
NW1/4 OF SECTION 7-16-12

NORTHWEST CORNER SECTION 07-16-12