

**WEST 1/4 CORNER SECTION 07, TOWNSHIP 16 SOUTH, RANGE 12 EAST**

- 1) ON PAGE 82 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 15" X 12" X 5"** FOR THE WEST 1/4 CORNER OF SECTION 7-16-12 ON THE WEST TOWNSHIP BOUNDARY ON DECEMBER 18, 1856.  
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
  - 1) 40.00 CHAINS NORTH ON THE WEST TOWNSHIP BOUNDARY TO THE 14" X 14" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 6 & 7-16-12
  - 2) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 18" X 15" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 7 & 18-16-12
  
- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, BY D. W. BOWMAN, DEPUTY, IN SURVEY NUMBER 58 RECORDED IN SURVEY BOOK "A" ON PAGE 157 DATED MAY 22, 1868 FOR A SURVEY OF LAND OWNED BY JONES AND OTHERS, BEING SECTION 7-16-12, TO ESTABLISH THE NORTHEAST, NORTHWEST AND SOUTHEAST CORNERS OF THE WEST 1/2 OF THE NORTHEAST 1/4 OF SECTION 7-16-12, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 7-16-12 ON THE RANGE LINE ON THIS SURVEY.
  
- 3) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 155 OF TERM 2, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGES 78 & 79 DATED MARCH 4-6, 1909 AT THE ORDER OF LeMONT DeCAMP TO ESTABLISH THE CORNERS AND BOUNDARIES OF LOTS 3 & 4 OF SECTION 1-16-11 AND ANY OTHER CORNERS THAT MIGHT BE NECESSARY IN SAID SECTION TO ESTABLISH THE SAID CORNERS AND BOUNDARIES OF SAID LOTS, SAID THAT **HE FOUND THE ORIGINAL GOVERNMENT STONE** AT THE EAST 1/4 CORNER OF SECTION 12-16-11 ON THE RANGE LINE ON THIS **PERMANENT SURVEY**.  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 2,639.6' SOUTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 12-16-11
  - 2) 2,640' NORTH ON THE RANGE LINE TO THE 20" X 10" X 6" LIMESTONE ROCK HE PLANTED FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 1-16-11
  
- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN SURVEY F07001 IN THE SURVEY FILE FOR TOWNSHIP 16-12 DATED SEPTEMBER 9, 1986 FOR PROJECT NUMBER 86084 AND RECORDED IN VOLUME 429 ON PAGE 121 IN THE REGISTER OF DEEDS OFFICE ON DECEMBER 3, 1986, SAID THAT THIS SECTION SHOWS EVIDENCE OF GLO FRAUD, AS THE DISTANCES EAST & WEST AND THE ALIGNMENT ALONG THE EAST SIDE ARE NOT IN HARMONY WITH THE GOVERNMENT NOTES. HE SAID THAT HE DETERMINED THAT THE WEST 1/4 CORNER OF SECTION 7-16-12 ON THE RANGE LINE WAS **OBLITERATED**. **HE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP** FOR THE WEST 1/4 CORNER OF SECTION 7-16-12 BASED ON THE PHYSICAL EVIDENCE THAT HE FOUND AT THIS CORNER, I.E., IN LINE WITH A FENCE TO THE WEST AND IN LINE WITH THE FENCE NORTH-SOUTH. HE NOTED THAT THIS POSITION IS CONFIRMED BY THE DISTANCES TO THE SOUTH AND THE ALIGNMENT ON THE RANGE LINE.
  - 1) IN LINE WITH A FENCE TO THE WEST
  - 2) IN LINE WITH A FENCE NORTH-SOUTH
  - 3) AT THE EAST SIDE OF A CORNER FENCE POSTHIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 2,642.30' SOUTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 7-16-12

CONTINUED ON PAGE 2

- 5) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED MAY 9, 2012 FOR PROJECT NUMBER 12098-02 FOR SURVEY F06002 IN THE SURVEY FILE FOR TOWNSHIP 16-12, A SURVEY FOR A TRACT IN THE SOUTHWEST QUARTER OF SECTION 6-20-12 FOR BILL MARTIN, SAID THAT **HE FOUND THE 5/8" REBAR WITH THE REMAINS OF A CAP** AT THE WEST 1/4 CORNER OF SECTION 7-16-12 ON THE RANGE LINE FROM HIS EXISTING REFERENCE TIES ON FILE AT THE COUNTY SURVEYOR'S OFFICE. HE NOTED THAT HE HAD SET THIS CAPPED REBAR IN 1986.
- 1) THIS CAPPED REBAR IS ON THE EAST SIDE OF A CORNER FENCE POST
  - 2) IN LINE WITH A FENCE TO THE WEST
  - 3) IN LINE WITH A FENCE NORTH-SOUTH
  - 4) 2,643.09' SOUTH TO THE STONE AT THE SOUTHWEST CORNER OF SECTION 7
  - 5) 2,643.09' NORTH TO A 13" BOLT WITH A GEAR AT THE WEST 1/4 CORNER OF SECTION 7 [**NOTE:** THIS SHOULD BE NORTHWEST CORNER OF SECTION 7-16-12 – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 8,091.45' NORTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 6-16-12 ON THE 3<sup>RD</sup> STANDARD PARALLEL

WEST QUARTER CORNER SECTION 07-16-12