

NORTHWEST CORNER SECTION 08, TOWNSHIP 16 SOUTH, RANGE 12 EAST

- 1) ON PAGE 467 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 17" X 12" X 6"** FOR THE CORNER TO SECTIONS 5, 6, 7 & 8-16-12.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 40.15 CHAINS EAST TO THE 12" X 11" X 6" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 5 & 8-16-12
 - 2) 80.30 CHAINS EAST TO THE 20" X 10" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 4, 5, 8 & 9-16-12
- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, BY D. W. BOWMAN, DEPUTY, IN SURVEY NUMBER 57 RECORDED IN SURVEY BOOK "A" ON PAGE 156 DATED MAY 20, 1868 FOR A SURVEY OF LAND OWNED BY SWEET AND OTHERS, BEING SECTION 8-16-12, TO ESTABLISH THE CENTER CORNER AND LAY OFF 40 ACRES ON THE NORTH SIDE OF THE SOUTHWEST 1/4 OF SECTION 8-16-12, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 8-16-12 ON THIS SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 159 RODS, 9-1/2 LINKS SOUTH TO THE STONE HE SET FOR THE WEST 1/4 CORNER OF SECTION 8-16-12
- 2) 318 RODS, 19 LINKS SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 8-16-12
- 3) 162 RODS EAST TO THE STONE HE SET FOR THE NORTH 1/4 CORNER OF SECTION 8-16-12
- 4) 324 RODS EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 8-16-12

- 3) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, BY D. W. BOWMAN, DEPUTY, IN SURVEY NUMBER 58 RECORDED IN SURVEY BOOK "A" ON PAGE 157 DATED MAY 22, 1868 FOR A SURVEY OF LAND OWNED BY JONES AND OTHERS, BEING SECTION 7-16-12, TO ESTABLISH THE NORTHEAST, NORTHWEST AND SOUTHEAST CORNERS OF THE WEST 1/2 OF THE NORTHEAST 1/4 OF SECTION 7-16-12, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 7-16-12 ON THIS SURVEY.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 80 RODS WEST TO THE STONE HE SET FOR THE NORTHEAST CORNER OF THE W1/2 OF THE NE1/4 OF SECTION 7-16-12
- 2) 160 RODS WEST TO THE STONE HE SET FOR THE NORTH 1/4 CORNER OF SECTION 7-16-12

- 4) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, PER C. H. RICE, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 147 DATED MARCH 6-8, 1883 AT THE ORDER OF GEORGE W. DeCAMP TO PERMANENTLY ESTABLISH THE SOUTHEAST AND NORTHEAST CORNERS OF SECTION 6-16-12, SAID THAT **HE SET A STONE** FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 6-16-12 ON LINE AND AT THE "PROPER CORRECTION" BETWEEN THE STONE THAT HE FOUND AT THE EAST 1/4 CORNER ON THE EAST LINE OF SECTION 7-16-12 AND THE STONE THAT HE FOUND AT THE EAST 1/4 CORNER OF SECTION 6-16-12 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 39.85 CHAINS SOUTH TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 7-16-12
- 2) 39.85 CHAINS NORTH TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 6-16-12

HIS INFORMATION IS CONTINUED ON PAGE 3

- 3) 81.36 CHAINS NORTH TO THE STONE HE SET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 6-16-12 ON THE 3RD STANDARD PARALLEL
 - 4) 20.00 CHAINS WEST TO THE STONE HE SET FOR THE PERMANENT SOUTH 1/8TH CORNER OF THE SE1/4 OF SECTION 6-16-12
 - 5) 40.00 CHAINS WEST TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 6-16-12 "SET BY SOME FORMER SURVEYOR WHERE I WOULD HAVE PUT THE 1/4 CORNER ON THE SOUTH LINE OF SECTION 6"
 - 6) 60.00 CHAINS WEST TO THE TRUE POSITION FOR THE SOUTH 1/8TH CORNER OF THE SW1/4 OF SECTION 6-16-12, MARKED BY A **WITNESS STONE HE SET AT 1 ROD NORTH DUE TO 142 MILE CREEK**
 - 7) 72.15 CHAINS WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 6-16-12 ON THE RANGE LINE
- 5) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 16, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 16 DATED MARCH 17-18, 1884 ORDERED BY JAMES JONES FOR A SURVEY TO ESTABLISH THE SOUTH 1/4 CORNER AND THE CENTER CORNER SECTION 5-16-12, SURVEY F05001 IN THE SURVEY FILE FOR TOWNSHIP 16-12, RECORDED IN VOLUME 41 ON PAGE 13 IN THE REGISTER OF DEEDS OFFICE ON JANUARY 27, 1887, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 5-16-12 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 40.00 CHAINS NORTH TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 5-16-12
 - 2) 40.18 CHAINS EAST TO THE 2" X 12" X 15" STONE HE SET FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 5-16-12
 - 3) 80.36 CHAINS EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 5-16-12
- 6) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 113, RECORDED IN SURVEY BOOK "E" ON PAGE 113 DATED AUGUST 17-19, 1885, AND RECORDED IN VOLUME 41 ON PAGE 34 IN THE REGISTER OF DEEDS OFFICE ON JANUARY 27, 1887 AND SURVEY F06001 IN THE SURVEY FILE FOR TOWNSHIP 16-11, SURVEYED PER THE ORDER OF THE **DISTRICT COURT OF LYON COUNTY** TO SURVEY AND SUBDIVIDE SECTION 6-16-12, SAID THAT **HE MAY HAVE FOUND OR SET A STONE** AT THE SOUTHEAST CORNER OF SECTION 6-1-612 AS HE VERIFIED THE POSITION OF THIS CORNER BY MEASURING TO THE STONE THAT HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 5-16-12, THE STONE AT THE NORTH 1/4 CORNER OF SECTION 8-16-12, AND THE STONE AT THE WEST 1/4 CORNER OF SECTION 5-16-12 ON THIS **DISTRICT COURT ORDERED SURVEY**.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,640' SOUTH TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 8-16-12
 - 2) 2,652' EAST TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 5-16-12
 - 3) 5,304' EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 5-16-12
 - 4) 1,320.5' WEST TO THE LOCATION FOR THE PERMANENT SOUTH 1/8TH CORNER OF THE SE1/4 OF SECTION 6-16-12. [**NOTE:** HE OFFSET THE 3" X 8" X 16" LIMESTONE 12' NORTH – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR
 - 5) 2,641' WEST TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 6-16-12]
 - 6) 3,961' WEST TO THE LOCATION FOR THE SOUTHWEST CORNER OF THE E1/2 OF THE SW1/4 OF SECTION 6-16-12. [**NOTE:** HE SET THE LIMESTONE THAT WAS 3" X 3" AT THE TOP, 4" X 12" AT THE BASE AND 24" LONG AT 16' NORTH DUE TO A CREEK – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]

- 7) 4,764' WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 6-16-12 ON THE RANGE LINE
 - 8) 2,640' NORTH TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 5-16-12
 - 9) 3,960' NORTH TO THE 3" X 7" X 14" LIMESTONE HE SET FOR THE PERMANENT EAST 1/8TH CORNER OF THE NE1/4 OF SECTION 6-16-12 BUT **NOT** ON LINE BETWEEN THE STONES AT THE NORTHEAST AND SOUTHEAST CORNERS OF SECTION 6-16-12 DUE TO A 6°50' ANGLE TO THE RIGHT AT THE EAST 1/4 CORNER OF SECTION 6-16-12
 - 10) 5,410' NORTH TO THE STONE HE SET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 6-16-12 ON THE 3RD STANDARD PARALLEL
- 8) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN SURVEY F07001 IN THE SURVEY FILE FOR TOWNSHIP 16-12 DATED SEPTEMBER 9, 1986 FOR PROJECT NUMBER 86084 AND RECORDED IN VOLUME 429 ON PAGE 121 IN THE REGISTER OF DEEDS OFFICE ON DECEMBER 3, 1986, SAID THAT THIS SECTION SHOWS EVIDENCE OF GLO FRAUD, AS THE DISTANCES EAST & WEST AND THE ALIGNMENT ALONG THE EAST SIDE ARE NOT IN HARMONY WITH THE GOVERNMENT NOTES. HE SAID THAT HE SEARCHED FOR THE STONE AT THE NORTHEAST CORNER OF SECTION 7-16-12, BUT HE DID **NOT** FIND THE STONE. HE CONCLUDED FROM THE LANGUAGE OF EDMISTON'S 1885 SURVEY THAT NO MONUMENT WAS SET [SURVEY BOOK "E", PAGE 113]. HE DID **NOT** RESET THE NORTHEAST CORNER OF SECTION 7-16-12 ON THIS SURVEY.

NORTHWEST CORNER 08-16-12