

WEST 1/4 CORNER SECTION 09, TOWNSHIP 16 SOUTH, RANGE 12 EAST

- 1) ON PAGE 462 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 13" X 12" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 8 & 9-16-12.

- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, BY D. W. BOWMAN, DEPUTY, IN SURVEY NUMBER 57 RECORDED IN SURVEY BOOK "A" ON PAGE 156 DATED MAY 20, 1868 FOR A SURVEY OF LAND OWNED BY SWEET AND OTHERS, BEING SECTION 8-16-12, TO ESTABLISH THE CENTER CORNER AND LAY OFF 40 ACRES ON THE NORTH SIDE OF THE SOUTHWEST 1/4 OF SECTION 8-16-12, SAID THAT **HE SET A STONE** FOR THE EAST 1/4 CORNER OF SECTION 8-16-12 EQUIDISTANT BETWEEN THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 8-16-12 AND THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 8-16-12 ON THIS SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 324 RODS, 15 LINKS WEST TO THE STONE HE SET FOR THE WEST 1/4 CORNER OF SECTION 8-16-12

- 3) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, BY MATTHEW BROWN, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 113, A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 93 DATED JUNE 8, 1886 FOR A ROAD IN TOWNSHIP 16, RANGE 12 WITH NO PRINCIPAL PETITIONER NAMES, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 8-16-12 TO END THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS WEST ON THE CENTER SECTION LINE TO THE STONE HE FOUND AT THE CENTER CORNER OF SECTION 8-16-12 AT A TURN TO THE SOUTH ON THIS ROAD SURVEY – THIS PORTION OF THE ROAD IS 40 FEET WIDE, 20 FEET EACH SIDE OF THE CENTER SECTION LINE

- 4) MATTHEW BROWN, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY FOR ROAD NUMBER 327 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 258 TO 260 PETITIONED BY GILBERT C. SWEET AND OTHERS FOR A ROAD IN SECTION 8-16-12 [PACKET 584 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JUNE 8, 1886, WAS ESTABLISHED AS A 30 FOOT AND 40 FOOT WIDE ROAD AS DESCRIED IN THE FIELD NOTES ON JULY 7, 1886 AS NOTED BY T. E. McMILLAN, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON DECEMBER 3, 1886 BY ROLAND LAKIN, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 8-16-12 TO END ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS WEST ON THE CENTER SECTION LINE TO THE STONE HE FOUND AT THE CENTER CORNER OF SECTION 8-16-12 – THIS PORTION OF THE ROAD IS 40 FEET WIDE, 20 FEET EACH SIDE OF THE CENTER SECTION LINE

- 5) **REA PIN—MUST VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY JUST "HEELED-IN" FOR UTILITY USE ONLY!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR** REA BOOK 30 ON PAGE 23 SAYS THAT **THEY SET AN IRON PIN** FOR THE WEST 1/4 CORNER OF SECTION 9-16-12 IN LINE WITH A FENCE TO THE EAST AND A ROAD TO THE WEST, AND AT 2,630.4' NORTH OF THE SOUTHWEST CORNER OF SECTION 9-16-12, THAT THEY ALSO SET.
 - 1) 30' EAST TO A WITNESS PIN BY A FENCE POST

CONTINUED ON PAGE 2

- 6) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 16-12 SHOWS A **REA PIN** AT THE 'SE CORNER NE1/4 SECTION 08-16-12". **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY JUST "HEELED-IN" FOR UTILITY USE ONLY!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
- 1) 30' EAST TO A WITNESS [REA]
- 7) COMMISSIONER'S ROAD JOURNAL BOOK "B", PAGE 98
ON FEBRUARY 11, 1955 A PETITION SIGNED BY RUSSELL SWEET AND OTHERS FOR THE VACATION OF A ROAD IN TOWNSHIP 16-12 WAS PRESENTED TO VERNON E. GRIFFITH, COUNTY CLERK. THE ROAD WAS VIEWED BY THE COUNTY COMMISSIONERS ON MARCH 8, 1955 AND THE FINAL ORDER OF THE BOARD OF COUNTY COMMISSIONERS ON MARCH 8, 1955 VACATED THE FOLLOWING ROAD:
- 1) BEGINNING AT A STONE IN THE ROAD FROM WHICH THE 40 ROD STONE ON THE WEST LINE OF SECTION 8-16-12 BEARS NORTH 75 DEGREES AND NO MINUTES WEST A DISTANCE OF 66 FEET; FROM THIS POINT AND RUNNING EAST VA. NORTH 76 DEGREES AND 10 MINUTES EAST 112.5 FEET; THENCE VA. NORTH 58 DEGREES 10 MINUTES EAST 105 FEET, THIS BEING 20 FEET SOUTH OF A HEDGE FENCE; THENCE EAST ON THE SOUTH SIDE OF HEDGE TO THE 1/2 SECTION LINE; THENCE NORTH 40 RODS TO THE CENTER OF SAID SECTION; THENCE EAST ON THE 1/2 SECTION LINE TO A POINT 428 FEET WEST OF THE EAST LINE OF SAID SECTION 8-16-12, AND THERE ENDING.

WEST QUARTER CORNER 09-16-12