

NORTH 1/4 CORNER SECTION 10, TOWNSHIP 16 SOUTH, RANGE 12 EAST

- 1) ON PAGE 458 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 15" X 12" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 3 & 10-16-12.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.95 CHAINS WEST TO THE 20" X 14" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 3, 4, 9 & 10-16-12
 - 2) 39.95 CHAINS EAST TO THE 23" X 18" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 2, 3, 10 & 11-16-12

- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 23 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 90 TO 92 FOR A PETITION BY SIDNEY PUTMAN AND OTHERS COR A COUNTY ROAD IN TOWNSHIPS 15-12 AND 16-12 [PACKET 128 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JUNE 4, 1879, WAS ESTABLISHED ON JULY 7, 1879, AND WAS RECORDED ON JULY 11, 1879 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF THE SOUTHWEST 1/4 OF SECTION 3-16-12 ON THIS ROAD SURVEY. FROM THE BEGINNING OF SAID ROAD TO THE NORTHWEST CORNER OF THE SOUTHEAST 1/4 OF SECTION 3-16-12 THE ROAD SHALL BE 50 FEET WIDE, AND THE BALANCE OF SAID ROAD IS TO BE 60 FEET WIDE.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS 60 FOOT WIDE ROAD EXTENDS NORTH ON THE 1/2 SECTION LINE TO THE SOUTHWEST CORNER OF THE W1/2 OF THE NE1/4 OF SECTION 3-16-12 AT A TURN TO THE EAST
 - 2) THIS 60 FOOT WIDE ROAD EXTENDS SOUTH ON THE 1/2 SECTION LINE TO THE NORTHEAST CORNER OF THE NW1/4 OF SECTION 22-16-12 AT A TURN TO THE EAST

- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 38, A ROAD SURVEY RECORDED IN SURVEY BOOK "E" ON PAGE 219 DATED FEBRUARY 25, 1902 FOR A COUNTY ROAD IN TOWNSHIP 16-12 FOR D. C. HOUCK, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF THE SOUTHEAST 1/4 OF SECTION 3-16-12 ON THIS ROAD SURVEY
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,318-2/4' EAST TO THE 3" X 12" X 15" STONE HE SET FOR THE SOUTHWEST CORNER OF THE E1/2 OF THE SE1/4 OF SECTION 3-16-12 FOR THE SOUTH END OF THIS ROAD SURVEY
 - 2) 2,637-1/2' EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 3-16-12

- 4) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A ROAD SURVEY FOR ROAD NUMBER 570 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 145 THROUGH 148 BY A PETITION BY D. L. HOUCK AND OTHERS FOR THE VACATION AND RELOCATION OF A ROAD IN SECTION 3-16-12 [PACKET 720 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON FEBRUARY 25, 1902, WAS ESTABLISHED AS A 50 FOOT WIDE ROAD, 25 FEET ON EACH SIDE OF THE LINE SURVEYED, ON MARCH 6, 1902, AND RECORDED ON MARCH 23, 1902 BY ALVA J. SMITH, COUNTY SURVEYOR, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF THE SOUTHEAST CORNER OF SECTION 3-16-12 AT THE END OF THE ROAD THAT WAS VACATED ON THIS ROAD SURVEY.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

HIS INFORMATION IS CONTINUED ON PAGE 2

- 1) 1,318-3/4' EAST TO THE 3" X 12" X 15" STONE HE SET FOR THE SOUTHWEST CORNER OF THE E1/2 OF THE SE1/4 OF SECTION 3-16-12 TO BEGIN THE ROAD RELOCATION SURVEY
 - 2) 2,637-1/2' EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 3-16-12
 - 3) THE ROAD **VACATED** EXTENDS NORTH FOR 1/2 MILE TO THE NORTHWEST CORNER OF THE SE1/4 OF SECTION 3-16-12, THEN EXTENDS EAST FOR 1/4 MILE TO THE STONE AT THE NORTHWEST CORNER OF THE E1/2 OF THE SE1/4 OF SECTION 3-16-12 TO BEGIN THE ROAD **VACATED** ON THIS ROAD SURVEY
- 5) JAMES H. BROSEMER, L.S. 82, IN AN **AGREEMENT SURVEY** THAT SURVEYED AND DIVIDED IN HALF BY **ACREAGE** THAT PART OF THE WEST 1/2 OF SECTION 3-16-12 OWNED AND OCCUPIED BY ROBERT J. & LENA M. LYNCH (E1/2 OF W1/2) AND WILLIAM C. & MARGARET E. LYNCH (W1/2 OF W1/2) FILED IN VOLUME 365, PAGE 627 IN THE REGISTER OF DEEDS OFFICE ON MAY 8, 1979, FOR JOB NUMBER 79-08; DATED APRIL 6, 1979, SHOWS ON HIS DRAWING THAT **HE SET AN 80 D SPIKE** FOR THE SOUTHEAST CORNER OF THE EAST 1/2 OF THE WEST 1/2 OF SECTION 3-16-12 ON THIS **AGREEMENT SURVEY** ALONG EXISTING FENCE LINES.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 1,339.48' WEST TO THE 80 D SPIKE SET FOR THE DIVISION CORNER
 - 2) 2,662.26' WEST TO THE 80 D SPIKE SET FOR THE SOUTHWEST CORNER OF THE W1/2 OF THE W1/2 OF SECTION 3-16-12

NORTH QUARTER CORNER SECTION 10-16-12