

**NORTH 1/16 CORNER NORTHEAST QUARTER OF SECTION 10, TOWNSHIP 16 SOUTH,
RANGE 12 EAST**

- 1) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 38, A ROAD SURVEY RECORDED IN SURVEY BOOK "E" ON PAGE 219 DATED FEBRUARY 25, 1902 FOR A COUNTY ROAD IN TOWNSHIP 16-12 FOR D. C. HOUCK, PRINCIPAL PETITIONER, SAID THAT **HE SET A 3" X 12" X 15" STONE** FOR THE SOUTHWEST CORNER OF THE EAST 1/2 OF THE SOUTHEAST 1/4 OF SECTION 3-16-12 FOR THE SOUTH END OF THIS ROAD SURVEY FOR A 50 FOOT WIDE ROAD LYING 25 FEET EACH SIDE OF THE LINE SURVEYED. HE SET THIS STONE ON LINE AND HALFWAY BETWEEN THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF THE SOUTHEAST 1/4 OF SECTION 3-16-12 AND THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 3-16-12. HE PLACED BROKEN PIECES OF ROCKS IN THE HOLE BESIDE THE STONE.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,318-3/4' WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 3-16-12
 - 2) 1,318-3/4' EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 3-16-12
 - 3) 2,627' NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF THE E1/2 OF THE SE1/4 OF SECTION 3-16-12 TO BEGIN THIS ROAD SURVEY
- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A ROAD SURVEY FOR ROAD NUMBER 570 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 145 THROUGH 148 BY A PETITION BY D. L. HOUCK AND OTHERS FOR THE VACATION AND RELOCATION OF A ROAD IN SECTION 3-16-12 [PACKET 720 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON FEBRUARY 25, 1902, WAS ESTABLISHED AS A 50 FOOT WIDE ROAD, 25 FEET ON EACH SIDE OF THE LINE SURVEYED, ON MARCH 6, 1902, AND RECORDED ON MARCH 23, 1902 BY ALVA J. SMITH, COUNTY SURVEYOR, SAID THAT **HE SET A 3" X 12" X 15" STONE** FOR THE SOUTHWEST CORNER OF THE EAST 1/2 OF THE SOUTHEAST 1/4 OF SECTION 3-16-12 AT THE END OF THE ROAD RELOCATED ON THIS ROAD SURVEY. HE SET THIS STONE ON LINE AND HALFWAY BETWEEN THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 3-16-12 AND THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF THE SOUTHEAST 1/4 OF SECTION 3-16-12.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,318-3/4' WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 3-16-12
- 2) 1,318-3/4' EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 3-16-12
- 3) THIS RELOCATED ROAD EXTENDS NORTH FOR 2,627 FEET TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF THE E1/2 OF THE SE1/4 OF SECTION 3-16-12 TO BEGIN THIS ROAD RELOCATION SURVEY

NORTH SIXTEENTH CORNER NORTHEAST QUARTER 10-16-12