

NORTHWEST CORNER SECTION 11, TOWNSHIP 16 SOUTH, RANGE 12 EAST

- 1) ON PAGE 454 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 23" X 18" X 4"** FOR THE CORNER TO SECTIONS 2, 3, 10 & 11-16-12.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS EAST TO THE 16" X 8" X 6" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 2 & 11-16-12
- 2) 80.00 CHAINS EAST TO THE 24" X 12" X 8" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 1, 2, 11 & 12-16-12

- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 112 RECORDED IN SURVEY BOOK "A" ON PAGE 203 DATED MAY 5, 1869 FOR A SURVEY OF SECTION 2-16-12, TO ESTABLISH THE CENTER CORNER AND THE 1/4 CORNER ON THE NORTHERN BOUNDARY, AND TO REESTABLISH THE 1/4 CORNERS ON THE SOUTHERN AND EASTERN BOUNDARIES OF SECTION 2-16-12, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 2-16-12 ON THIS SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 160 RODS, 5 LINKS NORTH TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 2-16-12
- 2) 320 RODS, 5 LINKS NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 2-16-12
- 3) 158 RODS, 2 LINKS EAST TO THE STONE HE SET FOR THE SOUTH 1/4 CORNER OF SECTION 2-16-12
- 4) 318 RODS, 2 LINKS EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 2-16-12

- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 133 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 118 TO 120 PETITION BY WILLIAM HUFFMAN AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 16-12 [PACKET 375 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON SEPTEMBER 17, 1881, WAS ESTABLISHED AS A 50 FOOT WIDE ROAD ON OCTOBER 5, 1881 AS NOTED BY J. M. GRIFFITH, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON OCTOBER 14, 1881 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 11-16-12 ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 2 MILES TO THE NORTHWEST CORNER OF SECTION 9-16-12 AT THE TERMINUS OF THIS ROAD SURVEY
- 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 1 MILE TO THE NORTHWEST CORNER OF SECTION 12-16-12 TO COMMENCE THIS ROAD SURVEY

- 4) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE LEFT PAGE 234 DATED SEPTEMBER 17, 1881, FOR A ROAD SURVEY IN TOWNSHIP 16-12, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 11-16-12 ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 2 MILES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 9-16-12 AT THE TERMINUS OF THIS ROAD SURVEY
- 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 1 MILE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 12-16-12 TO COMMENCE THIS ROAD SURVEY

- 5) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 70 DATED SEPTEMBER 11, 1883 FOR A ROAD IN TOWNSHIP 16, RANGE 12 FOR JOHN KRELLER, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 10-16-12 TO END THE SECOND ROAD ON THIS ROAD SURVEY. THERE IS NO WIDTH RECORDED ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THE SECOND ROAD EXTENDS WEST ON THE SECTION LINE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 9-16-12 TO BEGIN THE SECOND ROAD ON THIS ROAD SURVEY – [**NOTE:** HE WROTE IN RED THAT THIS SECOND ROAD WAS **NOT** GRANTED – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]
- 6) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 38, A ROAD SURVEY RECORDED IN SURVEY BOOK "E" ON PAGE 219 DATED FEBRUARY 25, 1902 FOR A COUNTY ROAD IN TOWNSHIP 16-12 FOR D. C. HOUCK, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 3-16-12 ON THIS ROAD SURVEY FOR A 50 FOOT WIDE ROAD LYING 25 FEET EACH SIDE OF THE LINE SURVEYED.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 1,318-3/4' WEST TO THE 3" X 12" X 15" STONE HE SET FOR THE SOUTHWEST CORNER OF THE E1/2 OF THE SE1/4 OF SECTION 3-16-12 FOR THE SOUTH END OF THIS ROAD SURVEY
 - 2) 2,637-1/2' WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 3-16-12
- 7) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A ROAD SURVEY FOR ROAD NUMBER 570 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 145 THROUGH 148 BY A PETITION BY D. L. HOUCK AND OTHERS FOR THE VACATION AND RELOCATION OF A ROAD IN SECTION 3-16-12 [PACKET 720 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON FEBRUARY 25, 1902, WAS ESTABLISHED AS A 50 FOOT WIDE ROAD, 25 FEET ON EACH SIDE OF THE LINE SURVEYED, ON MARCH 6, 1902, AND RECORDED ON MARCH 23, 1902 BY ALVA J. SMITH, COUNTY SURVEYOR, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 3-16-12.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 1,318-3/4' WEST TO THE 3" X 12" X 15" STONE HE SET FOR THE SOUTHWEST CORNER OF THE E1/2 OF THE SE1/4 OF SECTION 3-16-12 AT THE SOUTH END OF THIS ROAD SURVEY
 - 2) 2,637-1/2' WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 3-16-12
- 8) JAMES H. BROSEMER, L.S. 82, IN A LAND SURVEY REFERENCE REPORT DATED MAY 16, 1995, FOR A SURVEY FOR MELVIN STANFORD, SURVEY F11001 IN THE SURVEY FILE FOR TOWNSHIP 16-12, AND RECORDED IN VOLUME 491 ON PAGE 301 IN THE REGISTER OF DEEDS OFFICE ON JUNE 7, 1995, TO DETERMINE THE ACREAGE THAT LIES SOUTH OF THE RECENTLY CONSTRUCTED FENCE FROM THE EAST 1/4 CORNER OF SECTION 11-16-12 WEST TO THE WEST LINE OF SECTION 11 THAT LIES NORTH OF THE NORTH LINE OF THE SOUTH 1/2 OF THE SOUTHEAST 1/4 AND THE SOUTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 11-16-12, SAID THAT **HE FOUND THE 4" X 15" GLO LIMESTONE** AT THE NORTHWEST CORNER OF SECTION 11-16-12 FROM RECORD AND FIELD INFORMATION ON FILE IN THE COUNTY ENGINEER'S OFFICE. **HE PLACED A 1/2" REBAR WITH HIS "LS 82" CAP OVER THE CENTER OF THE STONE.**

HIS TIES ARE ON PAGE 3

- 2) 19.0' SOUTH TO A CORNER FENCE POST
- 3) 27.2' NORTH TO A CORNER FENCE POST
- 4) IN LINE WITH A HEDGE TO THE NORTH
- 5) 1.2' EAST TO A LINE OF HEDGE TO THE SOUTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,636.92' EAST TO THE 1/2" REBAR WITH HIS "LS 81" CAP HE SET FOR THE NORTH 1/4 CORNER OF SECTION 11-16-12
- 2) 2,042.11' SOUTH TO THE 6" DIAMETER STEEL FENCE POST HE FOUND
- 3) 2,646.09' SOUTH TO THE GLO STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 11-16-12

NORTHWEST CORNER 11-16-12