

**WEST 1/4 CORNER SECTION 11, TOWNSHIP 16 SOUTH, RANGE 12 EAST**

- 1) ON PAGE 454 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 14" X 10" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 10 & 11-16-12.
  
- 2) JAMES H. BROSEMER, L.S. 82, IN A LAND SURVEY REFERENCE REPORT DATED MAY 16, 1995, FOR A SURVEY FOR MELVIN STANFORD, SURVEY F11001 IN THE SURVEY FILE FOR TOWNSHIP 16-12, AND RECORDED IN VOLUME 491 ON PAGE 301 IN THE REGISTER OF DEEDS OFFICE ON JUNE 7, 1995, TO DETERMINE THE ACREAGE THAT LIES SOUTH OF THE RECENTLY CONSTRUCTED FENCE FROM THE EAST 1/4 CORNER OF SECTION 11 WEST TO THE WEST LINE OF SECTION 11 THAT LIES NORTH OF THE NORTH LINE OF THE SOUTH 1/2 OF THE SOUTHEAST 1/4 AND THE SOUTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 11, SAID THAT **HE FOUND THE 4" X 9" GLO LIMESTONE WITH THE TOP 4" EXPOSED** AT THE WEST 1/4 CORNER OF SECTION 11-16-12 FROM RECORD AND FIELD INFORMATION. **HE PLACED A 1/2" REBAR WITH HIS CAP AT THE CENTER AND EAST SIDE OF THE STONE.**
  - 1) THIS STONE IS IN A NORTH-SOUTH FENCE LINE  
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
    - 1) 603.98' NORTH TO A 6" DIAMETER STEEL POST
    - 2) 2,646.09' NORTH TO THE GLO STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 11-16-12
    - 3) 2,636.08' EAST TO THE COMPUTED POSITION FOR THE CENTER CORNER OF SECTION 11-16-12

WEST QUARTER CORNER 11-16-12