

NORTH 1/4 CORNER SECTION 15, TOWNSHIP 16 SOUTH, RANGE 12 EAST

- 1) ON PAGE 458 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 16" X 14" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 10 & 15-16-12.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.95 CHAINS WEST TO THE 26" X 7" X 7" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 9, 10, 15 & 16-16-12
 - 2) 39.94 CHAINS EAST TO THE 24" X 11" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 10, 11, 14 & 15-16-12

- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 23 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 90 TO 92 FOR A PETITION BY SIDNEY PUTMAN AND OTHERS COR A COUNTY ROAD IN TOWNSHIPS 15-12 AND 16-12 [PACKET 128 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JUNE 4, 1879, WAS ESTABLISHED ON JULY 7, 1879, AND WAS RECORDED ON JULY 11, 1879 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF THE NORTHWEST 1/4 OF SECTION 15-16-12 ON THIS ROAD SURVEY. FROM THE BEGINNING OF SAID ROAD TO THE NORTHWEST CORNER OF THE SOUTHEAST 1/4 OF SECTION 3-16-12 THE ROAD SHALL BE 50 FEET WIDE, AND THE BALANCE OF SAID ROAD IS TO BE 60 FEET WIDE.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS 60 FOOT WIDE ROAD EXTENDS NORTH ON THE 1/2 SECTION LINE TO THE SOUTHWEST CORNER OF THE W1/2 OF THE NE1/4 OF SECTION 3-16-12 AT A TURN TO THE EAST
 - 2) THIS 60 FOOT WIDE ROAD EXTENDS SOUTH ON THE 1/2 SECTION LINE TO THE NORTHEAST CORNER OF THE NW1/4 OF SECTION 22-16-12 AT A TURN TO THE EAST

NORTH QUARTER CORNER 15-16-12