

**NORTH 1/4 CORNER SECTION 16, TOWNSHIP 16 SOUTH, RANGE 12 EAST**

- 1) ON PAGE 462 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 12" X 11" X 6"** FOR THE 1/4 CORNER BETWEEN SECTIONS 9 & 16-16-12.  
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 40.00 CHAINS WEST TO THE 25" X 15" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 8, 9, 16 & 17-16-12
  - 2) 40.00 CHAINS EAST TO THE 26" X 7" X 7" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 9, 10, 16 & 17-16-12
  
- 2) ARTHUR MILLIKEN, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F", ON PAGE 74 DATED NOVEMBER 20, 1883 FOR A ROAD IN TOWNSHIP 16, RANGE 12 FOR B. H. Y. WILBUR, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE** AT THE 1/4 CORNER ON THE NORTH SIDE OF SECTION 16-16-12 TO END THE SECOND ROAD OF THIS ROAD SURVEY FOR A 40 FOOT WIDE ROAD.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) THIS 40 FOOT WIDE ROAD EXTENDS SOUTH ON THE EAST SIDE OF THE 1/2 SECTION LINE FOR ONE MILE TO THE STONE HE FOUND AT THE 1/4 CORNER ON THE SOUTH SIDE OF SECTION 16-16-12 TO END THE SECOND ROAD ON THIS ROAD SURVEY
  
- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY FOR ROAD NUMBER 249 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 582 TO 584 PETITIONED BY B. H. Y. WILBUR AND OTHERS FOR TWO ROADS IN TOWNSHIP 16-12[PACKET 495 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON NOVEMBER 20, 1883, WAS ESTABLISHED AS 40 FOOT AND 60 FOOT WIDE ROADS ON JANUARY 11, 1884 AS NOTED BY JOHN E. JONES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON JANUARY 31, 1884 BY ROLAND LARKIN, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 SECTION CORNER OF SECTION 16-16-12 AT THE TERMINUS OF THE SECOND ROAD ON THIS ROAD SURVEY.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) THIS SECOND 40 FOOT WIDE ROAD EXTENDS SOUTH ON THE EAST SIDE OF THE 1/2 SECTION LINE FOR 1 MILE TO THE STONE HE FOUND AT THE SOUTH 1/4 SECTION CORNER OF SECTION 16-16-12 TO BEGIN THE SECOND ROAD ON THIS ROAD SURVEY. IT WAS NOTED THAT THIS ROAD IS LOCATED ON THE EAST SIDE OF THE SECTION LINE AND THAT THE LAND WAS WHOLLY ON THE LAND OF B. H. Y. WILBUR AND FREELY DONATED FOR ROAD PURPOSES
  
- 4) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 25, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 25 DATED APRIL 3 & 4, 1884 TO SUBDIVIDE THE NORTHWEST AND SOUTHWEST 1/4 OF SECTION 16-16-12 FOR J. E. WALLINGFORD, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 16-16-12 ON THIS **PERMANENT SURVEY**.  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 1,322' WEST TO THE STONE HE SET FOR THE PERMANENT NORTH 1/8<sup>TH</sup> CORNER OF THE NW1/4 OF SECTION 16-16-12
  - 2) 2,644' WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 16-16-12
  
- 5) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JANUARY 15, 2004, FOR PROJECT NUMBER 04002-02, A REPORT OF SURVEY OF A 10.0 ACRE TRACT IN THE SOUTHEAST 1/4 OF SECTION 16-

16-12, SURVEY F16001 IN THE SURVEY FILE FOR TOWNSHIP 16-12, SAID THAT HE EXCAVATED WITH A COUNTY ROAD GRADER AND **HE FOUND A FOSSILIZED 5" X 5" X 22" LIMESTONE MARKED WITH A "4" ON THE SOUTH SIDE** AT THE NORTH 1/4 CORNER OF SECTION 16-16-12. **HE SET A 1/2" X 24" REBAR WITH HIS "LS 752" CAP BELOW THE STONE.**

- 1) **A 5/8" X 24" REBAR WITH A LYON COUNTY CAP WAS SET ON THE SOUTH SIDE CENTER OF THE STONE**
  - 2) 34.7' NNW TO A SPIKE & WASHER IN THE SIDE OF A CORNER FENCE POST
  - 3) 23.63' SW TO THE NEAR FACE OF A PIPE CORNER FENCE POST
  - 4) 58.9' SE TO A SPIKE & WASHER IN A CORNER FENCE POST
  - 5) 20.0' EAST TO THE CENTERLINE TRAVELED WAY OF GRAVEL COUNTY ROAD "R5" TO THE SOUTH
  - 6) 49' EAST TO A LINE OF FENCE TO THE SOUTH – EXTENDED
  - 7) 2.0' WEST TO A LINE OF FENCE TO THE NORTH – EXTENDED
  - 8) 9.5' WEST TO A LINE OF FENCE TO THE SOUTH – EXTENDED
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 5,313.64' SOUTH TO THE KDOT ALUMINUM CAP HE FOUND AT THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 16-16-12

NORTH QUARTER CORNER 16-16-12