

**NORTHWEST CORNER SECTION 18, TOWNSHIP 16 SOUTH, RANGE 12 EAST**

- 1) ON PAGE 82 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 15" X 4"** FOR THE CORNER TO SECTIONS 7 & 18-16-12 ON THE WEST TOWNSHIP BOUNDARY ON DECEMBER 18, 1856.  
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 33.12 CHAINS EAST TO THE 14" X 11" X 4" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 7 & 18-16-12
  - 2) 73.12 CHAINS EAST TO THE 14" X 11" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 7, 8, 17 & 18-16-12
  - 3) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 14" X 13" X 5" LIMESTONE THEY SET FOR THE WEST 1/4 CORNER OF SECTION 18-16-12
  - 4) 80.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 28" X 12" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 18 & 19-16-12
  
- 2) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "E" ON PAGE 155 DATED DECEMBER 6 & 7, 1886 FOR A ROAD IN TOWNSHIP 16-11 FOR D. L. SAYLOR, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 13-16-11 ON THE RANGE LINE ON THE FIRST ROAD ON THIS ROAD SURVEY ON THE RANGE LINE.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) THE FIRST ROAD EXTENDS NORTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 12-16-11 TO BEGIN THE FIRST ROAD ON THIS ROAD SURVEY
  - 2) THE FIRST ROAD EXTENDS SOUTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 25-16-11 TO END THIS FIRST ROAD SURVEY
  - 3) **NOTE:** SEE ROAD RECORD BOOK "C" ON PAGE 372 – THE ROAD WAS GRANTED FOR ONE MILE BETWEEN SECTIONS 13-17-11 AND 18-17-12 – THE BALANCE OF THE ROAD WAS **REJECTED** – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR
  
- 3) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A ROAD SURVEY FOR ROAD NUMBER 355 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 370 TO 372 PETITIONED BY D. L. SAYLORS AND OTHERS COMMENCING AT THE NORTHEAST CORNER OF SECTION 12-16-11, THENCE SOUTH AS NEARLY AS PRACTICABLE ON THE SECTION LINES TO THE SOUTHEAST CORNER OF SECTION 25-16-12, THENCE SOUTH OVER A ROAD ALREADY LOCATED TO THE SOUTHEAST CORNER OF SECTION 12-17-11, THENCE SOUTH AS NEARLY AS PRACTICABLE ON THE SECTION LINES TO THE SOUTHEAST CORNER OF SECTION 25-17-11 [PACKET 604 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON DECEMBER 6, 1886, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 13-16-11 ON THE RANGE LINE. ON JANUARY 5, 1887 THE BOARD OF COUNTY COMMISSIONERS GRANTED THE ROAD FOR ONE MILE BETWEEN SECTIONS 13-17-11 AND 18-17-12, AND THE BALANCE OF THE ROAD WAS **REJECTED** AS NOTED BY T. E. McMILLAN, CHAIRMAN, AND RECORDED ON JANUARY 18, 1887 BY ROLAND LAKIN, COUNTY CLERK.
  
- 4) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN SURVEY NUMBER 179, A **PERMANENT SURVEY** AT THE REQUEST OF JAMES W. WORSTELL TO ESTABLISH THE LINES AND CORNERS OF THE SOUTHEAST 1/4 OF SECTION 14 AND THE NORTHEAST 1/4 OF SECTION 23, ALL IN TOWNSHIP 16, RANGE 11 RECORDED IN SURVEY BOOK "F" ON PAGE 133 DATED JUNE 18 TO JULY 7, 1888, SAID THAT HE DID **NOT** FIND THE STONE AT THE NORTHEAST CORNER OF SECTION 13-16-11 AS HE RAN THE RANGE LINE FROM THE STONE THAT HE FOUND

AT THE NORTHWEST CORNER OF SECTION 7-16-12 TO THE STONE THAT HE FOUND AT THE TOWNSHIP CORNER AT THE SOUTHEAST CORNER OF SECTION 36-16-11.

- 5) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN A ROAD SURVEY FOR ROAD NUMBER 436 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 5 THROUGH 8 PETITIONED BY E. R. MARCY AND OTHERS FOR A ROAD IN TOWNSHIPS 16-11 AND 16-12 [PACKET 676 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON FEBRUARY 8, 1898, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD ON APRIL 9, 1898 AS NOTED BY JACOB JACOB, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, ATTESTED TO BY H. E. PEACH, COUNTY CLERK, AND RECORDED ON DECEMBER 27, 1899 BY MATTHEW BROWN, COUNTY SURVEYOR, APPARENTLY **FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 12-16-11 ON THE RANGE LINE ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 1 MILE TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 12-16-11 TO BEGIN OF THIS ROAD SURVEY, LAYING THE ROAD 20 FEET EACH SIDE OF THE SECTION LINES
- 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 1 MILE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 7-16-12 AT THE TERMINUS OF THIS ROAD SURVEY, LAYING THE ROAD 20 FEET ON EACH SIDE OF THE SECTION LINES

- 6) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 118, A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 199 DATED JANUARY 3, 1905 FOR TWO ROADS ON THE RANGE LINE BETWEEN TOWNSHIP 16, RANGES 11 & 12 FOR J. A. RABOURN, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 7-16-12 ON THE RANGE LINE AT THE TERMINUS OF THE FIRST ROAD ON THIS ROAD SURVEY FOR A 40 FOOT WIDE ROAD.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THE FIRST ROAD APPROVED ON THIS ROAD SURVEY EXTENDS NORTH ON THE SECTION LINE FOR 3/4 OF A MILE TO THE STONE HE FOUND AT 20 FEET WEST OF A FENCE AT THE SOUTHWEST CORNER OF THE NW1/4 OF THE NW1/4 OF SAID SECTION 7, THENCE CONTINUES NORTH ON THE RANGE LINE FOR 719 FEET, THENCE N. 11°15' E. FOR 440-1/2 FEET, THENCE N. 57°50' E. FOR 242-1/2 FEET TO THE SECTION LINE, THENCE WEST ON THE SECTION LINE FOR 233 FEET TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 7-16-12 ON THE RANGE LINE TO BEGIN THE FIRST ROAD APPROVED ON THIS ROAD SURVEY
- 2) THE ROAD PETITIONED EXTENDING SOUTH ON THE RANGE LINE FOR 2 MILES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 30-16-12 WAS **REJECTED**

- 7) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A ROAD SURVEY FOR ROAD NUMBER 598 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 261 THROUGH 264 PETITION BY J. A. RABOURN AND OTHERS FOR A ROAD ON THE RANGE LINE BETWEEN TOWNSHIPS 16-11 AND 16-12 AS FOLLOWS: BEGINNING AT THE NORTHEAST CORNER OF SECTION 12-16-11, THENCE SOUTH ON THE SECTION LINE OR AS NEAR AS PRACTICABLE 4 MILES TO THE SOUTHEAST CORNER OF SECTION 25-16-11 AND THERE ENDING [PACKET 748 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JANUARY 3, 1905, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 7-16-12 ON THE RANGE LINE AT THE TERMINUS OF THE FIRST ROAD APPROVED ON THIS ROAD SURVEY. THE FINAL ORDER OF THE BOARD OF COUNTY COMMISSIONERS

GRANTED THE NORTH MILE AND THE SOUTH MILE ONLY AT 40 FEET WIDE, 20 FEET ON EACH SIDE OF THE LINE AS SURVEYED, ON APRIL 6, 1905 AS NOTED BY W. H. MAPES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, ATTESTED BY W. F. EGGERS, COUNTY CLERK, AND RECORDED ON MAY 9, 1905 BY ALVA J. SMITH, COUNTY SURVEYOR. THE REMAINDER OF THE ROAD AS PETITIONED WAS **REJECTED.**

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 3) THE FIRST ROAD APPROVED ON THIS ROAD SURVEY EXTENDS NORTH ON THE SECTION LINE FOR 3/4 OF A MILE TO THE STONE HE FOUND AT 20 FEET WEST OF A FENCE AT THE SOUTHWEST CORNER OF THE NW1/4 OF THE NW1/4 OF SAID SECTION 7, THENCE CONTINUES NORTH ON THE RANGE LINE FOR 719 FEET, THENCE N. 11°15' E. FOR 440-1/2 FEET, THENCE N. 57°50' E. FOR 242-1/2 FEET TO THE SECTION LINE, THENCE WEST ON THE SECTION LINE FOR 233 FEET TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 7-16-12 ON THE RANGE LINE TO BEGIN THE FIRST ROAD APPROVED ON THIS ROAD SURVEY
- 4) THE ROAD PETITIONED EXTENDING SOUTH ON THE RANGE LINE FOR 2 MILES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 30-16-12 WAS **REJECTED**
  
- 8) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 155 OF TERM 2, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGES 78 & 79 DATED MARCH 4-6, 1909 AT THE ORDER OF LeMONT DeCAMP TO ESTABLISH THE CORNERS AND BOUNDARIES OF LOTS 3 & 4 OF SECTION 1-16-11 AND ANY OTHER CORNERS THAT MIGHT BE NECESSARY IN SAID SECTION TO ESTABLISH THE SAID CORNERS AND BOUNDARIES OF SAID LOTS, SAID THAT **HE FOUND THE CORNER STONE IN GOOD CONDITION** AT THE SOUTHEAST CORNER OF SECTION 12-16-11 ON THE RANGE LINE. HE RAN THE RANGE LINE NORTH TO THE STONE THAT HE SET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 1-16-11 ON THE 3<sup>RD</sup> STANDARD PARALLEL ON THIS **PERMANENT SURVEY.**  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 2,639.6' NORTH ON THE RANGE LINE TO THE ORIGINAL GOVERNMENT STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 12-16-11
  - 2) 5,279.6' NORTH ON THE RANGE LINE TO THE 20" X 10" X 6" LIMESTONE ROCK HE PLANTED FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 1-16-11
  
- 9) IN A FIELD BOOK LABELED "16-12 15-10 16-10 15-11 AND 16-11" STORED IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE, IT SHOWS A **"STONE IN SIGHT"** AT THE NORTHWEST CORNER OF SECTION 18-16-12 ON THE RANGE LINE.
  - 1) 30.4' NE TO A CORNER POST
  - 2) 26.2' SE TO A CORNER POST
  
- 10) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN SURVEY F07001 IN THE SURVEY FILE FOR TOWNSHIP 16-12 DATED SEPTEMBER 9, 1986 FOR PROJECT NUMBER 86084 AND RECORDED IN VOLUME 429 ON PAGE 121 IN THE REGISTER OF DEEDS OFFICE ON DECEMBER 3, 1986, SAID THAT THIS SECTION SHOWS EVIDENCE OF GLO FRAUD, AS THE DISTANCES EAST & WEST AND THE ALIGNMENT ALONG THE EAST SIDE ARE NOT IN HARMONY WITH THE GOVERNMENT NOTES. HE SAID THAT **HE FOUND A 5" X 7" X 21" LIMESTONE PROTRUDING ABOVE THE GROUND** AT THE SOUTHWEST CORNER OF SECTION 7-16-12 ON THE RANGE LINE. HE IDENTIFIED THIS STONE AS THE STONE THAT WAS FOUND BY ALVA J. SMITH IN 1904 AS RECORDED IN SURVEY BOOK "F" ON PAGE 177. THIS SURVEY IS FILED IN VOLUME 429 ON PAGE 121 IN THE REGISTER OF DEEDS OFFICE.

HIS TIES ARE ON PAGE 4

- 1) 20.0' EAST TO A LINE OF FENCE TO THE SOUTH
- 2) 26.5' SE TO A PK NAIL IN A CORNER FENCE POST
- 3) 9.1' WNW TO A PK NAIL IN A CORNER FENCE POST
- 4) 2.5' NORTH TO A LINE OF FENCE TO THE WEST
- 5) 1.0' WEST TO A LINE OF FENCE TO THE NORTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,642.30' NORTH ON THE RANGE LINE TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE WEST 1/4 CORNER OF SECTION 7-16-12
- 2) 2,123.44' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTH 1/4 CORNER OF SECTION 7-16-12
- 3) 3,443.44' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTH 1/16<sup>TH</sup> CORNER OF THE SE1/4 OF SECTION 7-16-12
- 4) 4,763.44' EAST TO THE 1/2" REBAR HE FOUND AT THE SOUTHEAST CORNER OF SECTION 7-16-12

- 11) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 24, 1998, FOR PROJECT NUMBER 97397-02, SAID THAT **HE FOUND THE 5" X 7" LIMESTONE PROTRUDING 9" ABOVE THE SURFACE OF THE GROUND WITH A REBAR ON THE EAST SIDE AT THE NORTHWEST CORNER OF SECTION 18-16-12 ON THE RANGE LINE.** HE IDENTIFIED THIS STONE AS THE STONE THAT WAS FOUND BY ALVA J. SMITH IN 1904 AS RECORDED IN SURVEY BOOK "F" ON PAGE 177.

- 1) 13.0' EAST TO A LINE OF FENCE TO THE SOUTH-EXTENDED
- 2) 25.9' SE TO A CONCRETE NAIL & WASHER IN THE WEST SIDE OF A CORNER FENCE POST
- 3) 9.3' WNW TO A CONCRETE NAIL & SHINER IN THE SOUTH SIDE OF A CORNER FENCE POST
- 4) 1.0' WEST TO A LINE OF FENCE TO THE NORTH-EXTENDED
- 5) 3.0' SOUTH TO A LINE OF FENCE TO THE WEST-EXTENDED

- 12) MARTIN G. LONG, L.S 1081, OF CP ENGINEERS AND LAND SURVEYORS, INC. IN A LAND SURVEY REFERENCE REPORT DATED AUGUST 17, 1998, FOR KDOT PROJECT 56-56 K-1088-01, THE BRIDGE REPLACEMENT ON HILL CREEK ON HIGHWAY 56, PLAT OF SURVEY 97-22S, SURVEY F11001 IN THE SURVEY FILE FOR TOWNSHIP 16-11 FOR PART OF SECTIONS 11, 12, 13, 14, 23 & 24, SAID THAT **HE FOUND THE 5" X 7" GLO LIMESTONE WITH A WITNESS BAR ON THE EAST SIDE AND 0.150 METERS ABOVE GRADE** AT THE NORTHEAST CORNER OF SECTION 13-16-11 ON THE RANGE LINE FROM REFERENCES BY STEVEN S. BROSEMER, L.S. 752, IN 1998 AND BY ALVA J. SMITH IN 1904. HE SENT THE FOLLOWING METRIC TIES:

- 1) 2.840 METERS NW TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
- 2) 7.850 METES SSE TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
- 3) 4.000 METERS EAST TO A FENCE LINE TO THE SOUTH
- 4) 0.400 METERS WEST TO A FENCE LINE TO THE NORTH
- 5) 1.200 METERS NORTH TO A FENCE LINE TO THE WEST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 800.819 METERS WEST TO THE 1/2" REBAR WITH "CORP LS-27" CAP HE SET FOR THE NORTH 1/4 CORNER OF SECTION 13-16-11
- 2) 1,601.638 METERS WEST TO THE 1/2" REBAR WITH "CORP LS-27" CAP HE SET FOR THE NORTHWEST CORNER OF SECTION 13-16-11
- 3) 3,206.299 METERS WEST TO THE 1/2" REBAR HE FOUND AT THE NORTHWEST CORNER OF SECTION 14-16-11
- 4) 805.499 METERS NORTH ON THE RANGE LINE SOUTH TO THE 5/8" CAPPED REBAR HE FOUND AT THE EAST 1/4 CORNER OF SECTION 13-16-11
- 5) 1,610.998 METERS SOUTH ON THE RANGE LINE TO THE 1/2" REBAR WITH "CORP LS-27" CAP HE SET FOR THE SOUTHEAST CORNER OF SECTION 13-16-11

CONTINUED ON PAGE 5

- 13) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED MAY 9, 2012 FOR PROJECT NUMBER 12098-02 FOR SURVEY F06002 IN THE SURVEY FILE FOR TOWNSHIP 16-12, A SURVEY FOR A TRACT IN THE SOUTHWEST QUARTER OF SECTION 6-20-12 FOR BILL MARTIN, SAID THAT **HE FOUND THE 5" X 7" LIMESTONE** AT THE SOUTHWEST CORNER OF SECTION 7-16-12 ON THE RANGE LINE FROM HIS EXISTING REFERENCE TIES ON FILE IN THE COUNTY SURVEYOR'S OFFICE DATED MARCH 1988. HE NOTED THAT HE HAD FIRST FOUND THIS STONE IN 1986, AND HE HAD IDENTIFIED THIS STONE AS THE STONE THAT WAS FOUND BY ALVA J. SMITH IN 1904 AS RECORDED IN SURVEY BOOK "F" ON PAGE 177.
- 1) 1/2" IRON PIN ON THE NORTH SIDE OF THE STONE
  - 2) 3' NORTH TO A LINE OF FENCE TO THE WEST
  - 3) 13' EAST TO A LINE OF FENCE TO THE SOUTH
  - 4) 1' WEST TO A LINE OF FENCE TO THE NORTH
  - 5) 25.9' SW TO A CONCRETE NAIL & WASHER IN THE WEST SIDE OF A CORNER FENCE POST
  - 6) 9.3' WNW TO A CONCRETE NAIL & WASHER IN THE SOUTH SIDE OF A CORNER FENCE POST
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,643.09' NORTH ON THE RANGE LINE TO THE 5/8" REBAR WITH THE REMAINS OF A CAP HE FOUND AT THE SOUTHWEST CORNER OF THE NW1/4 OF SECTION 7-16-12
  - 2) 5,286.18' NORTH ON THE RANGE LINE TO THE 13" BOLT WITH A GEAR ON TOP HE SET FOR THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 6-16-12
  - 3) 10,734.54' NORTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 6-16-12 ON THE 3<sup>RD</sup> STANDARD PARALLEL

NORTHWEST CORNER SECTION 18-16-12