

**NORTH 1/4 CORNER SECTION 22, TOWNSHIP 16 SOUTH, RANGE 12 EAST**

- 1) ON PAGE 457 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 15" X 12" X 3"** FOR THE 1/4 CORNER BETWEEN SECTION 15 & 22-16-12.  
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 40.00 CHAINS WEST TO THE 21" X 10' X 8" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 15, 16, 21 & 22-16-12
  - 2) 40.00 CHAINS EAST TO THE 22" X 12" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 14, 15, 22 & 23-16-12
  
- 2) G. M. WALKER, BRECKENRIDGE COUNTY SURVEYOR FROM 1857 TO 1860, IN SURVEY NUMBER 31 OF THE SECOND TERM RECORDED IN SURVEY BOOK "A" ON PAGES 34 & 35 DATED JUNE 9, 1859 TO ESTABLISH THE CENTER POST AND TO DIVIDE THE SOUTHEAST 1/4 AND THE SOUTHWEST 1/4 OF SECTION 22-16-12, SAID THAT **HE FOUND THE NORTH 1/4 STONE POST** OF SECTION 22-16-12 ON THIS SURVEY.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 40.06 CHAINS SOUTH TO THE STAKE HE SET FOR THE CENTER POST OF SECTION 22-16-12
  - 2) 60.09 CHAINS SOUTH TO THE STAKE HE SET FOR THE W1/4/4 POST OF THE SE1/4 OF SECTION 22-16-12
  - 3) 80.12 CHAINS SOUTH TO THE FOUND STONE SOUTH 1/4 POST OF SEC. 22-16-12
  
- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGES 158 TO 160 [PACKET 311 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] PETITIONED BY B. G. H. WILBUR AND OTHERS FOR A ROAD IN TOWNSHIPS 16-12, 17-11 AND 17-12, SURVEYED AUGUST 27, 1870, ESTABLISHED BY THE ORDER OF THE BOARD OF COUNTY COMMISSIONERS ON SEPTEMBER 5<sup>TH</sup>, 1870 AS A 50 FOOT WIDE ROAD, AND FILED AND RECORDED ON THE 5<sup>TH</sup> DAY OF SEPTEMBER 1870 BY DAVID S. GILMORE, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF THE SOUTHWEST 1/4 OF SECTION 15-16-12 TO BEGIN THIS ROAD SURVEY.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) THIS ROAD EXTENDS WEST ON THE SECTION LINE FOR 1 MILE AND 1,295 FEET TO WITHIN 50 FEET OF THE NORTH 1/2/4 CORNER OF THE NW1/4 OF SECTION 21-16-12 AT A TURN TO THE SOUTH ON THE EAST SIDE OF THE 1/2/4 LINE
  
- 4) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 23 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 90 TO 92 FOR A PETITION BY SIDNEY PUTMAN AND OTHERS COR A COUNTY ROAD IN TOWNSHIPS 15-12 AND 16-12 [PACKET 128 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JUNE 4, 1879, WAS ESTABLISHED ON JULY 7, 1879, AND WAS RECORDED ON JULY 11, 1879 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF THE NORTHWEST 1/4 OF SECTION 22-16-12 ON THIS ROAD SURVEY. FROM THE BEGINNING OF SAID ROAD TO THE NORTHWEST CORNER OF THE SOUTHEAST 1/4 OF SECTION 3-16-12 THE ROAD SHALL BE 50 FEET WIDE, AND THE BALANCE OF SAID ROAD IS TO BE 60 FEET WIDE.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) THIS 60 FOOT WIDE ROAD EXTENDS NORTH ON THE 1/2 SECTION LINE TO THE SOUTHWEST CORNER OF THE W1/2 OF THE NE1/4 OF SECTION 3-16-12 AT A TURN TO THE EAST

- 2) THIS 60 FOOT WIDE ROAD EXTENDS EAST ON THE SECTION LINE TO THE NORTHEAST CORNER OF THE W1/2 OF THE NE1/4 OF SECTION 22-16-12 AT A TURN TO THE SOUTH
- 5) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 108 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 18 TO 20 PETITIONED BY HERBERT MILLER AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 16-12 [PACKET 353 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON MARCH 15, 1881, WAS ESTABLISHED AS A 50 FOOT WIDE ROAD ON ARIL 15, 1881 AT NOTED BY J. M. GRIFFITH, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON MAY 5, 1881 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER THE SOUTHEAST 1/4 OF SECTION 15-16-12 AT THE TERMINUS OF THIS ROAD SURVEY.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES TO THE NORTHEAST CORNER OF THE W1/2 OF THE NE1/4 OF SECTION 21-16-12; THEN CONTINUES SOUTHERLY TO A POINT 1,345 FEET WEST OF THE SOUTHEAST CORNER OF SECTION 21-16-12; THEN EXTENDS EAST ON THE SECTION LINES TO THE SOUTHEAST CORNER OF SECTION 21-16-12; THEN CONTINUES SOUTH ON THE SECTION LINES TO THE NORTHEAST CORNER OF SECTION 33-16-12 TO COMMENCE THIS ROAD SURVEY
- 6) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON LEFT SIDE PAGE 203 DATED MARCH 15, 1881, FOR A ROAD SURVEY IN TOWNSHIP 16-12 APPARENTLY **FOUND THE STONE** AT THE SOUTHWEST CORNER OF THE SOUTHEAST 1/4 OF SECTION 15-16-12 TO END THIS ROAD SURVEY.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THE ROAD EXTENDS 3,960' WEST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF THE WEST 1/2 OF THE NORTHWEST 1/4 OF SECTION 21-16-12 TO AN ANGLE STONE ON THIS ROAD SURVEY

NORTH QUARTER CORNER 22-16-12