

**NORTHWEST CORNER SECTION 22, TOWNSHIP 16 SOUTH, RANGE 12 EAST**

- 1) ON PAGE 457 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 21" X 10" X 8"** FOR THE CORNER TO SECTIONS 15, 16, 21 & 22-16-12.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS EAST TO THE 15" X 12" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 15 & 22-16-12
- 2) 80.00 CHAINS EAST TO THE 22" X 12" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 14, 15, 22 & 23-16-12

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGES 158 TO 160 [PACKET 311 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] PETITIONED BY B. G. H. WILBUR AND OTHERS FOR A ROAD IN TOWNSHIPS 16-12, 17-11 AND 17-12, SURVEYED AUGUST 27, 1870, ESTABLISHED BY THE ORDER OF THE BOARD OF COUNTY COMMISSIONERS ON SEPTEMBER 5<sup>TH</sup>, 1870 AS A 50 FOOT WIDE ROAD, AND FILED AND RECORDED ON THE 5<sup>TH</sup> DAY OF SEPTEMBER 1870 BY DAVID S. GILMORE, COUNTY CLERK, SHOWS ON HIS SURVEY DRAWING THE NORTHWEST CORNER OF SECTION 22-16-12 ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINE TO WITHIN 50 FEET OF THE 1/2/4 CORNER ON THE NORTH SIDE OF THE NW1/4 OF SECTION 21-16-12 AT A TURN TO THE SOUTH ON THE EAST SIDE OF THE 1/2/4 LINE
- 2) THIS ROAD EXTENDS EAST ON THE SECTION LINE TO THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 15-16-12 TO BEGIN THIS ROAD SURVEY

- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 108 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 18 TO 20 PETITIONED BY HERBERT MILLER AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 16-12 [PACKET 353 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON MARCH 15, 1881, WAS ESTABLISHED AS A 50 FOOT WIDE ROAD ON ARIL 15, 1881 AT NOTED BY J. M. GRIFFITH, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON MAY 5, 1881 BY WILLIAM F. EWING, COUNTY CLERK, APPARENTLY **FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 22-16-12 ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS EAST ON THE SECTION LINES TO THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 15-16-12 AT THE TERMINUS OF THIS ROAD SURVEY
- 2) THIS ROAD EXTENDS WEST ON THE SECTION LINES TO THE NORTHEAST CORNER OF THE W1/2 OF THE NE1/4 OF SECTION 21-16-12; THEN CONTINUES SOUTHERLY TO A POINT 1,345 FEET WEST OF THE SOUTHEAST CORNER OF SECTION 21-16-12; THEN EXTENDS EAST ON THE SECTION LINES TO THE SOUTHEAST CORNER OF SECTION 21-16-12; THEN CONTINUES SOUTH ON THE SECTION LINES TO THE NORTHEAST CORNER OF SECTION 33-16-12 TO COMMENCE THIS ROAD SURVEY

- 4) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 70 DATED SEPTEMBER 11, 1883 FOR A ROAD IN TOWNSHIP 16, RANGE 12 FOR JOHN KRELLER, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 15-16-12 TO END THE THIRD ROAD ON THIS ROAD SURVEY. THERE IS NO WIDTH RECORDED ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

HIS INFORMATION IS CONTINUED ON PAGE 2

- 1) THE FIRST ROAD EXTENDS NORTH ON THE SECTION LINE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 16-16-12 TO BEGIN THE THIRD ROAD ON THIS ROAD SURVEY. [**NOTE:** HE WROTE IN RED THAT THIS THIRD ROAD WAS **NOT** GRANTED – WARREN CHIP WOODS, L.S. 6-03, COUNTY SURVEYOR]
  
- 5) ARTHUR MILLIKEN, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F", ON PAGE 74 DATED NOVEMBER 20, 1883 FOR A ROAD IN TOWNSHIP 16, RANGE 12 FOR H. Y. WILBUR, PRINCIPAL PETITIONER, APPARENTLY **FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 22-16-12 ON THE FIRST ROAD OF THIS ROAD SURVEY FOR A 60 FOOT WIDE ROAD. HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) THIS FIRST ROAD EXTENDS WEST ON THE SECTION LINE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 20-16-12 TO BEGIN THE FIRST ROAD ON THIS ROAD SURVEY
  - 2) THIS FIRST ROAD EXTENDS EAST ON THE SECTION LINE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 24-16-12 TO END THE FIRST ROAD ON THIS ROAD SURVEY
  
- 6) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY FOR ROAD NUMBER 249 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 582 TO 584 PETITIONED BY B. H. Y. WILBUR AND OTHERS FOR TWO ROADS IN TOWNSHIP 16-12[PACKET 495 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON NOVEMBER 20, 1883, WAS ESTABLISHED AS 40 FOOT AND 60 FOOT WIDE ROADS ON JANUARY 11, 1884 AS NOTED BY JOHN E. JONES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON JANUARY 31, 1884 BY ROLAND LARKIN, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 22-16-12 ON THE FIRST ROAD ON THIS ROAD ON THIS ROAD SURVEY. HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) THIS FIRST 60 FOOT WIDE ROAD EXTENDS WEST ON THE SECTION LINES FOR 2 MILES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 20-16-12 TO BEGIN THE FIRST ROAD ON THIS ROAD SURVEY
  - 2) THIS FIRST 60 FOOT WIDE ROAD EXTENDS EAST ON THE SECTION LINES FOR 2 MILES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 24-16-12 AT THE TERMINUS OF THE FIRST ROAD ON THIS ROAD SURVEY
  
- 7) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A SURVEY OF SECTIONS 20 & 21-16-12 MADE NOVEMBER 23 THROUGH 25, 1883 AND FILED FOR RECORD ON DECEMBER 5, 1883 IN VOLUME 23 ON PAGE 178 AT THE REGISTER OF DEEDS OFFICE, SURVEY F20008 IN THE SURVEY FILE FOR TOWNSHIP 16-12, SAID THAT **HE SET A LIMESTONE** FOR THE NORTHEAST CORNER OF SECTION 22-16-12 ON THIS SURVEY. HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 19.91 CHAINS WEST TO THE LIMESTONE HE SET FOR THE NORTH 1/8<sup>TH</sup> CORNER OF THE NE1/4 OF SECTION 21-16-12
  - 2) 39.82 CHAINS WEST TO THE LIMESTONE HE SET FOR THE NORTH 1/4 CORNER OF SECTION 21-16-12
  - 3) 79.64 CHAINS WEST TO THE 16" X 12" X 3" LIMESTONE HE SET FOR THE NORTHWEST CORNER OF SECTION 21-16-12
  - 4) 119.77 CHAINS WEST TO THE 12" X 12" X 3" LIMESTONE HE SET FOR THE NORTH 1/4 CORNER OF SECTION 20-16-12
  - 5) 159.80 CHAINS WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 20-16-12

CONTINUED ON PAGE 3

- 8) C. ANSCHUTZ, KDOT SURVEY PARTY CHIEF, IN A REPORT DATED SEPTEMBER 1994 FOR KDOT PROJECT 56-56-K-5378-01, SAID THAT HE CONSIDERED THAT THE NORTHEAST CORNER OF SECTION 21-16-12 WAS **OBLITERATED**. HE RESET THIS CORNER AS SHOWN ON OLD KDOT PLANS FOR PROJECT 50N-29-FAP 419, SECTION "F", DATED 1931. THESE OLD PLANS SHOW A FENCE LINE RUNNING TO THE SOUTH AS BEING 21 FEET EAST OF THE CORNER. HE SAID THAT HE SET THIS CORNER 11.3 FEET SOUTH OF THE OLD 1931 ALIGNMENT AND 1,820.0 FEET WEST OF THE OLD 1931 P. I. BAR HE FOUND AT THE 1931 P. I. STATION 681 + 82.0. **HE SET A 5/8" X 36" REBAR WITH A STANDARD KDOT 2" ALUMINUM CAP STAMPED "NE COR 21-16-12", CENTER PUNCHED AND SET 3 INCHES DEEP, FOR THE NORTHEAST CORNER OF SECTION 21-16-12.**
- 1) 61.00' NW TO A SPIKE & KDOT DISC IN A 30" HEDGE TREE
  - 2) 110.70' NE TO A SPIKE & KDOT DISC IN A 30" HEDGE TREE
  - 3) 64.45' SSE TO A SPIKE & KDOT DISC IN A 35" LOCUST TREE
  - 4) 38.90' SE TO A SPIKE & KDOT DISC IN THE SIDE OF A CORNER FENCE POST
  - 5) 36.80' SW TO A SPIKE & KDOT DISC IN THE TOP OF A FENCE POST
  - 6) 60.50' NNE TO A SPIKE & KDOT DISC IN THE SIDE OF A FENCE POST
  - 7) 21.0' EAST TO AN OLD NORTH-SOUTH FENCE LINE RUNNING TO THE SOUTH AND EXTENDED BACK TO THE NORTH
  - 8) 11.3' NORTH TO THE TRAVELED WAY OF PRESENT U.S. 56 HIGHWAY
- A REFERENCE REPORT BY ROBERT M. SELLEY, L.S. 1195, SHOWS THE FOLLOWING:
- 1) 2,634.15' WEST TO THE KDOT ALUMINUM CAPPED REBAR OVER THE 3/4" PIPE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 21-16-12
  - 2) 5,285.41' WEST TO THE KDOT ALUMINUM CAPPED REBAR OVER THE 1/2" SQUARE REBAR HE FOUND AT THE NORTHEAST CORNER OF SECTION 20-16-12

NORTHWEST CORNER SECTION 22-16-12