

**NORTH 1/4 CORNER SECTION 23, TOWNSHIP 16 SOUTH, RANGE 12 EAST**

- 1) ON PAGE 453 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 11" X 2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 14 & 23-16-12.  
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 39.95 CHAINS WEST TO THE 22" X 12" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 14, 15, 22 & 23-16-12
  - 2) 39.95 CHAINS EAST TO THE 24" X 10" X 8" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 13, 14, 23 & 24-16-12
  
- 2) STATE HIGHWAY COMMISSION SURVEYORS H. L. OAKES, J. L. DOLE AND JOHN REID, FOR PROJECT 50N-29-FAP 419 "F" IN JUNE 1929, SAID THAT **THEY FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 23-16-12 AT 1.2 FEET RIGHT [NORTH] OF STATION 620+76.5. SEE PAGE 26 OF THEIR FIELD NOTES.
  - 1) 44.2' NORTH TO A 3/4" IRON PIPE
  - 2) 58.8' SE TO A 3/4" IRON PIPE
  - 3) 55.2' SOUTH TO A SPIKE IN A FENCE CORNER POST

NORTH QUARTER CORNER 23-16-12